

**Two Workers  
Are Killed  
Every Month  
in Trench  
Collapses!**

**One Cubic Yard  
of Soil Can  
Weigh As Much  
As A Car.**



# AN UNPROTECTED TRENCH IS AN EARLY GRAVE

**Make sure that trenches are protected from cave-ins by:**

- Sloping or benching trench walls, or
- Shoring trench walls with supports, or
- Shielding trench walls with trench boxes.



Photo courtesy of Speed Shore Corp.

**Inspect trenches at the start of each shift and as needed, throughout the workday.**

Provide safe entry and exit through the use of ladders, ramps or stairways.

Know where underground utilities are located before digging.

Keep all equipment, materials and spoil piles at least 2 feet back from trench edges.



Division of Occupational Safety and Health



[www.Lni.wa.gov/Safety](http://www.Lni.wa.gov/Safety)



1-800-423-7233



Washington State Department of  
Labor & Industries

*Other formats for persons with disabilities are available on request. Call 1-800-547-8367. TDD users, call 360-902-5797. L&I is an equal opportunity employer. This poster is based on OSHA poster 3215-08R-11. The Washington State Department of Labor & Industries thanks OSHA for permission to use this poster.*

PUBLICATION FSP0-912-000 [04-2013]