



Final Cost Benefit and Least Burden Analyses

Construction Cranes Rulemaking: Phase 1

**Construction Cranes Certification
WAC 296-155-529 through WAC 296-155-53214**

**Operator Qualifications and Certification
WAC 296-155-533 and WAC 296-155-53300**

July 2008

For a printed copy of this report, contact:

Name: Cindy Ireland

Address: PO Box 44620, Olympia WA 98504-4620

E-mail: mooc235@lni.wa.gov

Phone: (360) 902-5522

You can also view this report on the Department of Labor and Industries' website at

<http://www.lni.wa.gov/safety/topics/atoz/default.asp?KWID=378>

Table of Contents

CONCLUSION 1

PURPOSE OF THIS ANALYSIS 1

BACKGROUND 1

 HISTORY OF EXISTING RULES 1

 REASON FOR THIS RULE PROPOSAL 2

SCOPE OF ANALYSIS 3

COMPARISON OF THE CURRENT AND PROPOSED RULES..... 4

BASELINE FOR ANALYSIS 6

ANALYSIS OF COSTS & BENEFITS 6

LEAST BURDENSOME ANALYSIS 15

APPENDIX 1: SURVEY INSTRUMENT 20

APPENDIX 2: DATA COLLECTION DISPOSITION 39

APPENDIX 3: RISK CLASSES USED IN SURVEY SAMPLE FRAME – PHASE 1. 40

APPENDIX 4: ESTABLISHES ORIGIN OF PROPOSED RULE PROVISIONS. 42

APPENDIX 5: REFERENCES 114

 SUMMARY OF CRANE ACCIDENTS 116

Conclusion

The Washington State Department of Labor and Industries (L&I) determines on a preliminary basis that the benefits of the proposed rule are greater than the costs and that we are proposing the least burdensome alternative of the rule.

The proposed rule is expected to provide net benefits of approximately \$0.7 million per year. L&I estimates the approximate annual benefit is \$1.9 million per year. L&I estimates the annual cost of the proposed rule is about \$1.2 million. The net for each year is approximately \$0.7 million.

The proposed rule reduces the cost of operator training, thus reducing the burden of the rule and the law. This part of the proposed rule is what makes this proposal the least burdensome version of the rule.

During the preliminary stages of this analysis, L&I requested feedback on portions of the analysis. This final analysis includes all additional information provided.

Purpose of this analysis

L&I is proposing to amend chapter 296-155 WAC, Safety Standards for Construction Work, Part L. The Administrative Procedures Act (RCW 34.05.328 (1)(d) & (e)) requires two types of analyses before adopting a significant legislative rule – a cost-benefit analysis and a least burdensome alternative analysis. This report provides the results of these analyses and shows the potential impacts associated with the proposed rule.

Background

History of existing rules

In August 1994, while working to repair the ceiling of the Kingdome in Seattle, WA, a crane was used to lift two construction workers to sandblast the ceiling. The basket carrying the two workers fell 250 feet, sending the 32-year old and 39-year old men to their deaths, when the crane arm broke near its top. As it dropped, the basket struck the cab carrying the crane operator. The operator suffered head injuries as a result of the accident. As a result of this incident, the Governor mandated that the L&I establish the Washington State Cranes Safety Association and adopt regulations for the use of attached platforms with cranes. Both of these mandates were completed by L&I.

On November 16, 2006, at a downtown Bellevue construction site, a 217 foot tall tower crane collapsed, injuring the crane operator and killing a 31-year man in the living room of his top floor apartment. At approximately 7:30 PM, the crane operator was preparing to shut the crane down for the night. The tower crane was being rotated clockwise from the North towards the North East when the failure began to occur. The tower crane operator stated that he saw the end of the jib (crane boom) start to rise up, as if he had just released a heavy load from the rigging. He then felt the crane sway and start to tilt. The top of the crane fell toward the South, striking three buildings before crashing into the roof of the apartment building.

After the catastrophic tower crane accident that happened in Bellevue in November 2006, the legislature passed engrossed substitute house bill (ESHB) 2171 which was signed in April 2007. This bill requires the department to establish by rule a crane certification program for cranes used in the construction industry and to establish requirements that must be met to be considered a qualified crane operator.

L&I conducted two sets of statewide stakeholder meetings to gather input from the industry for use in developing draft rules. The first set of statewide stakeholder meetings was held in July 2007. Following these meetings, L&I decided to break the rulemaking into two phases.

The first phase would adopt rules for the construction crane certification program, qualification requirements for crane certifiers, and operator qualifications, as outlined in RCW 49.17.400 through 440.

The second phase is currently being drafted and will update the requirements that employers must follow with regard to inspection, maintenance and operation of cranes used in the construction industry. The second phase will also include updates to our current rigging and personnel lifting requirements.

The concerns in Washington pertaining to crane safety are consistent with views expressed globally in recent decades. Häkkinen (1993) discusses the evolution in crane safety throughout the 1970s and 1980s. Recent studies at the international¹ national², and state level³, indicate a strong correlation between: 1) increased operator training and experience and crane safety; and 2) consistent maintenance and inspection and crane safety. Though there are occasional “accidents”, the vast majority of crane accidents can be directly attributed to either operator error or the condition of the crane.

Reason for this rule proposal

This rulemaking is in response to Chapter 27, Laws of 2007 (Engrossed Substitute House Bill 2171) requiring L&I to have rules relating to certification of crane inspectors, construction cranes, and crane operators. The legislature intends to promote the safe condition and operation of cranes used in construction work by establishing certification requirements for construction cranes. The legislature intends that standards for safety of construction cranes and for certification of personnel operating cranes in construction work be established.

Construction cranes are not currently regulated in this state. In November, 2006, a tower crane collapsed and killed an individual in Bellevue, Washington and damaged several buildings in the area. Damages ranged in the hundreds of thousands of dollars. In the aftermath of this event, structural problems were found and corrected in other cranes. This proposal will prevent these types of accidents from happening. Cranes that are appropriately manufactured, assembled, inspected, maintained, and used are generally safe. Construction is growing in this state and it is important for public health, safety and welfare that this proposal is adopted.

¹ Häkkinen, 1993; Ross 1996

² Saruda, et al 1999; Yow, et al, 2000; McCann, 2003; Paques, 1993.

³ ENR September 2, 2002 and ENR December 8, 2003.

Scope of Analysis

This analysis evaluates the provisions of the proposed rule over which L&I had discretion. L&I has attempted to quantify the cost and benefits of the proposed rule changes based on anticipated compliance requirements of the proposed rule and without the proposed rule. The analysis uses existing rules and laws as the baseline for the analysis.

Data Collection Methodology for the Cranes Rulemaking

L&I uses surveys to obtain cost estimates from employers for economic analyses. For this proposed rule, L&I developed a survey with the help of the Cranes small stakeholder group to obtain cost estimates from employers. L&I contracted the Gilmore Research Group to do the survey due to its length and complexity. The survey instrument is in Appendix 1: Survey Instrument. The data collection process evolved through three phases. The results from this process are presented in Appendix 2: Data Collection Disposition. In addition, below are descriptions of the phases throughout the process.

Phase 1: The Construction Sample

L&I designed a sample frame of 10,010 firms based on the risk class of the employers.⁴ Risk class is directly associated with an account number and payroll systems and is likely to be an accurate assessment of the employer's business size and activity. Chapter 19.85 RCW, Regulatory Fairness Act, requires L&I to assess costs to small business based on the 2-digit NAICS code. Therefore L&I selected firms in NAICS Sector 23, Construction. The risk classes are included as Appendix 3: Risk Classes Used in Survey Sample Frame – Phase 1. These risk classes were selected as a result of a technical review by the L&I Cranes Safety unit. As a check on the selection process, industry description information was requested in the survey instrument.

Gilmore randomly selected 370 firms to contact as a starting group from the list provided by L&I. During a progress report, Gilmore and L&I discovered that survey responses predominantly indicated that the firms being surveyed did not use cranes as part of their business. Hoping a different set of firms might yield different results, Gilmore chose additional and different firms from the L&I-provided list, and collected data from 491 firms during this phase.

Unfortunately, the trend continued. L&I expected to have responses covering a random sample of 7,000 cranes. The response was too small. It is not possible to get meaningful results with the respondent pool generated. L&I reassessed the sample selection method.

Phase 2: Non-Random Targeted Crane Owner and User Selection

L&I decided to more specifically target firms that use cranes, rather than relying on industry codes to target them. To do this, L&I did the following:
Worked with the Associated General Contractors (AGC) to develop a list of survey candidates
Contacted Coast Cranes to develop a list of firms that use cranes in their business

⁴ The risk classes are included as Appendix 1: Risk Classes Used in Survey Sample Frame – Phase 1. These risk classes were selected as a result of a technical review by the L&I Cranes Safety unit.

Reviewed our L&I project stakeholder list and selected firms likely to use cranes in their business.

As a result of this process, L&I provided Gilmore 325 entries for contacts. After removing duplicative information between the lists, this approach yielded the names of 285 firms that do, or are highly likely to, use cranes in their business activities. Gilmore reviewed the list of names and removed 79 firms that had already provided data in Phase 1.

Phase 3: Follow-Up to Non-Random Targeted Crane Owner and User Selection

While Phase 2 produced 160 additional results from firms that use cranes, the most valuable new information was that the expectation of 7,000 Cranes in Washington was wrong.

L&I does not maintain a current count of construction cranes in Washington state. However, L&I did contact businesses to develop an estimate of the number of cranes in Washington state. In Department of Licensing indicated the number of mobile cranes, currently registered and exempt, in Washington state as of July 2008 is 1,383. This information is used to compare the survey results and determine the credibility of the survey responses.

Also, many of the responses indicated that the firms subcontracted work involving cranes. L&I contacted individual firms to discuss the common work methods of the industry. As a result of these conversations, L&I developed a third list of firms. After Gilmore reviewed this list and removed firms that had provided data in either Phase 1 or Phase 2, the list provided 109 additional firms.

Comparison of the Current and Proposed Rules

Current rule requirements

The key elements of the proposed rule are not required by existing construction cranes rules: operator certification, inspector certification, and annual crane certification.

Description of proposed changes:

WAC 296-155-53102(1)

A requirement is being added which would require an applicant to submit an application and successfully complete written examinations developed and administered by the department or its authorized representative. This requirement is necessary in order to have capable and knowledgeable individuals accredited to certify construction cranes in the state of Washington.

WAC 296-155-53102(2)(c)

A requirement is being added that all applicants must demonstrate at least five years of crane related experience, of which two years must be actual crane inspection activities. The other three years may include experience in duties such as a crane operator, crane mechanic, crane shop foreman, crane operations supervisor, or rigging specialist. Related education may be substituted for the three years of related experience at a ratio of two years of education for one year of experience. This requirement is necessary to ensure that applicants seeking certification possess the knowledge and experience necessary to conduct construction crane certification inspections in the state of Washington.

WAC 296-155-53102(4)

A requirement is being added that the applicant must successfully complete the written examinations in order to be an accredited crane certifier. The first written examination will test the applicant's general knowledge of operation, testing, inspection and maintenance requirements, and the duties and recordkeeping responsibilities required by the proposed rules. The other written examinations will test the applicant's knowledge of the safe operating and engineering principles and practices with respect to specific crane types subject to the accreditation, including inspection and proof loading requirements. This requirement is necessary to ensure that applicants seeking certification possess the knowledge and experience necessary to conduct construction crane certification inspections in the state of Washington.

WAC 296-155-53108(1)

A requirement is being added that an accreditation will be valid for three years and that crane certifiers must complete forty hours of crane related training every three years. This requirement is necessary to ensure that all applicants possess knowledge of the changes happening within the industry.

WAC 296-155-53108(2)

A requirement is being added that an application for renewal must demonstrate she/he has been actively inspecting cranes during their prior accreditation period. An applicant is considered active if he/she has certified at least twenty-one cranes during their three year accreditation period. If the applicant certified cranes in another state, then that applicant must provide documentation showing they were active during their accreditation period. An applicant who has not certified at least twenty-one cranes during the accreditation period may take the written exams to become recertified. This requirement is necessary to ensure skills and knowledge are maintained to accurately conduct inspections.

WAC 296-155-53108(3)

A requirement is being added that all applicants for renewal must successfully complete the written examinations every six years. This requirement is necessary in order that all applicants possess knowledge of the changes happening within the industry.

WAC 296-155-53204(1)(u)

A requirement is being added that a portable fire extinguisher must be installed in the cab or at the machinery housing of an articulating boom crane. This requirement is necessary in order to provide a safe means to extinguish any potential fire. Also, this is a current requirement for all of the other types of cranes covered by this rule.

WAC 296-155-53214(1)(a)

A requirement is being added that if a crane contacts an energized power line the certification becomes invalid. In order to reinstate the crane operating certification, the crane owner must have a certified crane inspector re-inspect the crane to ensure the crane was not damaged by the contact, and, if necessary, conduct additional proof load tests. Any deficiencies identified by the certified crane inspector must be corrected prior to reinstatement of the crane operating

certificate. This requirement is necessary in the event of contact an energized line. The crane could possibly be damaged and not operating in a safe condition.

Baseline for Analysis

The baseline for this analysis is the existing rules and laws. In Appendix 4 there is a crosswalk displaying where the new requirements came from including laws, other rules, and DOSH. New requirements coming directly from the law or from an existing rule will not be evaluated in this cost benefit analysis. New requirements where L&I had some discretion are evaluated.

Analysis of Costs & Benefits

Costs

L&I estimates the annual cost of the proposed rule ranges from \$1,200,000 to \$1,275,000. The total estimated cost for a 9 year cycle of training is \$10.9 to \$11.5 million.

Table 1. Cost Summary

Costs by Category	Item	Unit Costs Low	Unit Costs High	Number of Workers Per Firm	Low Total	High Total
Certifiers Accreditation						
-Experience	Existing effort					
-Application	Time Cost	\$ 5,082		4.45	\$ 22,617	
-Training (Non-Union)	Fee	\$ 325	\$ 1,295		\$ 325	\$ 1,295
-Exam	Fee	\$ 215	\$ 275	4.45	\$ 957	\$ 1,224
3 Year Renewal						
-Experience	Time Cost	\$ 5,082		4.45	\$ 22,617	
-Application	Time Cost	\$ 2,541		4.45	\$ 11,308	
-Continuing education	Training Cost	\$ 826		4.45	\$ 3,676	
6 Year Renewal Exam	Fee, Time Cost	\$ 5,297	\$ 5,357	4.45	\$ 23,573	\$ 23,840
Recertifying Cranes	2 cases only	1500	3000		\$ 3,000	\$ 6,000
	Crane Time	150			\$ 2,400	
Sub Total W/O Recertification					\$86,194	\$91,045
Annual Effect Per firm					\$9,577	\$10,116
9-year total for all Firms					\$10,860,475	\$11,471,638
Annual Aggregate Effect					\$1,206,720	\$1,274,627

For this final analysis L&I requested information from owners of cranes on their experience with the cost of training, specifically data on employee turnover and the need to provide training to new staff. We received no additional information in response. The current analysis represents the best available data.

These costs come from:

Training: The training and accreditation costs are evaluated as a 9 year cycle since the requirements for renewal at 3 and 6 years differ. There are approximately 45,720 crane and tower crane operators nation wide and approximately 900⁵ in Washington working in this job class. The average employment per firm of operators is 28.8. In addition small companies on average hire .6 new inexperienced operators per year and large companies hire about 25 new inexperienced operators each year. The average across all firms is 5 new inexperienced operators each year per firm. Employees will need to be trained for certifying cranes. Survey results indicate that most small companies expect to use their own operators to certify their cranes. Most of the larger owners expect to hire outside certifiers. Further, the small companies appear to specialize and dominate the mobile cranes. Finally, the small companies appear to pay their experienced employees more than the large companies.

Cranes will also need to be re-certified if they make contact with energized power lines.

Wages are a large factor in estimating the costs. Based on the reported wages in the survey, operator wages range from \$20 to \$31 per hour depending on how experienced the employees are. Inspector wages range from \$24.40 per hour for inexperienced inspectors to \$63 per hour for inspectors that already meet L&I’s qualifications.

Average Wages by Experience	Wages
Number of Firms	126
Inspectors meeting qualifications	\$63.53
Less Experienced Crane Certifiers	\$24.40
Inexperienced Operators	\$20.94
Experienced Operators	\$30.77

The number of employees affected by the additional accreditation training is probably overstated. L&I summed the average number of employees for companies that already have experienced inspectors with the average number of new hires for companies that expect to hire experienced inspectors and the number of new hires for companies that expect to hire and train inexperienced inspectors. **It is unlikely that most companies will do all 3 of these things. Therefore the stated accreditation costs may be twice the actual costs.**

Cost for Accredited Crane Certifiers to Obtain Initial Accreditation

(Required by proposed WAC 296-155-53100)

⁵ The survey covered 273 of these workers but no independents.

There are no current or existing rules that require construction crane certifiers or that require certifiers to obtain accreditation through L&I in order to inspect construction cranes. Since there is no accreditation at this moment, firms will follow a variety of strategies: an average of 2.3 employees per firm already qualify, an average of 2 will be put through training, and an average of .15 inexperienced employees will be hired and trained for this work.

Step 1: Obtain Required Experience

Compliance Process:

In order to be eligible for accreditation, the applicant must have 5 years of crane-related experience, 2 years experience performing crane inspections and 3 years related experience as a crane operator, crane mechanic, crane shop foreman, crane operations supervisor, or rigging specialist. The 2 years actual inspection experience can be obtained by conducting the periodic and frequent inspections which employers are currently required to perform under WAC 296-155-525(2)(d) or the annual inspection of hoisting equipment required under WAC 296-155-525(2)(e). The additional 3 years experience may be obtained by working in any of the identified positions. In addition, related education may be substituted for the 3 years related experience at a rate of 2 years education for every 1 year of actual experience.

Potential Compliance Costs for this Process:

L&I anticipates that costs associated with this provision will be the staff time needed to obtain the necessary amount of experience required or, if education is substituted for experience, the costs for crane related classes identified in the rule. However, the costs to obtain actual experience will be minimal given that an individual can obtain this experience by working for an employer and conducting the periodic and frequent inspections required by existing rules. The person must be competent but does not need to be accredited under WAC 296-155-525(2)(d). Therefore under this existing requirement, it benefits the employer as well as the employee to obtain this on-the-job-training. In addition, related experience can be obtained by working for an employer in one of the identified trades.

Estimated Cost: \$0

For example the union provides free training to members in the hoisting trade at the Operating Engineers Regional Training Center in Ellensburg. They require 6,000 hours of work done in this trade.

Step 2: Application for Accreditation

Compliance Process:

This proposed rule requires applicants to submit a written application and a resume setting forth the knowledge, training and experience the applicant possesses working with cranes. The application/resume must contain verifiable references.

Potential Compliance Costs:

L&I anticipates that costs associated with this provision will be the staff time needed to complete the application document and resume. Further they will probably study for the exam and get ready to take it before applying.

Estimated Cost: \$5,082 per applicant

Experienced applicants earn on average \$63 per hour. Employers may or may not pay employees to apply. However, application is a cost of the rule. L&I assumes that the applicants will not apply until they are ready to take the exams. In addition to the on-the-job-training above, if the application process, studying for the exam, and taking the exam requires 80 hours of time per applicant, the cost would be \$5,082 per applicant per exam. There are approximately 45,720 crane and tower crane operators nation wide and approximately 900 in Washington working in this job class. Within maritime crane operations, over 60% can do inspections. In our survey it could be as low as 1/3. However, it is unlikely that all of these individuals will pursue accreditation to conduct certification inspections on construction cranes.

Step 3: Successfully Complete Written Examinations

Compliance Process:

L&I will be developing between 2 and 6 types of written examinations for applicants. All applicants must successfully pass a written examination that will test the applicant's knowledge of the requirements of WACs 296-155-529 through 296-155-53214. In addition, the applicant will be required to successfully pass a written exam testing the applicant's knowledge on safe operating and engineering principles and other practices for the specific types of cranes the applicant wishes to certify, separated out by Mobile Cranes, Tower Cranes, Articulating Cranes, Derricks, and Overhead Cranes.

Potential Compliance Costs: \$325 to \$1,295 per class and \$215 to \$275 per exam

L&I anticipates that costs associated with this provision will be the staff time necessary to prepare for and take the exam (which are included in Step 2 above) and payment of the fees required for each individual exam. The exam fees are anticipated to range from \$215 to \$275. Some companies offer training for these exams, which range in cost from \$325 to \$1,295 and may include trial exams.

Cost for Certifiers to Renew Accreditation

(Required by proposed WAC 296-155-53108)

There are no current or existing rules that require construction crane certifiers or that require certifiers to obtain accreditation or renew accreditation through L&I in order to inspect construction cranes.

Step 1: Obtain Required Experience

Compliance Process:

In order to qualify for renewed accreditation, construction crane certifiers must have conducted at least 21 crane certification inspections during their three year accreditation period OR retake the certification examinations required by WAC 296-155-53100.

Potential Compliance Costs: \$0 to \$5,082 per person

L&I anticipates that there will be no cost associated with the requirement to conduct at least 21 crane inspections during the three year accreditation period. Given that certifiers will be paid for this inspection work, if they are called for inspections, then there will be no cost associated with obtaining this experience.

However, certifiers who opt to retake the exams in lieu of the 21 crane inspections, will be required to pay the exam fees to retake the exams. The costs associated will be the staff time necessary to prepare for and take the exam and payment of the fees required for each individual exam. The fees are anticipated to range from \$215 to \$275.

Employers may or may not pay employees to apply. However, application is a cost of the rule. L&I assumes that applicants will not apply until they are ready to take the exams. In addition to the on-the-job-training above, if the application process, studying for the exam, and taking the exam requires 80 hours of time per applicant, the cost would be \$5,082 per applicant per exam.

Step 2: Obtain Required Education

Compliance Process:

In order to qualify to apply for renewed accreditation, construction crane certifiers will need to complete 40 hours of continuing education in crane related courses approved by the Department during the 3 year accreditation period.

Potential Compliance Costs:

L&I anticipates that the costs associated with this provision will be the staff time to take these courses and the course registration fees.

Estimated Cost: \$826 per applicant plus \$2,541 for the 40 hours

40 hours is a cost \$2,541 per applicant plus a possible cost of \$826 per renewal per applicant. L&I assumes some of the applicants will obtain this training free through the union. These costs are part of union dues but the training is a cost to the union. Others may obtain training from professional schools with fees ranging from \$325 to \$1,295.

Step 3: Application for Renewal

Compliance Process:

Accredited construction crane certifiers must renew their certification through L&I every 3 years.

Potential Compliance Costs: Cost Included above.

L&I anticipates that the cost associated with this provision will be the staff time required to prepare renewal application.

Step 4: 6 year Renewal, Successfully Complete Written Examinations

Compliance Process:

At a minimum, every six years, or for the second 3 year renewal, the crane certifiers must re-take and successfully pass the certification examinations required by WAC 296-155-53100 for every type of crane they wish to inspect and certify.

Potential Compliance Costs: \$5,279 to \$5,357.

L&I anticipates that costs associated with this provision will be the staff time necessary to prepare for and take the exam and payment of the fees required for each individual exam. The fees may range from \$215 to \$275. In addition to the on-the-job-training above, if the application process, studying for the exam, and taking the exam requires 80 hours, the cost will be \$5,082 per applicant per exam.

Recertification of crane following hitting power line

(Required by proposed WAC 296-155-53214)

There are no current or existing rules that require construction crane owners to certify their construction cranes. As a result, current rules also do not require a certification re-inspection if the crane makes contact with a power line.

Compliance Process:

Crane operating certificates (valid for 1 year) will automatically be invalidated if any part of the crane makes contact with an energize power line. In order to have the crane certification reinstated, crane owners must have all crane components re-inspected by an accredited crane certifier with no findings of deficiencies. If the accredited crane certifier identifies deficiencies during this re-inspection, the crane owner must correct all identified deficiencies and have this verified by the crane certifier before the crane certification can be reinstated. In addition, if the crane certifier determines during re-inspection that the crane must also be proof load tested, the crane must also have a proof load test successfully completed.

Worker Time Assumption:

Some employers may have their own employees do this as part of their accreditation experience requirements which are listed above. This cost should then not be counted in both places. However, some will hire a private party to recertify the crane. These costs are reported to range from \$1,500 to \$3,000. L&I has assumed that this cost will apply.

Crane Time Cost:

Until it is recertified and possibly repaired, the crane will be out of service. This time is unknown because only 2 respondents reported having made contact with power lines. L&I is

using 8 hours as a place holder and a cost of \$150 per hour as an estimated replacement lease rates.

For this final analysis L&I requested information from owners of cranes on their experience with this issue, specifically data on the frequency of striking live wires as well as the cost of load testing and inspection. As L&I received no further input, the current estimates represent the best available data.

Potential Total Compliance Costs: \$3,000 to \$6000 for 2 incidents and \$2,400 for replacement rentals. This does not include the cost of repairs.

Benefits

The law created the potential for benefits from reduced accidents. In writing the proposed rule, L&I has attempted to reduce some of the possible training costs implied by the 2,000 hour limit without significantly reducing the increased safety benefits.

L&I estimates the benefit of reduced training costs are approximately \$19 million and the benefit of reduced mortality is \$260,000.

L&I estimates the approximate annual benefit is \$1.9 million per year.

Crane Operator Qualifications for Certification

(Required by proposed WAC 296-155-53300)

There are no current or existing rules that contain operator experience requirements in order for the crane operator to be a qualified operator. However the law requires construction crane operators to have up to 2,000 hours of experience. Without the rule, crane operators could be required to obtain 2,000 hours of experience. The law therefore creates both the increases in cost from training and any benefits from training. The rule sets a variety of hours of experience which are less than 2,000 hours. The rule creates a cost reduction or benefit by setting the hours of experience required based on the size and type of crane. It may also create a foregone benefit in the form of voiding the reduced accidents which 2,000 hours of training might have created.

Compliance Process:

Operators are expected to obtain a specific amount of actual operating experience/training and related experience, by crane type and capacity, in order to become a qualified operator. These requirements are set forth in Table 1 below.

Table 2. Crane Operator Experience

Crane Type	Number of Hours of Actual Crane Operating Experience	Number of Hours of Crane Related Experience
(1) Mobile Cranes		
(a) Lattice Boom Crawler Cranes (LBC)	300 tons and above 1000 Hours	300 tons and above 1000 Hours

	Under 300 tons 500 Hours	Under 300 tons 500 Hours
(b) Lattice Boom Truck Cranes (LBT)	300 tons and above 1000 Hours Under 300 tons 500 Hours	300 tons and above 1000 Hours Under 300 tons 500 Hours
(c) Large Telescopic Boom Cranes (Swing Cab) (TLL)	Over 130 tons 750 Hours Over 40 tons to 130 tons 250 Hours 40 tons and under 40 Hours	Over 130 tons 750 Hours Over 40 tons to 130 tons 250 Hours 40 tons and under 40 Hours
(d) Small Telescopic Boom Cranes (Fixed Cab)(TSS)	15 tons and above 40 Hours Under 15 tons 20 Hours	15 tons and above 40 Hours Under 15 tons 20 Hours
(e) Articulating Boom Cranes	20 Hours	20 Hours
(2) Tower Cranes		
(a) Hammerhead	500 Hours	500 Hours
(b) Luffer	500 Hours	500 Hours
(c) Self-Erecting	50 Hours	50 Hours
(3) Overhead Cranes		
(a) Cab Operated	40 Hours	40 Hours
(b) Pendant/Remote	40 Hours	40 Hours
(4) Derricks	20 Hours	500 Hours
<p>Hours of actual crane operating experience. For all cranes: time while the operator is at the controls of the crane; and/or has direct control of that crane; and/or a combination of operating hours within the same crane type. For mobile cranes: it also includes time while installing/removing boom sections, luffing boom, jib, extending and retracting outriggers/stabilizers, leveling crane, and replacing hoisting rope. For tower cranes: it includes time while jumping (increasing the height of the tower/mast).</p> <p>Note: Additional actual crane operator experience may account for crane related experience.</p> <p>Hours of crane related experience: Time as a signalman/bellman, oiler, crane mechanic, crane inspector, formal classroom training, crane simulator operation, and a combination of operating hours on other categories of cranes.</p>		

Potential Reduced Compliance Costs: \$19 million, or spread over a 10 year period, \$1.9 million per year. L&I anticipates that the cost associated with this provision will be the wage paid to the operator trainee throughout the time needed to obtain necessary hours of experience. While operators will need to reapply, they will not need to redo the experience. L&I assumes the employees will tend to stay in the work once they have their training and has assumed the cost would therefore be spread over at least 10 years of service.

Mobile Cranes: \$18.5 million

Tower Cranes:	\$125 thousand
Overhead Cranes:	\$369 thousand
Derricks:	\$0

This estimate is based on the year 1 cost savings given the difference between the law and the rule in terms of training time, and the savings in training time given the reported actual current levels of experience.

For this final analysis, L&I requested information from owners of cranes on their experience with the cost of training, specifically data on employee turnover and the need to provide training to new staff. As L&I received no further input, the current estimates represent the best available data.

Lives Saved

L&I anticipates there will be a reduction in the number and type of accidents as a result of compliance with the proposed rules and the law. This will result from reduced effects of crane accidents including reduced property damage, injury, equipment damage, emergency response, road closures, investigations, and power outages. Current data does not allow quantifying all of these benefits. However, L&I does have information on national mortality rates per 100,000 workers per 10 year period.

Benefit of lives saved: \$2.6 million every 10 years

The expected gain over an average 10-year period would be a 20% reduction in the typical 1.89 mortalities. About 20% of the fatal accidents are due to crane or tower crane failure. The crane inspections required by the proposed rules are assumed here to reduce mortality from this source. This would have a 10-year value of \$2.6 million, assuming a value of statistical-life of \$7 million, and an average annual value of \$260,000.

Operator error creates 80% of the loss. However, L&I has reduced training requirements from those in the law, therefore, any gain from additional operator training by comparison to current levels would be due to the law and not to the rule. It therefore cannot be counted as a benefit of the rule.

Net Benefits

The net benefit of the rule is estimated at over \$0.7 million per year.⁶ The estimated annual net benefits are equal to the benefit (\$1.9 million) minus the cost (\$1.2 million).

- + L&I estimates the approximate annual benefit is \$1.9 million per year.
- L&I estimates the annual cost of the proposed rule is about \$1.2 million.
- = The net for each year is approximately \$0.7 million.

⁶ The benefits and costs are treated as annual for the net benefit comparison because some of the costs have a 9 year cycle, the mortality calculations are based on a 10 year average, and the cost of experience is spread over the career of an employee.

Least Burdensome Analysis

RCW 34.05.328(1)(e) requires L&I to “determine, after considering alternative versions of the rule and the analysis required under (b), (c), and (d) of this subsection, that the rule being adopted is the least burdensome alternative for those required to comply with it that will achieve the general goals and specific objectives stated under (a) of this subsection.”

The table below presents requirements of the proposal and the alternative requirements considered.

Requirement	Rationale	Alternative Requirements
<p>WAC 296-155-53102(1) A requirement is being added which would require an applicant to submit an application and successfully complete written examinations developed and administered by the department or its authorized representative. L&I has provided a grace period for maritime and other qualified crane certifiers to ensure an adequate number of certifiers are available to meet the needs of the industry. This requirement is necessary in order to have an adequate number of capable and knowledgeable individuals accredited to certify construction cranes in the state of Washington.</p>	<p>This requirement was specifically requested by stakeholders during the statewide stakeholder meetings. Additional details in this requirement were developed in collaboration with the small stakeholder group. This small stakeholder group was comprised of business and labor representatives including representatives from the Associated General Contractors (AGC), International Union of Operating Engineers, Independent Business Association (IBA), Truss Manufacturers Association, Sichelsteel Cranes, Coast Cranes, Morrow cranes, business and labor representatives from the electrical industry, and currently certified maritime crane inspectors.</p>	<p>L&I considered not creating a grace period for maritime and other qualified certifiers. After consideration, L&I determined that the grace period would provide additional time for individuals who planned to obtain the required certification and would ensure that the industry had enough qualified certifiers to meet their needs. Per proposed WAC 296-155-53100(2) and (3), the grace period would expire on January 1, 2012 or when the individual’s maritime certification expires, whichever is the earliest. However, the proposed rule allows the individual to continue inspecting construction cranes until January 1, 2012 if the individual renews their maritime certification.</p> <p>Stakeholders suggested that L&I</p>


Requirement	Rationale	Alternative Requirements
		<p>require certifiers to meet the same qualification criteria for crane operators. After consideration, L&I determined that it was not necessary for crane certifiers to meet the operator qualification requirements.</p>
<p>WAC 296-155-53102(2)(c) A requirement is being added that all applicants must demonstrate at least five years of crane related experience, of which two years must be actual crane inspection activities. The other three years may include experience in duties such as a crane operator, crane mechanic, crane shop foreman, crane operations supervisor, or rigging specialist. Related education may be substituted for related experience at a ratio of two years of education for one year of experience up to three years. This requirement is necessary in order to have applicants with knowledge and experience being accredited in the state of Washington.</p>	<p>This requirement was mirrored after the California State Plan (CAL-OSHA) requirements for crane certifiers. Title 8 CA Code of Regulations, §344.61(2).</p>	<p>L&I considered adopting the OSHA maritime requirement of 10-years of experience. After consideration, L&I determined that 5 years of crane-related experience was sufficient.</p> <p>L&I considered requiring various levels of experience ranging from 10 years to 5 years. After consideration, L&I determined that 5 years of crane-related experience was sufficient.</p>
<p>WAC 296-155-53102(4) A requirement is being added that the applicant must successfully complete the written examinations in order to be an accredited crane certifier. The first written examination will include a general knowledge of operation, testing, inspection and maintenance requirements, and the duties and recordkeeping responsibilities required by this rule. The other written examinations will include safe operating and engineering principles and practices with respect to specific crane types</p>	<p>This requirement was mirrored after the California State Plan (CAL-OSHA) requirements for crane certifiers. Title 8 CA Code of Regulations, §344.61(4)(e).</p>	<p>L&I considered the development of additional exams by breaking the crane type out by capacity (tonnage). After consideration, L&I determined that exams provided by crane type were sufficient.</p> <p>L&I considered requiring the inspectors to take exams for all of the crane types regardless of what types</p>

Requirement	Rationale	Alternative Requirements
<p>subject to the accreditation, including inspection and proof loading requirements. This will result in the minimum of 2 examinations per inspector and a maximum of 6 exams. This requirement is necessary in order to have accredited crane certifiers that have the knowledge and experience to certify cranes in the state of Washington.</p>		<p>of cranes the inspector planned to inspect. After consideration, L&I determined that requiring examination for the type of crane the inspector planned to inspect was sufficient.</p>
<p>WAC 296-155-53108(1) A requirement is being added that an accreditation will be valid for three years and that crane certifiers must complete forty hours of crane related training every three years. This requirement is necessary to ensure that all applicants are current with the changes happening within the industry.</p>	<p>The requirement for renewing every three years was mirrored after the California State Plan (CAL-OSHA) requirements for crane certifiers. Title 8 CA Code of Regulations, §344.64.</p> <p>Stakeholders requested L&I require crane certifiers complete crane related continuing education in order to re-certify. L&I and the small stakeholder group developed the requirement that crane certifiers take 40 hours of continuing education every 3 years.</p>	<p>L&I considered requiring additional continued education. After consideration, L&I determined 40 hours of continued education was sufficient.</p> <p>L&I considered requiring reapplication for accreditation at more frequent intervals than 3 years. After consideration, it was determined that reapplication at 3 years was sufficient.</p>
<p>WAC 296-155-53108(2) A requirement is being added that an application for renewal must be filed with the department not less than 60 days prior to expiration of the accredited crane certifier’s certification, providing the applicant has been actively inspecting cranes during their prior accreditation period An applicant is considered active if he/she has certified at least twenty-one cranes during their accreditation period. If the applicant certified cranes in another state, then that applicant must provide documentation</p>	<p>This requirement was added in consultation with the small stakeholder group to ensure that cranes certifiers maintain skills and knowledge to accurately conduct inspections.</p>	<p>L&I considered requiring additional inspections to be completed to be considered “active.” After consideration, L&I determined 21 inspections was sufficient.</p> <p>Based on stakeholder requests, L&I considered requiring exams every 3 years instead of every 6 years. After consideration, L&I determined an</p>

Requirement	Rationale	Alternative Requirements
<p>showing they were active during their accreditation period. An applicant who has not certified at least twenty-one cranes during the accreditation period may take the written exam to become recertified. This requirement is necessary to ensure skills and knowledge are maintained to accurately conduct inspections.</p>		<p>accreditation period of 6 years was sufficient.</p>
<p>WAC 296-155-53108(3) A requirement is being added that all applicants for renewal must successfully complete the written examinations every six years. This requirement is necessary in order that all applicants are current with the changes happening within the industry.</p>	<p>The requirement for successfully completing the written examinations every six years was mirrored after the California State Plan (CAL-OSHA) requirements for crane certifiers. Title 8 CA Code of Regulations, §344.64.</p>	<p>L&I considered requiring annual renewal for accreditation of the crane certifiers. After consideration, L&I determined that completing the written examination every six years was sufficient.</p> <p>L&I considered bi-annual renewal for accreditation of the crane certifiers. After consideration, L&I determined that completing the written examination every six years was sufficient.</p>
<p>WAC 296-155-53204(1)(u) A requirement is being added that a portable fire extinguisher must be installed in the cab or at the machinery housing of an articulating boom crane. This requirement is necessary in order to provide a safe means to extinguish any potential fire. Also, this is a current requirement for all of the other types of cranes covered by this rule.</p>	<p>L&I, in consultation with the small stakeholder group, added this requirement to ensure consistency across all crane types. All other crane types are required by ANSI to have a portable fire extinguisher on the crane.</p>	<p>L&I believes the failure of ANSI to include this as an articulating boom crane requirement was an oversight since all other cranes must have a fire extinguisher.</p>
<p>WAC 296-155-53214(1)(a) A requirement is being added that if a crane comes</p>	<p>The requirement to re-inspect a crane after contact with an energized line derives from</p>	<p>Based on stakeholder request, L&I originally considered several other</p>

Requirement	Rationale	Alternative Requirements
<p>in contact with an energized line the certification becomes invalid. This requirement is necessary in the event of contact an energized line. The crane could possibly be damaged and not operating in a safe condition.</p>	<p>standard manufacturer’s recommendations. In addition, stakeholders requested this provision.</p>	<p>reasons to invalidate a crane certification other than connection with an energized line. Some of these included:</p> <p>Lightning strikes;</p> <p>Any repair or modification that effects the safe operation of the equipment such as modifications or additions involving a safety device or operator aid, critical part of a control system, power plant, braking system, load-sustaining structural components, load hook, or in-use operating mechanism or capacity; or</p> <p>Other deficiencies identified by a qualified person.</p>

Appendix 1: Survey Instrument



Washington State Department of Labor & Industries

Division of Occupational Safety and Health

2008 Crane Rulemaking Survey

Responses to this survey are anonymous and confidential

Introduction:

The purpose of this survey is to determine any costs your business may incur due to the adoption of the proposed crane rule. Your answers will also help us determine how the proposed rule could impact businesses of different types and sizes.

There are five sections in this survey:

- Section 1: General questions about your business as a whole
- Section 2: Questions to answer if your business employs crane operators
- Section 3: Questions to answer if your business owns cranes
- Section 4: Questions to answer if your business employs crane inspectors
- Section 5: Questions to answer if your business uses cranes

Each section will ask you questions that will help us determine how these rules might affect your business.

You may not need to fill out all sections. For example, if your company owns cranes and employs crane operators but does not actually operate the cranes, you would fill out Section 1, Section 2 and Section 3. On the other hand if your company uses cranes, but does not own any and does not employ and crane operators or crane inspectors, then you would fill out Section 1 and Section 5 only.

Please answer the questions the best you can. If you do not have the exact information, use your best estimate, or leave the response blank. In order for your cost data to be included in the economic analysis of this rule, the survey must be filled out and returned in the included postage-paid envelope by May 16, 2008.

If you have any questions about the proposed rule or the survey, please contact:

Cindy Ireland

Safety and Health Specialist
Division of Occupational Safety and Health
Department of Labor and Industries
(360) 902-5522

Section 1: GENERAL QUESTIONS ABOUT YOUR BUSINESS

1a. During 2007, what was the maximum number of full-time workers your business employed?

_____ full-time workers (*if none, enter 0*)

1b. During 2007, how many total hours did your part-time and/or seasonal employees work?

_____ hours (if none, or if you don't employ part-time or seasonal workers, enter 0)

1c. Please check the **one** industry name that most closely describes your business. If more than one of these industries fits your business, please select the one that represents the largest part of your business:

Construction
<input type="checkbox"/> Construction of buildings
<input type="checkbox"/> Heavy and civil engineering construction
<input type="checkbox"/> Specialty trade contractors
Manufacturing
<input type="checkbox"/> Electrical equipment, appliance, and component manufacturing
Mining
<input type="checkbox"/> Support activities for mining
Real estate and rental and leasing
<input type="checkbox"/> Rental and leasing services
Utilities
<input type="checkbox"/> Utilities
Wholesale trade
<input type="checkbox"/> Merchant wholesalers, durable goods
<input type="checkbox"/> Merchant wholesalers, nondurable goods

1d. Does your firm own cranes, use cranes, employ crane operators or employ crane inspectors in any area of the construction industry? Please do not include service trucks with mobile lifting devices designed specifically for use in the power line and electrical service industry or handling associated materials to be installed or removed from utility poles in any of your responses. The rule language does not apply to this equipment.

Yes: Please continue with the rest of the survey.

No: Thank you for providing the information above. You have completed the survey. Please mail the survey in the postage-paid envelope included in your packet.

Section 2: CRANE OPERATORS

CRANE AND DERRICK OPERATORS, GENERAL QUESTIONS

If you do not employ any crane or derrick operators, please go to the next section, "Crane Owners".

2. How many operators of any type of crane or derrick do you expect to need to hire in the following years?

2008: _ operators (please include any operators already hired this year)

2009: _ operators

2010: _ operators

3. On average, how many hours a day do each of your operators operate cranes?
_____ hours per operator per day

4. When you hire new crane operators that have no experience operating cranes, how much do you pay them per hour?

\$ _____ per hour

5. When you hire new crane operators that are experienced crane operators and that require no additional training by you, how much do you pay them per hour?

\$ _____ per hour

Please answer the questions in the following sub-sections about the crane operators you employ, including how many operators you employ for each type of crane and how many crane operators you think you will need to hire in the next three years.

For the questions below, crane-related experience means time as a signal man/bellman, oiler, crane mechanic, crane inspector, formal classroom training, crane simulator operation, and a combination of operation hours on this or other categories of cranes.

CRANE OPERATORS, MOBILE CRANES

6a. Do you employ mobile crane operators?

Yes → How many? __

No → Please go to 'Crane Operators, Tower Cranes'

MOBILE CRANES—PLEASE WRITE "0" IF NONE
--

6b. Lattice Boom Crawler Cranes—300 ton capacity and above
--

MOBILE CRANES—PLEASE WRITE “0” IF NONE

How many operators do you currently employ that operate these cranes?
_____ (if none, enter "0")

How many of the operators you employ have both **1,000 hours** of actual crane operating experience on lattice boom crawler cranes of any capacity and an *additional 1,000 hours* of crane-related experience?
_____ operators (if none, or if you do not employ crane operators, enter "0")

We need to know how many operators of lattice boom crawler cranes of 300 ton capacity and above you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:

2008: _ new, *untrained* operators 2008: _ new, *trained* operators
2009: _ new, *untrained* operators 2009: _ new, *trained* operators
2010: _ new, *untrained* operators 2010: _ new, *trained* operators

When you hire untrained operators for lattice boom crawler cranes of 300 ton capacity and above, how many hours do you train the operator before allowing them to operate the crane without supervision?
_____ hours of training

6c. Lattice Boom Crawler Cranes, under 300 ton capacity

How many operators do you currently employ that operate these cranes?
_____ (if none, enter "0")

How many of the operators you employ have both **500 hours** of actual crane operating experience on lattice boom crawler cranes of any capacity and an *additional 500 hours* of crane-related experience?
_____ operators (if none, or if you do not employ crane operators, enter "0")

We need to know how many operators of lattice boom crawler cranes of capacity under 300 tons you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:

2008: _ new, *untrained* operators 2008: _ new, *trained* operators
2009: _ new, *untrained* operators 2009: _ new, *trained* operators
2010: _ new, *untrained* operators 2010: _ new, *trained* operators

MOBILE CRANES—PLEASE WRITE “0” IF NONE
<p>When you hire untrained operators for lattice boom crawler cranes of capacity under 300 tons, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
<p>6d. Lattice Boom Truck Cranes, capacity 300 tons and above</p>
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 1,000 hours of actual crane operating experience on lattice boom truck cranes of any capacity and an <i>additional 1,000 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of lattice boom truck cranes of capacity 300 tons and above you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators</p> <p>2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators</p> <p>2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for lattice boom truck cranes of capacity 300 tons and above, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
<p>6e. Lattice Boom Truck Cranes, capacity under 300 tons</p>
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 500 hours of actual crane operating experience on lattice boom truck cranes of any capacity and an <i>additional 500 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>

MOBILE CRANES—PLEASE WRITE “0” IF NONE

We need to know how many operators of lattice boom truck cranes of capacity under 300 tons you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:

2008: _ new, *untrained* operators 2008: _ new, *trained* operators
2009: _ new, *untrained* operators 2009: _ new, *trained* operators
2010: _ new, *untrained* operators 2010: _ new, *trained* operators

When you hire untrained operators for lattice boom truck cranes of capacity under 300 tons, how many hours do you train the operator before allowing them to operate the crane without supervision?

_____ hours of training

6f. Large telescopic boom cranes (swing cab), capacity 130 tons or above

How many operators do you currently employ that operate these cranes?

_____ (if none, enter "0")

How many of the operators you employ have both **750 hours** of actual crane operating experience on large telescopic boom cranes (swing cab) of any capacity and an *additional 750 hours* of crane-related experience?

_____ operators (if none, or if you do not employ crane operators, enter "0")

We need to know how many operators of large telescopic boom cranes (swing cab) of capacity 130 tons or above you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:

2008: _ new, *untrained* operators 2008: _ new, *trained* operators
2009: _ new, *untrained* operators 2009: _ new, *trained* operators
2010: _ new, *untrained* operators 2010: _ new, *trained* operators

When you hire untrained operators for large telescopic boom cranes (swing cab) of capacity 130 tons or above, how many hours do you train the operator before allowing them to operate the crane without supervision?

_____ hours of training

6g. Large telescopic boom cranes (swing cab), capacity between 40 and 130 tons

How many operators do you currently employ that operate these cranes?

_____ (if none, enter "0")

MOBILE CRANES—PLEASE WRITE "0" IF NONE
<p>How many of the operators you employ have both 250 hours of actual crane operating experience on large telescopic boom cranes (swing cab) of any capacity and an <i>additional 250 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of large telescopic boom cranes (swing cab) of capacity between 40 and 130 tons you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators 2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators 2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for large telescopic boom cranes (swing cab) of capacity between 40 and 130 tons, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
<p>6h. Large telescopic boom cranes (swing cab), capacity under 40 tons</p>
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 40 hours of actual crane operating experience on large telescopic boom cranes (swing cab) of any capacity and an <i>additional 40 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of large telescopic boom cranes (swing cab) of capacity under 40 tons you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators 2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators 2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for large telescopic boom cranes (swing cab) of capacity under 40 tons, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
<p>6i. Small telescopic boom cranes (fixed cab), including boom trucks, capacity 15 tons or above</p>

MOBILE CRANES—PLEASE WRITE “0” IF NONE
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 40 hours of actual crane operating experience on small telescopic boom cranes (fixed cab), including boom trucks, of any capacity and an <i>additional 40 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of small telescopic boom cranes (fixed cab), including boom trucks, of capacity 15 tons or above you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators</p> <p>2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators</p> <p>2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for small telescopic boom cranes (fixed cab), including boom trucks, of capacity 15 tons or above, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
<p>6j. Small telescopic boom cranes (fixed cab), including boom trucks, capacity under 15 tons</p>
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 20 hours of actual crane operating experience on small telescopic boom cranes (fixed cab), including boom trucks, of any capacity and an <i>additional 20 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of small telescopic boom cranes (fixed cab), including boom trucks, of capacity under 15 tons you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators</p> <p>2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators</p> <p>2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>

MOBILE CRANES—PLEASE WRITE “0” IF NONE
When you hire untrained operators for small telescopic boom cranes (fixed cab), including boom trucks, of capacity under 15 tons, how many hours do you train the operator before allowing them to operate the crane without supervision? _____ hours of training
6k. Articulating Boom Cranes
How many operators do you currently employ that operate these cranes? _____ (if none, enter "0")
How many of the operators you employ have both 20 hours of actual crane operating experience on articulating boom cranes and an <i>additional 20 hours</i> of crane-related experience? _____ operators (if none, or if you do not employ crane operators, enter "0")
We need to know how many operators of articulating boom cranes you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year: 2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators 2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators 2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators
When you hire untrained operators for articulating boom cranes, how many hours do you train the operator before allowing them to operate the crane without supervision? _____ hours of training
The proposed rule will require articulating boom cranes to be equipped with a fire extinguisher with a basic minimum extinguishing rating of 10 BC in the cab or at the machinery housing. How many articulating cranes do you own that currently meet this qualification? _ cranes

CRANE OPERATORS, TOWER CRANES

- 7a. Do you employ tower crane operators?
- Yes → How many? __
 - No → Please go to 'Crane Operators, Overhead or Bridge Cranes'

TOWER CRANES—PLEASE WRITE “0” IF NONE
7b. Hammerhead Cranes

TOWER CRANES—PLEASE WRITE “0” IF NONE
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 500 hours of actual crane operating experience on hammerhead cranes and an <i>additional 500 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of hammerhead cranes you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators</p> <p>2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators</p> <p>2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for hammerhead cranes, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
<p>7c. Luffer Cranes</p>
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 500 hours of actual crane operating experience on luffer cranes and an <i>additional 500 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of luffer cranes you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators</p> <p>2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators</p> <p>2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>

TOWER CRANES—PLEASE WRITE “0” IF NONE
<p>When you hire untrained operators for luffer cranes, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
<p>7d. Self-Erecting Tower Cranes</p>
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 50 hours of actual crane operating experience on self-erecting tower cranes and an <i>additional 50 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of self-erecting tower cranes you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators</p> <p>2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators</p> <p>2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for self-erecting tower cranes, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>

CRANE OPERATORS, OVERHEAD OR BRIDGE

8a. Do you employ overhead or bridge crane operators?

- Yes → How many? __
- No → Please go to 'Derrick Operators'

Overhead or Bridge—PLEASE WRITE “0” IF NONE
<p>8b. Cab-Operated Cranes</p>
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>

Overhead or Bridge—PLEASE WRITE "0" IF NONE
<p>How many of the operators you employ have both 40 hours of actual crane operating experience on cab-operated cranes and an <i>additional 40 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of cab-operated cranes you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators 2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators 2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for cab-operated cranes, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>
8c. Pendant/Remote Cranes
<p>How many operators do you currently employ that operate these cranes?</p> <p>_____ (if none, enter "0")</p>
<p>How many of the operators you employ have both 40 hours of actual crane operating experience on pendant/remote cranes and an <i>additional 40 hours</i> of crane-related experience?</p> <p>_____ operators (if none, or if you do not employ crane operators, enter "0")</p>
<p>We need to know how many operators of pendant/remote cranes you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year:</p> <p>2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators 2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators 2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators</p>
<p>When you hire untrained operators for pendant/remote cranes, how many hours do you train the operator before allowing them to operate the crane without supervision?</p> <p>_____ hours of training</p>

DERRICK OPERATORS

9a. Do you employ derrick operators?

Yes → How many? __

No → Please go to 'Section 3: Crane Owners'

DERRICKS—PLEASE WRITE “0” IF NONE
9b. Derricks
How many of the operators you employ have both 20 hours of actual crane operating experience on derrick cranes and an <i>additional 500 hours</i> of crane-related experience? _____ operators (if none, or if you do not employ crane operators, enter "0")
We need to know how many operators of derrick cranes you think your business will need to hire in 2008, 2009 and 2010 and how many of these new operators you predict will need training to meet the requirements in the paragraph above. Please enter the number of new operators you think you will need to hire in the next three years, including any operators already hired this year: 2008: _ new, <i>untrained</i> operators 2008: _ new, <i>trained</i> operators 2009: _ new, <i>untrained</i> operators 2009: _ new, <i>trained</i> operators 2010: _ new, <i>untrained</i> operators 2010: _ new, <i>trained</i> operators
When you hire untrained operators for derricks, how many hours do you train the operator before allowing them to operate the derrick without supervision? _____ hours of training

Section 3: CRANE OWNERS

MOBILE CRANES

10. Does your business own mobile cranes?

- Yes → How many? __
- No → Please go to the next section, 'Tower Cranes'

If your business owns mobile cranes please answer the following questions about how many mobile cranes of each type your company owns:

MOBILE CRANES	# of Cranes Owned (if none, enter '0')
Lattice Boom Crawler Cranes—300 ton capacity and above	
Lattice Boom Crawler Cranes, under 300 ton capacity	
Lattice Boom Truck Cranes, capacity 300 tons and above	
Lattice Boom Truck Cranes, capacity under 300 tons	
Large telescopic boom cranes (swing cab), capacity 130 tons or above	
Large telescopic boom cranes (swing cab), capacity between 40 and 130 tons	
Large telescopic boom cranes (swing cab), capacity under 40 tons	
Small telescopic boom cranes (fixed cab), including boom trucks, capacity 15 tons or above	
Small telescopic boom cranes (fixed cab), including boom trucks, capacity under 15 tons	
Articulating Boom Cranes	
The proposed rule will require articulating boom cranes to be equipped with a fire extinguisher with a basic minimum extinguishing rating of 10 BC in the cab or at the machinery housing. How many articulating cranes do you own that currently meet this qualification?	

TOWER CRANES

11. Does your business own tower cranes?

- Yes → How many? __
- No → Please go to the next section, 'Overhead or Bridge Cranes'

If your business owns tower cranes please answer the following questions about how many tower cranes of each type your company owns:

TOWER CRANES	# of Cranes Owned (if none, enter '0')
Hammerhead Cranes	
Luffer Cranes	
Self-Erecting Tower Cranes	

OVERHEAD OR BRIDGE CRANES

12. Does your business own overhead or bridge cranes?

- Yes → How many? __
- No → Please go to the next section, 'Derricks'

If your business owns overhead or bridge cranes please answer the following questions about how many overhead or bridge cranes of each type your company owns:

OVERHEAD OR BRIDGE CRANES	# of Cranes Owned (if none, enter "0")
Cab-Operated Cranes	
Pendant/Remote Cranes	

DERRICKS

13a. Does your business own derricks?

- Yes → How many? __
- No → Please go to the next section, 'Other Types of Cranes'

13b. How many derricks does your business own? __derricks

OTHER TYPES OF CRANES

14. How many cranes not listed above does your company own? __ cranes (if none, enter "0")

SECTION 5: CRANE INSPECTORS

15a. Do you any of your employees inspect cranes? Yes: please continue with question 15b.

No: please go to the next section, "Crane Usage".

15b. How many of your employees conduct crane inspections? ___ employees

15c. If you own cranes, do you plan to use your own inspectors to perform crane inspections? If you do not own cranes, please continue with question 15d.

Yes: please continue with question 15d.

No: please go to the next section, "Crane Usage".

CRANE INSPECTORS—PLEASE WRITE "0" IF NONE

15d. Crane Inspector Qualifications and Training

Under the proposed rule, in order to be eligible for the inspector certification process, an inspector must have 5 years of crane-related experience, including:

2 or more years inspecting cranes

up to 3 years of related experience, including experience as a crane operator, crane mechanic, shop foreman, operations supervision, and rigging specialist

2 years of related education can be substituted for 1 year of related experience

How many of your current employees meet the above requirements? _____ employees

On average, how much does your company pay inspectors that meet the above requirements?

\$ _____ per hour

We need to know how many crane inspectors you think your business will need to hire in 2008, 2009 and 2010 and how many of these new inspectors you predict will need training to meet the requirements in the paragraph above. Please enter the number of new inspectors you think you will need to hire in the next three years, including any inspectors already hired this year:

2008: _ new, *untrained* inspectors 2008: _ new, *trained* inspectors

2009: _ new, *untrained* inspectors 2009: _ new, *trained* inspectors

2010: _ new, *untrained* inspectors 2010: _ new, *trained* inspectors

When you hire untrained crane inspectors, how many hours do you currently train the inspector before allowing them to inspect a crane without supervision?

_____ hours of training

On average, how much does your company pay untrained inspectors per hour?

\$ _____ per hour

How many of your company's inspectors do you expect will go through the inspector certification process?

_____ employees

Of these employees, how many meet the requirements listed under 15c above?

_____ employees

15e. In the table below, for each inspector your company employs, place an "x" in the box under each type of cranes that each inspector is qualified to inspect. (if you have more than 10 inspectors please copy page and continue)

Inspector #	Mobile Cranes	Tower Cranes	Overhead Cranes	Derrick Cranes
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				

15f. Do any of your inspectors currently participate in continuing education?
 Yes: please continue with question 15g. No: please go to question 15i.

15g. On average, how many hours of continuing education units (CEUs) do each of your inspectors participate in annually?
 _____ hours

15h. Through what vendors do your inspectors participate in continuing education?

15i. How many of your inspectors do you anticipate will be conducting at least 21 crane inspections during each three-year period following initial certification?
 _____ inspectors

SECTION 4: CRANE USAGE

16a. Do you use cranes in your business operations?
 Yes: Please continue the survey with question 16b.
 No: Your survey is complete—please return it in the postage-paid envelope as soon as possible

16b. Will the employee conducting the inspection of a given crane also be the only employee qualified to repair or modify that same crane?
 Yes No

16c. Do you currently have a crane inspector inspect the tower crane and tower crane assembly parts after reconfiguring the boom, jib, or counter-jib? Yes No

16d. How many times per year do you reconfigure your crane after initial erection?
 _____ times per year

16e. How many times per year do any of your cranes contact a power line? _____ times per year

16f. How many times per year do any of your cranes become overloaded? _____ times per year

16g. Under which of the following circumstances do you currently, or would you if the circumstance arose, have your cranes inspected? Please check all that apply.

- after initial erection of the crane
- after overloading the crane. when *not* directed to overload the crane by the manufacturer or a registered professional engineer and when *not* when proof-load testing the crane
- after contacting a power line
- after any modification or repair of a load bearing part, including the boom, jib, or counter-jib
- other, please specify: _____

16h. Who proof load tests your cranes?

- company employees
- outside crane inspector
- both

16i. Are any of your employees currently certified to perform crane inspections in the maritime industry?

- Yes No

16j. Do you own any cranes used in the maritime industry?

- Yes: please go to question 16k No: please go to question 16m

16k. Are the cranes you own used *only* in the maritime industry? Yes No

16l. How many of your cranes are used in the maritime industry? _ cranes (if none, put "0")

16m. How often do you inspect and proof load test your cranes?

- More often than one time per year: _____ times per year
- Less often than one time per year: one test every _ years.

Thank you for completing this survey. Please return it in the postage-paid envelope as soon as possible.

Appendix 2: Data Collection Disposition

July 2008	PHASE 1	PHASE 2	PHASE 3	TOTAL
Total sample received from DOSH	2220	425	126	
Mail completes	139	2**	2**	139
Bad address/no listing unable to call	219			
Refused	1			
Duplicate listings for companies/contacts		79	17	
No phone number/Unable to locate phone #		14		
L&I employee		1		
No company name/contact info in file		6		
Imported into telephone survey	1861	325	109	2295
Telephone completes	133	158	43	334
Refusal/company policy no surveys allowed/terminated survey	10	23	1	34
Wrong #, disconnect , fax, residential	86	13	4	103
Said sent/will send	12			
Resent/faxed qxr to respondent	8			
Language barrier	2	0	1	3
Still callable/not called *	1392	59	9	1460
Not qualified misc./gone for remainder	2	71	51	124
Cell phone	2	1	0	3
Returned mail survey after calling began (18 with large companies)	214			214
TOTAL completes	486	160	45	691
No to q1d	441	58	14	513
Long survey	20	85	26	131
Subcontracts cranes	25	17	5	47
Completes	486	160	45	691
Disqualified/unable to determine if qualified	311	85	56	452
Still callable/unreachable; no answer, blocked #/said will mail/mailed	1412	59	9	1480
Refused survey	11	23	1	35
Total Sample	2220	327	111	2658
* 926 were never called in Phase 1				
** These were mail surveys sent and received by L&I and sent to Gilmore for entry and surveys received after Phase 1 closed.				

Appendix 3: Risk Classes Used in Survey Sample Frame – Phase 1.

Risk main sub	Description
010100	STREET OR ROAD CONSTRUCTION, N.O.C.
010101	AIRPORT TAXIWAY OR RUNWAY: CONSTRUCTION OR REPAIR
010102	EXCAVATION, N.O.C.
010103	GRADING, N.O.C.
010104	LAND CLEARING OR FIREFIGHTING, N.O.C.
010105	ROAD SURFACING AND STRIPING
010106	COAXIAL CABLE OR CONDUIT CONSTRUCTION: UNDERGROUND
010107	CONCRETE CONSTRUCTION, N.O.C.
010110	DIKING, N.O.C.
010111	DITCHES AND CANALS, N.O.C.
010112	DREDGING, N.O.C.
010114	PIPELAYING, N.O.C.
010115	STREET OR ROAD CONSTRUCTION: GRAVEL PRODUCTION
010116	RAILROAD CONSTRUCTION OR REPAIR
010117	STREET OR ROAD CONSTRUCTION: RETAIN WALLS
010118	SEWAGE DISPOSAL PLANT, CONSTRUCTION
010121	TRENCHES AND SEWERS: CONSTRUCTION, N.O.C.
010122	TUNNELS AND APPROACHES - NON-PNEUMATIC
010123	TUNNELS AND APPROACHED - NON-PNEUMATIC
010126	STREET OR ROAD CONSTRUCTION: LIGHTING OR SIGN INSTALLATION
010135	SLOPE GROOMING
010150	REINFORCING STEEL INSTALLATION
010207	CONCRETE CONSTRUCTION, N.O.C.
010208	CONCRETE CULVERTS: SPAN LESS THAN 12 FEET
010412	DREDGING, N.O.C.
010700	UTILITY LINE CONSTRUCTION: UNDERGROUND
010701	PIPE LAYING, N.O.C.
010800	DITCHES AND CANALS, N.O.C.
010801	SEWER CONSTRUCTION
010802	TANKS, N.O.C. - UNDERGROUND TYPE: INSTALLATION, REPAIR OR REMOVAL
020101	BRIDGE OR OVERHEAD CROSSING CONSTRUCTION
020103	WHARF OR PIER CONSTRUCTION AND SUBAQUEOUS WORK, N.O.C.
020104	BREAKWATER, JETTY OR LEVEE CONSTRUCTION
020106	CONCRETE CULVERTS: SPAN OVER 12 FT
020107	UNDERCROSSINGS & APPROACHES
020108	TUNNELS AND APPROACHES
021701	CONCRETE - WOOD BUILDINGS
030108	LANDSCAPE OPERATIONS

Risk main sub	Description
030201	BRICK AND SLATE WORK, N.O.C.
030202	MASONRY, N.O.C.
040300	SIGN ERECTION OR REMOVAL
040314	SIGN ERECTION OR REMOVAL - NEON TYPE
050301	FURNACES OR HEATING SYSTEMS AND BOILERS: INSTALLATION, N.O.C.
050414	SIGN ERECTION OR REMOVAL - NEON TYPE
050500	BUILDING CONSTRUCTION: PRIVATE RESIDENCES
050501	BLDG. CONSTRUCTION: WOOD NOT EXCEEDING 3 STORIES IN HEIGHT
050502	BUILDING CONSTRUCTION, N.O.C
050503	WRECKING OR DEMOLISHING BUILDINGS
050524	BUILDING CONSTRUCTION: IRON/STEEL/CONCRETE
050525	WOOD BUILDINGS: MORE THAN 3 STORIES
050604	WRECKING OR DEMOLISHING BUILDINGS
050802	WINDMILL OR SILO ERECTION OR REPAIR
050811	CRANE OR DERRICK INSTALLATION
050900	OVERHEAD LINE CONSTRUCTION: TELEPHONE OR TELEGRAPH
050902	OVERHEAD LINE CONSTRUCTION: ELECTRIC
050903	OVERHEAD LINE CONSTRUCTION, N.O.C.
051601	PLAYGROUND EQUIPMENT: INSTALLATION - WOOD
051700	MOBIL HOME SET UP BY CONTRACTOR
060105	HIGHWAY LIGHTING INSTALLATION
060306	PUMP INSTALLATION OR REPAIR
200515	PLUMBING SUPPLY DEALERS
200622	OIL OR GAS WELL SUPPLIES OR EQUIPMENT DEALERS SECOND HAND
200901	ELECTRICAL SUPPLY DEALERS: EXCLUDING REPAIRS
200904	PUMP, PLUMBING, IRRIGATION PIPE, AND PIPE SUPPLY DEALERS: INCLUDES PUMP REPAIR IN SHOP
200906	HVAC SUPPLY DEALERS
210215	PLUMBING SUPPLY DEALERS
210222	OIL OR GAS WELL SUPPLIES EQUIPMENT DEALERS - SECOND HAND
520679	CONSTRUCTION OR ERECTION CONTRACTORS - PERM. SHOP OR YARD
640903	OIL OR GAS WELL SUPPLY OR EQUIPMENT DEALERS

Appendix 4: Establishes Origin of Proposed Rule Provisions.

WAC	Source
	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(1) The department shall establish, by rule, a crane certification program for cranes used in construction. In establishing rules, the department shall consult nationally recognized crane standards</p>
<p>WAC 296-155-52900 Scope.</p> <p>(1) Except as provided in subsection (2) below, this part applies to power-operated cranes and derricks used in construction that can hoist, lower and horizontally move a suspended load <u>(with or without attachments)</u>. Such equipment includes, but is not limited to: articulating boom cranes (such as knuckle-boom cranes); crawler cranes; floating cranes; cranes on barges; locomotive cranes; mobile cranes (such as wheel-mounted, rough-terrain, all-terrain, commercial truck-mounted, and boom truck cranes); multi-purpose machines when configured to hoist and lower (by means of a winch or hook) and horizontally move a suspended load; industrial cranes (such as carry-deck cranes); dedicated pile drivers; service/mechanic trucks with a hoisting device; a crane on a monorail; tower cranes (such as fixed jib (“hammerhead boom”), luffing boom and self-erecting); pedestal cranes; portal cranes; overhead and gantry cranes; straddle cranes; side-boom tractors; derricks; and variations of such equipment.</p>	<p>RCW 49.17.410 Construction crane safety — Application</p> <p>(1) RCW 49.17.400 through 49.17.430 apply to cranes used with or without attachments.</p>
<p>WAC 296-155-52900 Scope.</p> <p>(2) Exemptions. WAC 296-155-529 through WAC 296-155-53214 do not apply to the following:</p>	<p>RCW 49.17.400 Construction Crane Safety – Definitions</p> <p>(2) RCW 49.17.400 through 49.17.430 do not apply to:</p>

WAC	Source
<p>WAC 296-155-52900 Scope. Equipment included in paragraph (1) while it has been converted or adapted for non-hoisting/lifting use. Such conversions/adaptations include, but are not limited to, power shovels, excavators and concrete pumps.</p>	<p>RCW 49.17.400 Construction Crane Safety – Definitions (2)(a) A crane while it has been converted or adapted for a nonhoisting or nonlifting use including, but not limited to, power shovels, excavators, and concrete pumps;</p>
<p>WAC 296-155-52900 Scope. Power shovels, excavators, wheel loaders, backhoes, loader backhoes, track loaders. This machinery is also excluded when used with chains, slings or other rigging to lift suspended loads.</p>	<p>RCW 49.17.400 Construction Crane Safety – Definitions (2)(b) Power shovels, excavators, wheel loaders, backhoes, loader backhoes, and track loaders when used with or without chains, slings, or other rigging to lift suspended loads;</p>
<p>WAC 296-155-52900 Scope. Automotive wreckers and tow trucks when used to clear wrecks and haul vehicles.</p>	<p>RCW 49.17.400 Construction Crane Safety – Definitions (2)(c) Automotive wreckers and tow trucks when used to clear wrecks and haul vehicles;</p>
<p>WAC 296-155-52900 Scope. Service trucks with mobile lifting devices designed specifically for use in the power line and electric service industries or handling associated materials to be installed or removed from utility poles.</p>	<p>RCW 49.17.400 Construction Crane Safety – Definitions (2)(d) Service trucks with mobile lifting devices designed specifically for use in the power line and electric service industries, such as digger derricks (radial boom derricks), when used in the power line and electric service industries for auguring holes to set power and utility poles, or handling associated materials to be installed or removed from utility poles;</p>
<p>WAC 296-155-52900 Scope. Equipment originally designed as vehicle-mounted aerial devices (for lifting personnel) and self-propelled elevating work platforms.</p>	<p>RCW 49.17.400 Construction Crane Safety – Definitions (2)(e) Equipment originally designed as vehicle-mounted aerial devices (for lifting personnel) and self-propelled</p>

WAC	Source
	elevating work platforms;
WAC 296-155-52900 Scope. Hydraulic jacking systems, including telescopic/hydraulic gantries.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(f) Hydraulic jacking systems, including telescopic/hydraulic gantries;
WAC 296-155-52900 Scope. Stacker cranes.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(g) Stacker cranes;
WAC 296-155-52900 Scope. Powered industrial trucks (forklifts).	RCW 49.17.400 Construction Crane Safety – Definitions (2)(h) Powered industrial trucks (forklifts);
WAC 296-155-52900 Scope. Mechanic’s truck with a hoisting device when used in activities related to equipment maintenance and repair.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(i) Mechanic's truck with a hoisting device when used in activities related to equipment maintenance and repair;
WAC 296-155-52900 Scope. Equipment that hoists by using a come-a-long or chainfall.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(j) Equipment that hoists by using a come-along or chainfall;
WAC 296-155-52900 Scope. Dedicated drilling rigs.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(k) Dedicated drilling rigs;
WAC 296-155-52900 Scope. Gin poles used for the erection of communication towers.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(l) Gin poles used for the erection of communication towers;

WAC	Source
WAC 296-155-52900 Scope. Tree trimming and tree removal work.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(m) Tree trimming and tree removal work;
WAC 296-155-52900 Scope. Anchor handling with a vessel or barge using an affixed A-frame.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(n) Anchor handling with a vessel or barge using an affixed A-frame;
WAC 296-155-52900 Scope. Roustabouts.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(o) Roustabouts;
WAC 296-155-52900 Scope. Service cranes with booms that rotate manually.	DOSH initiated language.
WAC 296-155-52900 Scope. Machines equipped with a boom that is limited to up and down movement only and does not rotate.	DOSH initiated language.
WAC 296-155-52900 Scope. Cranes used on-site in manufacturing facilities or powerhouses for occasional or routine maintenance and repair work; and	RCW 49.17.400 Construction Crane Safety – Definitions (2)(p) Cranes used on-site in manufacturing facilities or powerhouses for occasional or routine maintenance and repair work; and
WAC 296-155-52900 Scope. Crane operators operating cranes on-site in manufacturing facilities or powerhouses for occasional or routine maintenance and repair work.	RCW 49.17.400 Construction Crane Safety – Definitions (2)(q) Crane operators operating cranes on-site in manufacturing facilities or powerhouses for occasional or routine maintenance and repair work.
WAC 296-155-52900 Scope. (3) Where provisions of this standard direct an operator, crewmember, or	DOSH initiated language.

WAC	Source
other employee to take certain actions, the employer must establish, effectively communicate to the relevant persons, and enforce work rules, to ensure compliance with such provisions.	
WAC 296-155-52902 Definitions. Accredited crane certifier means a crane inspector who has been accredited by the department.	DOSH initiated language.
WAC 296-155-52902 Definitions. Apprentice operator or trainee means a crane operator who has not met requirements established by the department under RCW 49.17.430.	RCW 49.17.400 Construction Crane Safety - Definitions "Apprentice operator or trainee" means a crane operator who has not met requirements established by the department under RCW 49.17.430.
WAC 296-155-52902 Definitions. Articulating boom crane means a crane whose boom consists of a series of folding, pin connected structural members, typically manipulated to extend or retract by power from hydraulic cylinders.	DOSH initiated language.
WAC 296-155-52902 Definitions. Audible signal means a signal made by a distinct sound or series of sounds. Examples include, but are not limited to, sounds made by a bell, horn, or whistle.	DOSH initiated language.
WAC 296-155-52902 Definitions. Bogie. See "travel bogie".	DOSH initiated language.
WAC 296-155-52902 Definitions. Boom (equipment other than tower crane) means an inclined spar, strut, or other long structural member which supports the upper hoisting tackle on a crane or derrick. Typically, the length and vertical angle of the boom can be varied to achieve increased height or height and reach when lifting loads. Booms can usually be grouped into general categories of hydraulically extendible, cantilevered type, latticed section, cable	DOSH initiated language.

WAC	Source
supported type or articulating type.	
<p>WAC 296-155-52902 Definitions. Boom (tower cranes). On tower cranes: if the “boom” (i.e., principle horizontal structure) is fixed, it is referred to as a jib; if it is moveable up and down, it is referred to as a boom.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Boom angle indicator. A device which measures the angle of the boom relative to horizontal.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Boom hoist limiting device includes boom hoist disengaging device, boom hoist shut-off, boom hoist disconnect, boom hoist hydraulic relief, boom hoist kick-outs, automatic boom stop device, or derricking limiter. This type of device disengages boom hoist power when the boom reaches a predetermined operating angle. It also sets brakes or closes valves to prevent the boom from lowering after power is disengaged.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Boom length indicator indicates the length of the permanent part of the boom (such as ruled markings on the boom) or, as in some computerized systems, the length of the boom with extensions/attachments.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Boom stop includes boom stops, (belly straps with struts/standoff) telescoping boom stops, attachment boom stops, and backstops. These devices restrict the boom from moving above a certain maximum angle and toppling over backward.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Boom suspension systems. A system of pendants, running ropes, sheaves, and other hardware which supports the boom tip and controls the boom angle.</p>	DOSH initiated language.

WAC	Source
<p>WAC 296-155-52902 Definitions. Certified crane inspector means a crane certifier accredited by the department.</p>	<p>RCW 49.17.400 Construction Crane Safety - Definitions (3) "Certified crane inspector" means a crane inspector who has been certified by the department.</p>
<p>WAC 296-155-52902 Definitions. Climbing. The process in which a tower crane is raised to a new working height, either by adding additional tower sections to the top of the crane (top climbing), or by a system in which the entire crane is raised inside the structure (inside climbing).</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Counterjib (counterweight jib) means a horizontal member of the tower crane on which the counterweights and usually the hoisting machinery are mounted.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Counterweight. Weight used to supplement the weight of equipment in providing stability for lifting loads by counterbalancing those loads.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Crane means power-operated equipment used in construction that can hoist, lower, and horizontally move a suspended load. "Crane" includes, but is not limited to: Articulating boom cranes, such as knuckle-boom cranes; crawler cranes; floating cranes; cranes on barges; locomotive cranes; mobile cranes, such as wheel-mounted, rough-terrain, all-terrain, commercial truck mounted, and boom truck cranes; multipurpose machines when configured to hoist and lower by means of a winch or hook and horizontally move a suspended load; industrial cranes, such as carry-deck cranes; dedicated pile drivers; service/mechanic trucks with a hoisting device; a crane on a monorail; tower cranes, such as fixed jib, hammerhead boom, luffing boom, and self-erecting; pedestal cranes;</p>	<p>RCW 49.17.400 Construction Crane Safety - Definitions (5) "Crane" means power-operated equipment used in construction that can hoist, lower, and horizontally move a suspended load. "Crane" includes, but is not limited to: Articulating cranes, such as knuckle-boom cranes; crawler cranes; floating cranes; cranes on barges; locomotive cranes; mobile cranes, such as wheel-mounted, rough-terrain, all-terrain, commercial truck mounted, and boom truck cranes; multipurpose machines when configured to hoist and lower by means of a winch or hook and horizontally move a suspended load; industrial cranes, such as carry-deck cranes;</p>

WAC	Source
portal cranes; overhead and gantry cranes; straddle cranes; side-boom tractors; derricks; and variations of such equipment.	dedicated pile drivers; service/mechanic trucks with a hoisting device; a crane on a monorail; tower cranes, such as fixed jib, hammerhead boom, luffing boom, and self-erecting; pedestal cranes; portal cranes; overhead and gantry cranes; straddle cranes; side-boom tractors; derricks; and variations of such equipment.
WAC 296-155-52902 Definitions. Crane/derrick type. Means crane or derricks as established by American Society of Mechanical Engineers (ASME).	DOSH initiated language.
WAC 296-155-52902 Definitions. Crawler crane. Equipment that has a type of base mounting which incorporates a continuous belt of sprocket driven track.	DOSH initiated language.
WAC 296-155-52902 Definitions. Critical lift means a lift that: <ul style="list-style-type: none"> ▪ Exceeds seventy-five percent of the crane or derrick rated load chart capacity; or ▪ Requires the use of more than one crane or derrick. 	DOSH initiated language.
WAC 296-155-52902 Definitions. Crossover points. Locations on a wire rope which is spooled on a drum where one layer of rope climbs up on and crosses over the previous layer. This takes place at each flange of the drum as the rope is spooled onto the drum, reaches the flange, and begins to wrap back in the opposite direction.	DOSH initiated language.
WAC 296-155-52902 Definitions. Dedicated pile-driver is a machine that is designed to function exclusively as a pile-driver. These machines typically have the ability to both hoist the material that will be pile-driven and to pile-drive that material.	DOSH initiated language.

WAC	Source
<p>WAC 296-155-52902 Definitions. Derrick is an apparatus consisting of a mast or equivalent member held at the end by guys or braces, with or without a boom, for use with a hoisting mechanism and operating ropes</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Directly under the load means a part or all of an employee is directly beneath the load.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Dismantling includes partial dismantling (such as dismantling to shorten a boom or substitute a different component).</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Drum rotation indicator. A device on a crane or hoist which indicates in which direction and at what relative speed a particular hoist drum is turning.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Electrical contact. When a person, object, or equipment makes contact or comes close in proximity with an energized conductor or equipment that allows the passage of current.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Equipment means equipment covered by this part.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Equipment criteria means instructions, recommendations, limitations and specifications.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Fall protection equipment means guardrail systems, safety net systems, personal fall arrest systems, positioning device systems or fall restraint systems.</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>WAC 296-155-52902 Definitions. Flange points. A point of contact between rope and drum flange where the rope changes layers.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Floating cranes/derricks means equipment designed by the manufacturer (or employer) for marine use by permanent attachment to a barge, pontoons, vessel or other means of flotation.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Free rated load test. Testing stability and operation of crane, carrier, wheels, tires, tracks, brakes, etc., under load, when lifting without outriggers and/or traveling with the load are permitted at the activity for the type of crane being tested.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Hoist means a mechanical device for lifting and lowering loads by winding rope onto or off a drum.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Hoisting. The act of raising, lowering or otherwise moving a load in the air with equipment covered by this standard. As used in this standard, “hoisting” can be done by means other than wire rope/hoist drum equipment.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Jib means an extension attached to the boom point to provide added boom length for lifting specified loads. The jib may be in line with the boom or offset to various angles in the vertical plane of the boom. For tower cranes, see boom (tower cranes).</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Land crane/derrick. Equipment not originally designed by the manufacturer for marine use by permanent attachment to barges,</p>	<p>DOSH initiated language.</p>

WAC	Source
pontoons, vessels, or other means of flotation.	
<p>WAC 296-155-52902 Definitions.</p> <p>Load is the weight of the object being lifted or lowered, including the weight of the load-attaching equipment such as the load block, ropes, slings, shackles, and any other auxiliary attachment.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Load moment (or rated capacity) indicator. A system which aids the equipment operator by sensing the overturning moment on the equipment, i.e. load X radius. It compares this lifting condition to the equipment's rated capacity, and indicates to the operator the percentage of capacity at which the equipment is working. Lights, bells, or buzzers may be incorporated as a warning of an approaching overload condition.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Load moment (or rated capacity) limiter. A system which aids the equipment operator by sensing the overturning moment on the equipment, i.e. load X radius. It compares this lifting condition to the equipment's rated capacity, and when the rated capacity is reached, it shuts off power to those equipment functions which can increase the severity of loading on the equipment, e.g., hoisting, telescoping out, or luffing out. Typically, those functions which decrease the severity of loading on the equipment remain operational, e.g., lowering, telescoping in, or luffing in.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Locomotive crane means a crane mounted on a base or car equipped for travel on a railroad track.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Load sustaining/bearing parts. Those parts of a crane that support the crane or load and upon failure could cause dropping, uncontrolled</p>	DOSH initiated language.

WAC	Source
shifting, or uncontrolled movement of the crane or load.	
WAC 296-155-52902 Definitions. Luffing boom is a member hinged to the rotating superstructure and used for supporting the hoisting tackle.	DOSH initiated language.
WAC 296-155-52902 Definitions. Luffing jib limiting device is similar to a boom hoist limiting device, except that it limits the movement of the luffing jib.	DOSH initiated language.
WAC 296-155-52902 Definitions. Mobile cranes. A lifting device incorporating a cable suspended latticed boom or hydraulic telescopic boom designed to be moved between operating locations by transport over the road. These are referred to in Europe as a crane mounted on a truck carrier.	DOSH initiated language.
WAC 296-155-52902 Definitions. Multiple lift rigging means a rigging assembly manufactured by wire rope rigging suppliers that facilitates the attachment of up to five independent loads to the hoist rigging of a crane.	DOSH initiated language.
WAC 296-155-52902 Definitions. Nationally recognized accrediting agency is an organization that, due to its independence and expertise, is widely recognized as competent to accredit testing organizations.	DOSH initiated language.
WAC 296-155-52902 Definitions. Nonstandard tower crane base means any deviation from the structural support or base configuration recommended by the crane manufacturer.	DOSH initiated language.
WAC 296-155-52902 Definitions. Occasional or routine maintenance and repair work means regular, customary and foreseeable work necessary to keep equipment in good repair and/or condition. This also includes regular, customary and foreseeable work necessary to return equipment to sound condition after	DOSH initiated language.

WAC	Source
damage.	
<p>WAC 296-155-52902 Definitions.</p> <p>Operational aid means an accessory that provides information to facilitate operation of a crane or that takes control of particular functions without action of the operator when a limiting condition is sensed. Examples of such devices include, but are not limited to, the following: anti-two-block device, rated capacity indicator, rated capacity (load) limiter, boom angle or radius indicator, lattice boom hoist disconnect device, boom length indicator, crane level indicator, drum rotation indicator, load indicator, and wind speed indicator.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Operational controls means levers, switches, pedals and other devices for controlling equipment operation.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Operator is a person who is operating the equipment.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Overhead and gantry cranes includes overhead/bridge cranes, semigantry, cantilever gantry, wall cranes, storage bridge cranes, launching gantry cranes, and similar equipment, irrespective of whether it travels on tracks, wheels, or other means.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Pendants includes both wire and bar types. Wire type: a fixed length of wire rope with mechanical fittings at both ends for pinning segments of wire rope together. Bar type: instead of wire rope, a bar is used. Pendants are typically used in a latticed boom crane system to easily change the length of the boom suspension system without completely changing the rope on the drum when the boom length is increased or</p>	DOSH initiated language.

WAC	Source
decreased.	
<p>WAC 296-155-52902 Definitions. Powerhouse means a plant wherein electric energy is produced by conversion from some other form of energy (e.g., chemical, nuclear, solar, mechanical, or hydraulic) by means of suitable apparatus. This includes all generating station auxiliaries and other associated equipment required for the operation of the plant. Not included are stations producing power exclusively for use with communication systems.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Power lines means electrical distribution and electrical transmission lines.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Qualified crane operator means a crane operator who meets the requirements established by the department under RCW 49.17.430.</p>	<p>RCW 49.17.400 Construction Crane Safety - Definitions (8) "Qualified crane operator" means a crane operator who meets the requirements established by the department under RCW 49.17.430.</p>
<p>WAC 296-155-52902 Definitions. Qualified person means a person who, by possession of a recognized degree, certificate, or professional standing, or who by extensive knowledge, training and experience, successfully demonstrated the ability to solve/resolve problems relating to the subject matter, the work, or the project.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Rated capacity. The maximum working load permitted by the manufacturer under specified working conditions. Such working conditions typically include a specific combination of factors such as equipment configuration, radii, boom length, and other parameters of use.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Rated capacity indicator. See load moment indicator.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions. Rated capacity limiter. See load moment limiter.</p>	DOSH initiated language.

WAC	Source
<p>WAC 296-155-52902 Definitions. RPE means a registered professional engineer licensed under chapter 18.43.040(1) RCW.</p>	<p>RCW 49.17.400 Construction Crane Safety - Definitions (7) "Professional engineer" means a professional engineer as defined in RCW 18.43.020.</p>
<p>WAC 296-155-52902 Definitions. RPSE means a registered professional structural engineer licensed under chapter 18.43.040(1) RCW.</p>	<p>RCW 49.17.400 Construction Crane Safety - Definitions (7) "Professional engineer" means a professional engineer as defined in RCW 18.43.020.</p>
<p>WAC 296-155-52902 Definitions. Running wire rope is a wire rope that moves over sheaves or drums.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Safety devices. Examples of safety devices are but not limited to the following: crane level indicator, horn, boom/jib or trolley stops, hydraulic holding device/check valve, rail clamps, rail stops, brakes, deadman control or forced neutral return control, emergency stop switch, guards, handrails, audible and visual alarms, etc.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Safety or health standard means a standard adopted under this chapter.</p>	<p>RCW 49.17.400 Construction Crane Safety - Definitions (9) "Safety or health standard" means a standard adopted under this chapter.</p>
<p>WAC 296-155-52902 Definitions. Taglines. A rope (usually fiber) attached to a lifted load for purposes of controlling load spinning and pendular motions or used to stabilize a bucket or magnet during material handling operations.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-52902 Definitions. Tower crane. A type of lifting structure which utilizes a vertical mast or tower to support a working boom (jib) suspended from the working boom. While the working boom may be fixed horizontally or have</p>	<p>DOSH initiated language.</p>

WAC	Source
luffing capability, it can always rotate about the tower center to swing loads. The tower base may be fixed in one location or ballasted and moveable between locations.	
<p>WAC 296-155-52902 Definitions.</p> <p>Travel bogie (tower cranes). An assembly of two or more axles arranged to permit vertical wheel displacement and equalize the loading on the wheels.</p>	DOSH initiated language.
<p>WAC 296-155-52902 Definitions.</p> <p>Two blocking means a condition in which a component that is uppermost on the hoist line such as the load block, hook block, overhaul ball, or similar component, comes in contact with the boom tip, fixed upper block or similar component. This binds the system and continued application of power can cause failure of the hoist rope or other component.</p>	DOSH initiated language.
<p>WAC 296-155-531 Crane Certifier Accreditation Process.</p> <p>WAC 296-155-53100 Accreditation of Crane Certifiers of Cranes and Derricks – Requirements.</p> <p>(1) Any person engaging in the testing, examination or inspection for the certification of a crane, used in lifting at a construction site must apply for and obtain a certificate of accreditation from the department pursuant to this rule. For the purposes of this rule an "accredited crane certifier" refers to any individual holding a certificate of accreditation pursuant to this regulation.</p> <p>(2) Any person authorized by the department to certify maritime cranes prior to the effective date of this rule may continue to perform services under this regulation until January 1, 2012. Any accredited crane certifier desiring to continue providing services pursuant to this rule must have applied for and obtained a certificate of accreditation under these rules</p>	DOSH initiated language.

WAC	Source
<p>from the department prior to January 1, 2012. Maritime certifiers wishing to perform construction crane certifications must notify the department that they will perform construction crane certifications. In addition, the maritime certifier must specify which cranes they are qualified to inspect under their maritime certificate. The department may issue these individuals a provisional accreditation specifying the crane types they are authorized to inspect which will be valid through December 31, 2011 or upon expiration of their maritime certification, whichever is earlier. Any provisionally accredited crane certifier desiring to continue providing services pursuant to this rule must have applied for and obtained a certificate of accreditation under these rules from the department prior to January 1, 2012.</p> <p>(3) Crane certifiers accredited by any other state or governmental entity may be authorized to inspect cranes in Washington State provided the certifier submits an application and resume along with the certificate of accreditation from that state or governmental entity, and the types of cranes they are authorized to inspect. The department may issue these individuals a provisional accreditation specifying the crane types they are authorized to inspect which will be valid through December 31, 2011 or upon expiration of their out of state certification, whichever is earlier. Any provisionally accredited crane certifier desiring to continue providing services pursuant to this rule must have applied for and obtained a certificate of accreditation under these rules from the department prior to January 1, 2012.</p> <p>(4) No person that has modified, altered, or repaired a crane which affected a load sustaining member of the crane may conduct the certifying inspection and proof load testing of that particular crane within the same certification period.</p>	
WAC 296-155-53102 Accreditation - Application Form and Applicant	RCW 49.17.420 Construction Crane Certification Program –

WAC	Source
<p><u>Qualifications.</u></p> <p>(1) An accreditation to certify cranes pursuant to this rule may be obtained by submitting a completed application to the Division of Occupational Safety and Health (DOSH) and successfully completing written examinations developed and administered by the department or its authorized representative. Application forms may be obtained by calling the: Crane Certification Section of DOSH (360) 902-4943 or by written request to: Post Office Box 44650 • Olympia, WA 98504-4650</p>	<p>Rules – Certificate of Operation.</p> <p>(2) The crane certification program must include, at a minimum, the following:</p> <p>(a) The department shall establish certification requirements for crane inspectors, including an experience requirement, an education requirement, a training requirement, and other necessary requirements determined by the director;</p>
<p>WAC 296-155-53102 Accreditation - Application Form and Applicant <u>Qualifications.</u></p> <p>(2) An applicant seeking an accreditation must satisfy all of the following criteria:</p> <p>(a) An application with an attached resume must be submitted to the department based on experience with the various crane types per the ASME B30 series. The application and resume must include knowledge, training and experience with verifiable references.</p> <p>(b) All applicants must possess knowledge of chapter 296-155 WAC, Safety Standards for Construction Work, as well as American Society of Mechanical Engineers (ASME) standards, relating to the design, testing, inspection and operation of cranes, including those specifically applicable to the types of cranes for which an accreditation will be issued.</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>(c) All applicants must demonstrate at least five years crane related experience, of which two years must be actual crane inspection activities. The other three years may include experience in duties such as a crane operator, crane mechanic, crane shop foreman, crane operations supervision, or rigging specialist. Related education may be substituted for related experience at a ratio of two years of education for one year of experience up to three years. Related education could include such courses in Engineering, Physics, Applied Mathematics, Applied Science Courses in Nondestructive Testing, Construction Technology, Technical Courses in Heavy Equipment Mechanic, Welding Technology, etc.</p> <p>(3) Application Form. Any application for accreditation will be accepted by the department upon the filing of a completed application. All information and attachments must be given under penalty of perjury. The application must include, but not be limited to, the following:</p> <p>(a) A statement of the crane types per the ASME B30 series the applicant desires to certify pursuant to the accreditation.</p> <p>(b) A statement of qualifications and experience, including their capacities, satisfying at a minimum the criteria set forth in this section as well as any and all other qualifications the applicant wishes the department to consider.</p> <p>(c) Any other relevant information the applicant desires to be considered by the department.</p> <p>(4) Written examinations. Applicants to be approved for accreditation must successfully complete the written examinations administered by the department or its authorized representative.</p> <p>(a) Once the department receives the application and resume, the department will make the determination and notify the applicant if they</p>	

WAC	Source
<p>meet the minimum qualifications to take the written examinations.</p> <p>(b) The first written examination will include a general knowledge of operation, testing, inspection and maintenance requirements, and the duties and recordkeeping responsibilities required by this rule.</p> <p>(c) The other written examinations will include safe operating and engineering principles and practices with respect to specific crane types subject to the accreditation, including inspection and proof loading requirements</p>	
<p>WAC 296-155-53104 Issuance of Accreditation.</p> <p>(1) The department may impose restrictions on the scope and use of the accreditation, such as limiting it to specific types of cranes based upon the qualifications of the applicant. The accreditation issued by the department will identify any limitations imposed by the department and the types of cranes the certifier is authorized to certify.</p> <p>(2) The department must deny issuance of an accreditation if the applicant does not satisfy the requirements of this rule.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-53106 Accreditation Application--Processing Time.</p> <p>(1) Within 45 calendar days of receipt of a completed application for an accreditation the department must inform the applicant in writing that it is either complete and accepted for filing or that it is deficient and what specific information or documentation is required to complete the application and will inform the applicant if the applicant is eligible to take the written examination. An application is considered complete if it is in compliance with the requirements of this rule.</p> <p>(2) Within 75 calendar days from the date of completion of the written examinations the department must inform the applicant in writing of its</p>	<p>DOSH initiated language.</p>

WAC	Source
decision regarding the issuance of the certificate of accreditation.	
<p>WAC 296-155-53108 Duration and Renewal of an Accreditation.</p> <p>(1) The accreditation will be valid for three years. Crane certifiers must complete forty (40) hours of crane related training every three years, in courses recognized by the department.</p> <p>(2) Application for renewal must be filed with the department not less than 60 days prior to expiration of the accredited crane certifier's certification. A renewal may be obtained by filing a completed application for renewal meeting the requirements of WAC 296-155-53102 hereof providing the applicant has been actively inspecting cranes during their prior accreditation period. An applicant is considered active if he/she has certified at least twenty-one cranes during their accreditation period. If the applicant certified cranes in another state, then that applicant must provide documentation showing they were active during their accreditation period. An applicant who has not certified at least twenty-one cranes during the accreditation period may take the written exam to become recertified.</p> <p>(3) At a minimum, all applicants for renewal must successfully complete the written examinations every six years.</p>	DOSH initiated language.
<p>WAC 296-155-53110 Revocation or Suspension of an Accreditation.</p> <p>(1) The department may suspend or revoke a certificate issued under the provisions of these rules upon the following grounds:</p> <p>(a) Permitting the duplication or use of one's own accreditation certificate by another;</p> <p>(b) Performing work for which accreditation has not been received;</p>	DOSH initiated language.

WAC	Source
<p>(c) Any person who obtains accreditation through fraudulent representation of accreditation requirements such as education, training, professional registration, or experience;</p> <p>(d) Any person who falsifies training documentation;</p> <p>(e) The holder of the certificate is found to be incompetent to carry out the work for which the certificate was issued;</p> <p>(f) Gross negligence, gross incompetence, a pattern of incompetence, or fraud in the certification of a crane;</p> <p>(g) Willful or deliberate disregard of any occupational safety standard while certifying a crane;</p> <p>(h) Misrepresentation of a material fact in applying for, or obtaining, a license to certify under this chapter;</p> <p>(i) Failure by an accredited crane certifier to maintain records;</p> <p>(j) Failure by an accredited crane certifier to report crane safety deficiencies affecting the safe operation of a crane while in the process of conducting an annual certification inspection;</p> <p>(k) Failure to meet or comply with the requirements of this rule or the limitations imposed on the accreditation; or</p> <p>(l) Performance of work not in compliance with applicable laws and</p>	

WAC	Source
<p>regulations.</p> <p>(2) Before any certificate may be suspended or revoked, the certificate holder must be given written notice of the department’s intention, mailed by certified mail, return receipt requested to the address as shown on the application form. The notice must specify the reasons for the department action and must give the certificate holder the opportunity to attend a hearing before the department. The department must also include within the notice of revocation or suspension specific conditions which must be met before the applicant will be entitled to apply for a new certification. At the suspension/revocation hearing the department must give the certificate holder the opportunity to produce witnesses and give testimony.</p> <p>(3) The hearing will be held at the department’s headquarters office or at such other location as may be designated by the assistant director and must be presided over an authorized representative of the assistant director. Following the informal hearing the department will issue a final decision on suspension or revocation.</p> <p>(4) A final suspension or revocation decision may be appealed to the superior court for the state of Washington in either the county in which the certificate holder resides or in Thurston County within thirty days after the suspension or revocation order is entered.</p> <p>(5) The filing of an appeal must not stay the suspension or revocation, and such action must remain in effect until such time as the applicant presents proof that the specified written conditions required by the department are met or until otherwise ordered after resolution of the</p>	

WAC	Source
appeal.	
<p>WAC 296-155-53112 Monitoring of Accredited Crane Certifiers. The Division of Occupational Safety and Health must monitor accredited crane certifiers to ensure that these certifiers certify cranes in accordance with all applicable Washington State laws and regulations. Monitoring activities will include, but not be limited to, audits of crane certifier’s activities, complaint inspections, referrals, or accident investigations.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation.</p> <p>(1) Accredited crane certifiers will issue a temporary certificate of operation if upon inspection and load proof testing no deficiencies were found that would affect the safe operation of the crane.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards, including meeting or exceeding national periodic inspection requirements recognized by the department;</p>
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation.</p> <p>(2) The accredited crane certifier will submit inspection worksheets and proof of load testing to the department within ten working days from the completion of the inspection and load proof test for consideration of the department for the issuance of a permanent certificate of operation.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards, including meeting or exceeding national periodic inspection requirements recognized by the department;</p> <p>(3)(g) Inspection reports including all information and</p>

WAC	Source
	documentation obtained from a crane inspection shall be made available or provided to the department by a certified crane inspector upon request.
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation.</p> <p>(3) If the accredited crane certifier upon inspection of a crane identifies deficiencies that would affect the safe operation or load handling capabilities of the crane, the accredited crane certifier must notify the department within five working days from completion of the onsite inspection by submitting the worksheet that identifies the deficiencies. If deficiencies are found that affect the safe operation or load handling capabilities of the crane no temporary certificate of operation will be issued until all identified deficiencies have been corrected and verified by an onsite visit by an accredited crane certifier.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards, including meeting or exceeding national periodic inspection requirements recognized by the department;</p> <p>(3)(f) A certified crane inspector must notify the department and the crane owner if, after inspection, the certified crane inspector finds that the crane does not meet safety or health standards. A certified crane inspector shall not attest that a crane meets safety or health standards until any deficiencies are corrected and the correction is verified by the certified crane inspector; and</p>
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation.</p> <p>(4) After the accredited crane certifier has verified that all deficiencies have been corrected and the crane has successfully passed a load proof test the accredited crane certifier will issue a temporary certificate of operation. The accredited crane certifier will submit inspection worksheets and proof of load testing to the owner or lessee and within ten days of completion of the inspection to the department for</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards,</p>

WAC	Source
<p>consideration of the department for the issuance of an annual certificate of operation.</p>	<p>including meeting or exceeding national periodic inspection requirements recognized by the department;</p>
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation. (5) The accredited crane certifier must attach an identification sticker if not already attached and legible to each crane and crane component (component meaning; luffing boom, swing-away jibs, fly sections, jibs at variable offsets and boom sections). The identification sticker number must be entered on the inspection work sheet submitted to the department. Identification stickers may only be removed by a department representative or an accredited crane certifier.</p> <p><i>Note:</i> Certified components may be installed without voiding the annual proof load test, providing the component was proof load tested within the prior four year period.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards, including meeting or exceeding national periodic inspection requirements recognized by the department;</p>
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation. (6) Certificates of operation issued by the department under the crane certification program established in this section are valid for one year from the effective date of the temporary operating certificate issued by the certified crane inspector.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards, including meeting or exceeding national periodic inspection requirements recognized by the department;</p> <p>(4) Certificates of operation issued by the department under the crane certification program established in this section are</p>

WAC	Source
	valid for one year from the effective date of the temporary operating certificate issued by the certified crane inspector.
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation.</p> <p>(7) The temporary or annual certificate of operation must be posted in the operator’s cab or with the operator’s manual.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3) Except as provided in RCW 49.17.410(2), any crane operated in the state must have a valid temporary or final certificate of operation issued by the certified crane inspector or department posted in the operator's cab or station.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards, including meeting or exceeding national periodic inspection requirements recognized by the department;</p>
<p>WAC 296-155-53114 Issuance of Temporary and Annual Certificates of Operation.</p> <p>(8) Maintaining Required Records. Accredited crane certifiers are required to maintain complete and accurate records pertaining to each crane of all inspections, tests and other work performed as well as copies of all notices of crane safety deficiencies, verifications of correction of crane safety deficiencies, and crane certifications issued for the previous five years and provide these records to the department upon request. Failure by an accredited crane certifier to maintain required records may result in accreditation suspension or revocation.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(3)(b) The department shall establish a process for certified crane inspectors to issue temporary certificates of operation for a crane and the department to issue a final certificate of operation for a crane after a certified crane inspector determines that the crane meets safety or health standards, including meeting or exceeding national periodic inspection requirements recognized by the department;</p>

WAC	Source
	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(5) This section does not apply to maritime cranes regulated by the department.</p>
<p>WAC 296-155-532 Crane Certification Requirements for Cranes</p> <p>WAC 296-155-53200 General Inspection Criteria, Wire Rope Inspection and Removal Criteria, and Pre-Proof Load Test Requirements for all cranes.</p> <p>(1) The accredited crane certifier must review the following documents as part of the crane certification process:</p> <p>(a) Crane maintenance records of critical components to ensure maintenance of these components has been performed in accordance with the manufacturer’s recommendations.</p> <p>(b) Crane periodic and frequent inspection documentation.</p> <p>(2) Safety devices. Make sure all safety devices are installed on equipment in accordance with the requirements located in chapter 296-155 WAC, Part L.</p> <p>(3) Operational aids. Operations must not begin unless operational aids are in proper working order, except where the owner or lessee meets the specified temporary alternative measures. See chapter 296-155 WAC, Part L for the list of operational aids.</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>Note: All accredited crane certifiers must meet and follow the requirements relating to fall protection, located in chapter 296-155 WAC, Part C-1, Fall Restraint and Fall Arrest.</p> <p>(4) General.</p> <p>(a) The accredited crane certifier must determine that the configurations of the crane are in accordance with the manufacturer's equipment criteria.</p> <p>(b) Where the manufacturer equipment criteria are unavailable a registered professional engineer (RPE), familiar with the type of equipment involved, must ensure criteria are developed for the equipment configuration.</p> <p>(5) Wire Rope.</p> <p>Wire ropes must meet the crane or wire rope manufacturer's specifications for size, type and inspection requirements. In the absence of the manufacturer's specifications, follow the requirements for removal criteria located in this section, including Table 1. <i>Table 1 included at end of document</i></p> <p>(b) The accredited crane certifier must perform a complete and thorough inspection covering the surface of the working range plus three additional wraps on the drum of the wire ropes.</p> <p>(c) If a deficiency is identified, an immediate determination must be</p>	

WAC	Source
<p>made by the accredited crane certifier as to whether the deficiency constitutes a safety hazard. If the deficiency is determined to constitute a safety hazard, the crane must not be certified until:</p> <p>(i) The wire rope is replaced and verified by the accredited crane certifier; or</p> <p>(ii) If the deficiency is localized, the problem is corrected by severing the wire rope; the undamaged portion may continue to be used. Joining lengths of wire rope by splicing is prohibited.</p> <p>(d) Remove wire rope from service if reductions from nominal diameter are greater than those shown below in Table 2. Table 2 included at end of document</p> <p>Replacement rope must be of a compatible size and have a strength rating at least as great as the original rope furnished or recommended by the crane manufacturer.</p> <p>(6) Prior to performing a proof load test:</p> <p>(a) A safe test area must be selected and all traffic and unauthorized personnel and equipment must be cleared from test area. This test area must be roped off or otherwise secured to prevent entry of unauthorized personnel and equipment;</p> <p>(b) Rigging gear must be inspected by a qualified person prior to using for load test of crane;</p> <p>(c) The employer must ensure all load test personnel understand the</p>	

WAC	Source
<p>safety procedures of the test;</p> <p>(d) Proof load tests, with the exception of tower cranes, are overload tests and extreme caution must be observed at all times. Personnel must remain clear of suspended loads and areas where they could be struck in the event of boom failure. The test load must be raised only to a height sufficient to perform the test;</p> <p>(e) During tests, safe operating speeds must be employed. Rated speeds in accordance with manufacturer's specifications need not be attained. Emphasis must be placed on the ability to safely control loads through all motions at normal speeds;</p> <p>(f) Proof load tests require the use of certified weights, or scaled weights using a certified scale with a current certificate of calibration;</p> <p>(g) Proof load tests must not exceed the manufacturer's specifications. Where these specifications are unavailable, a registered professional engineer familiar with the type of equipment involved must develop written specifications.</p>	
<p>WAC 296-155-53202 Additional Inspection Criteria and Proof Load Testing – Mobile Cranes.</p> <p>(1) After it is determined that the crane configurations meet the criteria in WAC 296-155-53200, the accredited crane certifier must conduct a visual inspection of the following components, if applicable, which can be visually inspected without disassembly (not including removal of inspection covers):</p> <p>(a) All control and drive mechanisms for adjustments interfering with</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>proper operation and for excessive wear or contamination by lubricants or other foreign matter;</p> <p>(b) Air, hydraulic, and other pressurized lines for deterioration or leakage, particularly those which flex in normal operation;</p> <p>(c) Hydraulic system for proper fluid level;</p> <p>(d) Safety latches on hooks for damage;</p> <p>(e) Hooks for deformation, cracks, excessive wear, or damage such as from chemicals or heat;</p> <p>(f) A legible and applicable operator's manual and load chart is in the operator's cab or station;</p> <p>(g) A portable fire extinguisher, with a basic minimum extinguishing rating of 10 BC must be installed in the cab or at the machinery housing;</p> <p>(h) Crane cleanliness and housekeeping. Inspect for trash, oil, grease, debris or excessive dirt on crane components and catwalks, if applicable;</p> <p>(i) Wire rope reeving for compliance with the manufacturer's specifications;</p> <p>(j) Wire rope, in accordance with WAC 296-155-53200(5);</p> <p>(k) Electrical apparatus for malfunctioning, signs of apparent excessive deterioration, dirt or moisture accumulation;</p>	

WAC	Source
<p>(l) Tires (when in use) for proper inflation and condition;</p> <p>(m) Ground conditions around the equipment for proper support, including ground settling under and around outriggers and supporting foundations, ground water accumulation, or similar conditions;</p> <p>(n) The equipment for level position;</p> <p>(o) Operator cab windows for significant cracks, breaks, or other deficiencies that would hamper the operator's view;</p> <p>(p) Rails, rail stops, rail clamps and supporting surfaces when the equipment has rail traveling;</p> <p>(q) Equipment structure (including the boom and, if equipped, the jib):</p> <p>(i) Structural members: deformed, cracked, or significantly corroded.</p> <p>(ii) Bolts, rivets and other fasteners: loose, failed or significantly corroded.</p> <p>(iii) Welds for cracks.</p> <p>(r) Sheaves and drums for cracks or significant wear;</p> <p>(s) Parts such as pins, bearings, shafts, gears, rollers and locking devices for distortion, cracks or significant wear;</p> <p>(t) Brake and clutch system parts, linings, pawls and ratchets for excessive wear;</p>	

WAC	Source
<p>(u) Safety devices and operational aids for proper operation (including significant inaccuracies);</p> <p>(v) Gasoline, diesel, electric, or other power plants for safety-related problems (such as leaking exhaust and emergency shut-down feature), condition and operation;</p> <p>(w) Chains and chain drive sprockets for excessive wear of sprockets and excessive chain stretch;</p> <p>(x) Travel steering, brakes, and locking devices, for proper operation;</p> <p>(y) Tires for damage or excessive wear;</p> <p>(z) Hydraulic, pneumatic and other pressurized hoses, fittings and tubing, as follows:</p> <p>(i) Flexible hose or its junction with the fittings for indications of leaks.</p> <p>(ii) Threaded or clamped joints for leaks.</p> <p>(iii) Outer covering of the hose for blistering, abnormal deformation or other signs of failure/impending failure.</p> <p>(iv) Outer surface of a hose, rigid tube, or fitting for indications of excessive abrasion or scrubbing.</p> <p>(aa) Hydraulic and pneumatic pumps and motors, as follows:</p> <p>(i) Performance indicators: unusual noises or vibration, low operating speed.</p> <p>(ii) Loose bolts or fasteners.</p> <p>(iii) Shaft seals and joints between pump sections for leaks.</p>	

WAC	Source
<p>(bb) Hydraulic and pneumatic cylinders, as follows:</p> <ul style="list-style-type: none"> (i) Drifting. (ii) Rod seals and welded joints for leaks. (iii) Cylinder rods for scores, nick and dents. (iv) Case (barrel) for significant dents. (v) Rod eyes and connecting joints: loose or deformed. <p>(cc) Outrigger pads/floats and slider pads for excessive wear or cracks; cribbing/dunnage for proper installation;</p> <p>(dd) Electrical components and wiring for cracked or split insulation and loose or corroded terminations;</p> <p>(ee) Legible warning labels and decals as required by the manufacturer;</p> <p>(ff) Operator seat: missing or unusable;</p> <p>(gg) Equipped with original, or the equivalent, steps, ladders, handrails, guards;</p> <p>(hh) Steps, ladders, handrails, guards: in unusable/unsafe condition;</p> <p>(2) Crane deficiencies. If the accredited crane certifier determines other findings need to be monitored, the accredited crane certifier must provide written notification to the owner or lessee.</p> <p>(3) Operational testing. An operational test must be made without a load applied to the hook of the following items if they are applicable to the</p>	

WAC	Source
<p>crane to ensure they function correctly:</p> <ul style="list-style-type: none"> (a) Load lifting/hoisting and lowering mechanisms; (b) Boom lifting/hoisting and lowering mechanisms; (c) Boom extension and retraction mechanism; (d) Swing mechanism; (e) Travel mechanism; (f) Brakes and clutches; (g) Limit, locking, and safety devices; (h) Suspension systems for cranes that work on rubber (tires); and (i) During the operational testing special attention must be paid to hydraulic and pneumatic valves: spools (sticking, improper return to neutral, and leaks); leaks; valve housing cracks; relief valves. 	
<p>WAC 296-155-53202 Additional Inspection Criteria and Proof Load Testing – Mobile Cranes.</p> <p>(4) Annual and quadrennial proof load testing.</p> <p>(a) Proof loads test must be completed on all hoist lines. The test load must be at least 100 percent but not to exceed 110 percent of rated capacity (i.e., for the crane's configuration of reeving, boom length, etc). The rated capacity must be the capacity shown on the posted load chart</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(c) Crane owners must ensure that cranes are inspected and load proof tested by a certified crane inspector at least annually and after any significant modification or significant repairs of structural parts. If the use of weights for a unit proof load test is not possible or reasonable, other recording</p>

WAC	Source
<p>or as limited by other factors such as hook block capacity or wire rope line pull if the crane is not fully reeved. The test load includes the weight of (or deduction values for) the hook, block, slings, and auxiliary lifting devices (and for some cranes hoist wire rope not accounted for in load charts), and the combined weight deduction values must be subtracted from the nominal test load in order to determine the amount of test weights to be used. Follow original equipment manufacturer (OEM) load chart instructions for weight deduction values. Check accuracy of load indicators where installed. Test procedures for these cranes must follow OEM procedures and recommendations.</p> <p>(b) Annual proof load testing. After the crane has passed the visual and operational tests, a proof load test must be conducted in the as-configured condition and must be performed within the structural and stability section of the manufacturer's load chart, as applicable. This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the examination.</p> <p>(c) Quadrennial proof load testing. No major component (luffing boom, swing-away jibs, fly sections, jibs at variable offsets and boom sections) may be used unless it has been proof load tested within the prior four year period. For jibs with variable offset angles, tests at the maximum offset used and maximum extension of all boom sections.</p> <p>(i) This test must be performed in accordance with this section and documented on the form or in the format approved by the department.</p>	<p>test equipment may be used. In adopting rules implementing this requirement, the department may consider similar standards and practices used by the federal government;</p>

WAC	Source
<p>(ii) A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the inspection.</p> <p>(d) Free rated load test (“on rubber”). Check the stability and operation of crane, carrier, wheels, tires, tracks, brakes, etc., under load by performing the following tests, when lifting without outriggers and/or traveling with the load are permitted at the activity for the type of crane being tested.</p> <p>Note: Ensure all free rated load tests “on rubber” lifting requirements established by the OEM are complied with. Attach taglines to the load to control oscillation. For cranes with outriggers, extend outriggers and maintain minimal clearance (3 to 4 inches) above ground. Test personnel must stand clear of tires during load tests. This test is only required if the owner/lessee wants an “on rubber” certification. If the crane has “on rubber” capabilities and the owner does not desire this certification, the crane certifier must document it on the certification document.</p> <p>(i) Maximum free rated load. Hoist maximum free rated test load at minimum possible radius over the rear (or over the front as required by the OEM). Slowly boom down to the maximum radius for the load. With boom and load hoist pawls (dogs) engaged where applicable, complete (A) and (B). (A) Rotate through the appropriate working arc; (B) Travel a minimum of 50 feet with test load over the rear (or front as required by the OEM) with the boom parallel to the longitudinal axis of the crane carrier.</p>	

WAC	Source
<p>(ii) Stability test. Repeat step (i) above with a test load corresponding to the radii determined as follows: For telescoping boom cranes, test with the boom approximately halfway between fully retracted and fully extended but do not exceed OEM's boom length limitation for lifting on rubber. If no ratings are governed by stability, no stability test is required.</p> <p>Note: When lifting test loads, always lift the load well within the maximum radius and slowly boom down to a pre-measured radius. Lift the test load only high enough to perform the required tests.</p>	
<p>WAC 296-155-53204 Additional Inspection Criteria and Proof Load Testing – Articulating Boom Cranes.</p> <p>(1) After it is determined that the crane configurations meet the criteria in WAC 296-155-53200, the accredited crane certifier must visually inspect the following items, if applicable, on cranes for sound physical condition and that they are functional within the manufacturer's recommendations (not including removal of inspection covers):</p> <p>(a) All control and drive mechanisms for adjustments interfering with proper operation and for excessive wear or contamination by lubricants or other foreign matter;</p> <p>(b) Safety devices for malfunction;</p> <p>(c) All hydraulic hoses, particularly those which flex in normal operation of crane functions;</p> <p>(d) Hooks and latches for deformation, chemical damage, cracks, and wear;</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>(e) Rope reeving for compliance with crane manufacturer's specifications;</p> <p>(f) Electrical apparatus for malfunctioning, signs of excessive deterioration, dirt, and moisture accumulation;</p> <p>(g) Hydraulic system for proper oil level and leaks;</p> <p>(h) Excessively worn or damaged tires. Recommended inflation pressure, cuts, and loose wheel nuts;</p> <p>(i) Connecting pins and locking device for wear and damage;</p> <p>(j) Deformed, cracked, or corroded members in the crane structure and carrier;</p> <p>(k) Loose bolts, particularly mounting bolts;</p> <p>(l) Cracked or worn sheaves and drums;</p> <p>(m) Worn, cracked, or distorted parts such as pins, bearings, shafts, gears, rollers, and locking devices;</p> <p>(n) Excessive wear on brake and clutch system parts and lining;</p> <p>(o) Travel steering, braking, and locking devices, for malfunction;</p> <p>(p) Hydraulic, pneumatic and other pressurized hoses, fittings and tubing,</p>	

WAC	Source
<p>as follows:</p> <ul style="list-style-type: none"> (i) Flexible hose or its junction with the fittings for indications of leaks. (ii) Threaded or clamped joints for leaks. (iii) Outer covering of the hose for blistering, abnormal deformation or other signs of failure/impending failure. (iv) Outer surface of a hose, rigid tube, or fitting for indications of excessive abrasion or scrubbing. <p>(q) Hydraulic and pneumatic pumps and motors, as follows:</p> <ul style="list-style-type: none"> (i) Performance indicators: unusual noises or vibration, low operating speed. (ii) Loose bolts or fasteners. (iii) Shaft seals and joints between pump sections for leaks. <p>(r) Hydraulic and pneumatic cylinders, as follows:</p> <ul style="list-style-type: none"> (i) Drifting. (ii) Rod seals and welded joints for leaks. (iii) Cylinder rods for scores, nick and dents. (iv) Case (barrel) for significant dents. <p>(s) Crane cleanliness and housekeeping. Inspect for trash, oil, grease, debris or excessive dirt on crane components and catwalks, if applicable;</p> <p>(t) Legible warning labels and decals as required by the manufacturer;</p> <p>(u) A portable fire extinguisher, with a basic minimum extinguishing rating of 10 BC must be installed in the cab or at the machinery housing.</p> <p>(v) A legible and applicable operator's manual and load chart is in the</p>	

WAC	Source
operator's cab or station;	
<p>WAC 296-155-53204 Additional Inspection Criteria and Proof Load Testing – Articulating Boom Cranes.</p> <p>(2) Annual proof load testing of articulating boom cranes.</p> <p>(a) Annual proof load testing. After the crane has passed the visual and operational tests, the accredited crane certifier must ensure a proof load test is conducted and must be performed within the structural and stability section of the manufacturer's load chart, as applicable. This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the examination.</p> <p>(b) Test loads must not be less than 100% or more than 110% of the rated load, unless otherwise recommended by the manufacturer.</p> <p>(c) Hoist the tests load to assure that the load is supported by the crane and held by the hoist brake(s).</p> <p>(d) Swing the crane, if applicable, the full range of its swing.</p> <p>(e) Boom the crane up and down within allowable working radius for the test load.</p> <p>(f) Lower the test load, stop and hold the load with the brake(s)</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(c) Crane owners must ensure that cranes are inspected and load proof tested by a certified crane inspector at least annually and after any significant modification or significant repairs of structural parts. If the use of weights for a unit proof load test is not possible or reasonable, other recording test equipment may be used. In adopting rules implementing this requirement, the department may consider similar standards and practices used by the federal government; <i>WAC 296-155-53206(7), 296-155-53208(3), 296-155-53210(2), 296-155-53212(2) and 296-155-53214</i></p>
<p>WAC 296-155-53204 Additional Inspection Criteria and Proof Load Testing – Articulating Boom Cranes.</p> <p>(3) Quadrennial proof load testing. If the articulating boom crane has a</p>	DOSH initiated language.

WAC	Source
jib or boom extension, these components may not be used unless it has been proof load tested within the prior four year period.	
<p>WAC 296-155-53206 Additional Inspection Criteria and Proof Load Testing – Tower Cranes.</p> <p>(1) Tower cranes and tower crane assembly parts must be inspected by a crane certifier both prior to assembly, following erection of the tower crane, after each climbing operation, or reconfiguring the boom, jib, or counterjib before placing the crane in service.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(d) Tower cranes and tower crane assembly parts must be inspected by a certified crane inspector both prior to assembly and following erection of a tower crane;</p>
<p>WAC 296-155-53206 Additional Inspection Criteria and Proof Load Testing – Tower Cranes.</p> <p>(2) The accredited crane certifier must verify a registered professional structural engineer, licensed under chapter 18.43 RCW, has certified that the crane foundations and underlying soil are adequate support for the tower crane with its maximum overturning movement.</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-53206 Additional Inspection Criteria and Proof Load Testing – Tower Cranes.</p> <p>(3) Prior to erecting a tower crane on a nonstandard tower crane base, the accredited crane certifier must verify that the engineering configuration of this base has been reviewed and acknowledged as acceptable by an independent registered professional structural engineer, licensed under chapter 18.43 RCW</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(e) Before installation of a nonstandard tower crane base, the engineering design of the nonstandard base shall be reviewed and acknowledged as acceptable by an independent professional engineer;</p>
<p>WAC 296-155-53206 Additional Inspection Criteria and Proof Load Testing – Tower Cranes.</p> <p>(4) The accredited crane certifier must review the following documents as part of the crane certification process for the current location and inspection period:</p> <p>(a) Crane maintenance records of critical components to ensure maintenance of these components has been performed in accordance with</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>the manufacturer's recommendations;</p> <p>(b) Crane periodic and frequent inspection documentation.</p> <p>(5) After it is determined that the crane configurations meet the criteria in WAC 296-155-53200, the accredited crane certifier must visually inspect the following items, if applicable, on tower cranes for sound physical condition and that they are functional within the manufacturer's recommendations (not including removal of inspection covers):</p> <p>(a) All control and drive mechanisms for interfering with proper operation and for excessive wear or contamination by lubricants or other foreign matter;</p> <p>(b) Motion limiting devices for proper operation with the crane unloaded; each motion should be inched into its limiting device by carefully running at slow speed;</p> <p>(c) Load limiting devices for proper operation and accuracy of settings;</p> <p>(d) Air, hydraulic, and other pressurized lines for deterioration or leakage, particularly those which flex in normal operation;</p> <p>(e) Hydraulic system for proper fluid level;</p> <p>(f) Hydraulic, pneumatic and other pressurized hoses, fittings and tubing, as follows:</p> <p>(i) Flexible hose or its junction with the fittings for indications of leaks.</p> <p>(ii) Threaded or clamped joints for leaks.</p> <p>(iii) Outer covering of the hose for blistering, abnormal deformation or</p>	

WAC	Source
<p>other signs of failure/impending failure.</p> <p>(iv) Outer surface of a hose, rigid tube, or fitting for indications of excessive abrasion or scrubbing.</p> <p>(g) Hydraulic and pneumatic pumps and motors, as follows:</p> <p>(i) Performance indicators: unusual noises or vibration, low operating speed.</p> <p>(ii) Loose bolts or fasteners.</p> <p>(iii) Shaft seals and joints between pump sections for leaks.</p> <p>(h) Hydraulic and pneumatic cylinders, as follows:</p> <p>(i) Drifting.</p> <p>(ii) Rod seals and welded joints for leaks.</p> <p>(iii) Cylinder rods for scores, nick and dents.</p> <p>(iv) Case (barrel) for significant dents.</p> <p>(i) Electrical components for malfunctioning, signs of apparent excessive deterioration, dirt or moisture accumulation, wiring for cracked or split insulation, and loose or corroded terminations;</p> <p>(j) Stationary cranes for manufacturer's recommended grounding of structure and power supply. Rail traveling cranes for grounding of each rail and the power supply per the manufacturer's recommendations;</p> <p>(k) Runway rail and clamps. Inspect for loose, broken or missing clamps;</p> <p>(l) Hooks and safety latches for deformation, cracks, excessive wear, or damage such as from chemicals or heat;</p>	

WAC	Source
<p>(m) Wedges and supports of climbing cranes for looseness or dislocation;</p> <p>(n) Braces or guys supporting cranes masts (towers) and anchor bolt base connections for looseness;</p> <p>(o) Crane structure (including the boom, jib and counter jib):</p> <p>(i) Structural members: deformed, cracked, or significantly corroded.</p> <p>(ii) Bolts, rivets and other fasteners: loose, failed or significantly corroded.</p> <p>(iii) Welds for cracks.</p> <p>(p) Cracked or worn sheaves and drums;</p> <p>(q) Worn, cracked, or distorted parts such as pins, bearings, shafts, gears, rollers, locking and clamping devices, sprockets, and drive chains or belts;</p> <p>(r) Excessive wear on brake and clutch system parts, linings, pawls, and ratchets;</p> <p>(s) Load, wind, and other indicators for inaccuracies outside the tolerances recommended by the manufacturer;</p> <p>(t) Travel mechanisms for malfunction, excessive wear or damage;</p> <p>(u) A legible and applicable operator's manual and load chart is in the operator's cab;</p> <p>(v) Crane cleanliness and housekeeping. Inspect for trash, oil, grease,</p>	

WAC	Source
<p>debris or excessive dirt on crane components and catwalks, if applicable;</p> <p>(w) A portable fire extinguisher, with a basic minimum extinguishing rating of 10 BC must be installed in the cab or at the machinery housing;</p> <p>(x) When applicable, tower tie-in collars, struts, and connections to building structure are structurally sound, free of cracks, distortion, excessive wear or corrosion. Pins and structural bolts are tight and installed per the manufacturer's specification;</p> <p>(y) Ballast blocks in place and secured per manufacturer's recommendations;</p> <p>(z) For cranes that telescope, the internal tower by a bottom climbing frame the climbing mechanism operates within the manufacturer's specifications;</p> <p>(aa) For cranes that top climb, the climbing frame operates within the manufacturer's specifications;</p> <p>(bb) A means to prevent traveling tower cranes running into stops while under power;</p> <p>(cc) A functional audible warning alarm that automatically sounds whenever the traveling tower crane travels;</p> <p>(dd) Wire rope reeving for compliance with the manufacturer's specifications;</p> <p>(ee) Wire rope, in accordance with WAC 296-155-53200(5);</p>	

WAC	Source
<p>(ff) Safety devices and operational aids for proper operation (including significant inaccuracies);</p> <p>(gg) Legible warning labels and decals as required by the manufacturer;</p> <p>(hh) Steps, ladders, handrails and guards are in safe and usable condition.</p> <p>(6) Additional requirements for tower cranes prior to performing a proof load test.</p> <p>Note: General requirements relating to pre-proof load tests for all cranes are located in WAC 296-155-53200.</p> <p>(a) When tower cranes are erected, and before placing in service, all functional motions, motion limiting, load limiting devices, locking and safety devices, brakes and clutches must be tested for operation and be within the manufacturer's specification prior to placing the crane in operation.</p> <p>(b) Proof load tests require the use of certified weights, or scaled weights using a certified scale with a current certificate of calibration.</p> <p>(c) Functional motion test must be at crane manufacturer's rated load. Each test must include:</p> <ul style="list-style-type: none"> (i) Load hoisting and lowering; (ii) Jib (boom) hoisting and lowering, or trolley travel; (iii) Slewing motion; (iv) Travel motion when rail mounted; (v) Brakes and clutches; and 	

WAC	Source
<p>(vi) Limit, locking, and safety devices.</p> <p><i>Note:</i> Functional motion tests made after climbing or telescoping may be performed without a load.</p> <p>(d) The functional motion test listed in subsection (6)(c) must continue until all controls, drives, and braking systems have been engaged and have functioned per the crane manufacturer's specifications.</p> <p>(e) Order in which test of tower cranes are to be performed is as follows: (i) Functional motion test without rated load; (ii) Functional motion test at crane manufacturer's rated load. For other than traveling cranes, these test may be combined with test of base structural support or foundation system given in subsection (6)(c); (iii) Test of base structural support or foundation per subsection (6)(f).</p> <p>(f) During functional motion tests, the crane's base structural support or foundation system must be visually checked by the accredited crane certifier. If any part of the crane's base structural support or foundation system shows excessive visual displacement, visual distress, or audible distress, then the lifted load must be lowered at hoist creep speed and all crane operations are to cease. An evaluation must then be made by the accredited crane certifier.</p>	
<p>(7) Proof load testing of tower cranes. Setting hoist load limits for tower cranes.</p> <p>(a) Annual proof load testing. After the crane has passed the visual and operational tests, the accredited crane certifier must ensure a proof load test is conducted and must be performed according to the manufacturer's</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(c) Crane owners must ensure that cranes are inspected and load proof tested by a certified crane inspector at least annually and after any significant modification or significant</p>

WAC	Source
<p>recommendations. This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the examination.</p> <p>(b) Tower crane hoist load limit switches must be set in accordance with the manufacture's specifications using specified certified weights. Procedure is to be verified by the accredited crane certifier. In the absence of the manufacturer's specifications, hoist load limit switches must be verified by means of a static test using test loads of 102.5 percent to 110 percent of the applicable ratings. Test loads are to be lifted at creep speed until just clear of the ground.</p> <p>(c) Setting of hoist load limits must be documented on the form provided by the department. A copy of the completed form and inspection worksheets must be sent to the department within ten days upon completion of the examination.</p> <p>(d) After erection of fixed freestanding tower cranes, the base structural support or foundation system on which the crane is supported must be tested before placing the crane in service. The test must be conducted with the crane manufacturer's rated load placed at maximum radius permitted by site conditions. When the base structural support or foundation is symmetrical, the crane's jib (boom) must be rotated through 90 degrees with 10 minute stops at the starting position and at each 45 degree position. When the support is asymmetrical, the crane's jib (boom) must be rotated through 360 degrees with 10 minute stops at the starting position and at each 45 degree position.</p>	<p>repairs of structural parts. If the use of weights for a unit proof load test is not possible or reasonable, other recording test equipment may be used. In adopting rules implementing this requirement, the department may consider similar standards and practices used by the federal government;</p>

WAC	Source
<p>(e) After erection of rail traveling tower cranes, the base structural support or foundation system to which the rail is attached must be tested before placing the crane in service. The test must be conducted with the crane manufacturer's rated load placed at maximum radius permitted by site conditions. The jib (boom) must be located over the bogie. The crane must travel the entire length of runway, returning with the same load over the bogie on the opposite rail.</p>	
<p>WAC 296-155-53208 Additional Inspection Criteria and Proof Load Testing - Self-erecting tower cranes.</p> <p>(1) After it is determined that the crane configurations meet the criteria in WAC 296-155-53200, the accredited crane certifier must visually inspect the following items, if applicable, on cranes for sound physical condition and that they are functional within the manufacturer's recommendations (not including removal of inspection covers):</p> <p>(a) For cranes that telescope the internal tower by a climbing frame the climbing mechanism is structurally sound; is free of cracks, distortion, excessive wear or corrosion; operates within the manufacturer's specifications;</p> <p>(b) Structural bolts are tightened;</p> <p>(c) All control and drive mechanisms for interfering with proper operation and for excessive wear or contamination by lubricants or other foreign matter;</p> <p>(d) Motion limiting devices for proper operation with the crane unloaded; each motion should be inched into its limiting device by carefully running at slow speed;</p> <p>(e) Load limiting devices for proper operation and accuracy of settings;</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>(f) Air, hydraulic, and other pressurized lines for deterioration or leakage, particularly those which flex in normal operation;</p> <p>(g) Hydraulic system for proper fluid level;</p> <p>(h) Hydraulic, pneumatic and other pressurized hoses, fittings and tubing, as follows:</p> <ul style="list-style-type: none"> (i) Flexible hose or its junction with the fittings for indications of leaks. (ii) Threaded or clamped joints for leaks. (iii) Outer covering of the hose for blistering, abnormal deformation or other signs of failure/impending failure. (iv) Outer surface of a hose, rigid tube, or fitting for indications of excessive abrasion or scrubbing. <p>(i) Hydraulic and pneumatic pumps and motors, as follows:</p> <ul style="list-style-type: none"> (i) Performance indicators: unusual noises or vibration, low operating speed. (ii) Loose bolts or fasteners. (iii) Shaft seals and joints between pump sections for leaks. <p>(j) Hydraulic and pneumatic cylinders, as follows:</p> <ul style="list-style-type: none"> (i) Drifting. (ii) Rod seals and welded joints for leaks. (iii) Cylinder rods for scores, nick and dents. (iv) Case (barrel) for significant dents. <p>(k) Electrical components for malfunctioning, signs of apparent excessive deterioration, dirt or moisture accumulation, wiring for cracked or split insulation, and loose or corroded terminations;</p>	

WAC	Source
<p>(l) Ensure crane is grounded per manufacturer's specifications;</p> <p>(m) Hooks and safety latches for deformation, cracks, excessive wear, or damage such as from chemicals or heat;</p> <p>(n) Crane structure (including the boom, jib and counter jib):</p> <p>(i) Structural members: deformed, cracked, or significantly corroded.</p> <p>(ii) Bolts, rivets and other fasteners: loose, failed or significantly corroded.</p> <p>(iii) Welds for cracks.</p> <p>(o) Cracked or worn sheaves and drums;</p> <p>(p) Worn, cracked, or distorted parts such as pins, bearings, shafts, gears, rollers, locking and clamping devices, sprockets, and drive chains or belts;</p> <p>(q) Excessive wear on brake and clutch system parts, linings, pawls, and ratchets;</p> <p>(r) Load, wind, and other indicators for inaccuracies outside the tolerances recommended by the manufacturer;</p> <p>(s) A legible and applicable operator's manual and load chart is in the operator's station;</p> <p>(t) Crane cleanliness and housekeeping. Inspect for trash, oil, grease, debris or excessive dirt on crane components and catwalks, if applicable;</p>	

WAC	Source
<p>(u) A portable fire extinguisher, with a basic minimum extinguishing rating of 10 BC must be installed in the cab or at the machinery housing;</p> <p>(v) Ballast blocks in place and secured per manufacturer's recommendations;</p> <p>(w) Wire rope reeving for compliance with the manufacturer's specifications;</p> <p>(x) Wire rope, in accordance with WAC 296-155-53200(5);</p> <p>(y) Safety devices and operational aids for proper operation (including significant inaccuracies);</p> <p>(z) Legible warning labels and decals as required by the manufacturer;</p> <p>(aa) Steps, ladders, handrails and guards are in safe and usable condition.</p> <p>(2) Additional requirements for self-erecting tower cranes prior to performing a proof load test.</p> <p>Note: General requirements relating to pre-proof load tests for all cranes are located in WAC 296-155-53200.</p> <p>(a) Functional motion test must be at crane manufacturer's rated load. Each test must include:</p> <p>(i) Load hoisting and lowering.</p> <p>(ii) Jib (boom) hoisting and lowering, or trolley travel.</p>	

WAC	Source
<p>(iii) Slewing motion.</p> <p>(iv) Brakes and clutches.</p> <p>(v) Limit, locking, and safety devices</p> <p>(b) The functional motion test listed in subsection (2)(a) must continue until all controls, drives, and braking systems have been engaged and have functioned per the crane manufacturer's specifications.</p> <p>(c) Order in which test of self-erecting tower cranes are to be performed is as follows:</p> <p>(i) Functional motion test without rated load</p> <p>(ii) Functional motion test at crane manufacturer's rated load. These test may be combined with test of base structural support or foundation system given in subsection (2)(a).</p> <p>(d) During functional motion tests, the crane's base structural support or foundation system must be visually checked by the accredited crane certifier. If any part of the crane's base structural support or foundation system shows excessive visual displacement, visual distress, or audible distress, then the lifted load must be lowered at hoist creep speed and all crane operations are to cease. An evaluation must then be made by the accredited crane certifier.</p>	
<p>WAC 296-155-53208 Additional Inspection Criteria and Proof Load Testing - Self-erecting tower cranes.</p> <p>(3) Annual proof load testing of self-erecting tower cranes.</p> <p>(a) Annual proof load testing. After the crane has passed the visual and operational tests, the accredited crane certifier must ensure a proof load test is conducted and must be performed according to the manufacturer's recommendations. This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(c) Crane owners must ensure that cranes are inspected and load proof tested by a certified crane inspector at least annually and after any significant modification or significant repairs of structural parts. If the use of weights for a unit proof load test is not possible or reasonable, other recording test equipment may be used. In adopting rules implementing this requirement, the department may consider similar</p>

WAC	Source
<p>days upon completion of the examination.</p> <p>(b) The structural support or foundation examination during proof load test:</p> <p>(i) This test must be conducted with the rated load placed at maximum radius permitted by site conditions. The superstructure must be rotated through 360 degrees with 5 minute stops at each outrigger position. If any part of the support structure becomes displaced or distressed, all crane operations must stop until an evaluation is made by a qualified person.</p> <p>(ii) For rail-mounted cranes, a load test must be conducted with the jib in the position causing maximum loading on one wheel or bogie. The test must comprise traveling the entire length of the runway, then returning with the same load on the other rail. If a sleeper or support becomes displaced or damaged, crane operations must stop until an evaluation is made by a qualified person or until track ballast has been reset, or repairs made and a satisfactory test performed.</p> <p>(c) Self-erecting tower crane hoist load limit switches must be set in accordance with the manufacturer's specifications using specified certified weights. Procedure is to be verified by the accredited crane certifier.</p> <p>(d) Setting of hoist load limits must be documented on the form provided by the department. A copy of the completed form and inspection worksheets must be sent to the department within ten days upon completion of the examination.</p>	<p>standards and practices used by the federal government;</p>

WAC	Source
<p>WAC 296-155-53210 Additional Inspection Criteria and Proof Load Testing – Overhead and Bridge Cranes.</p> <p>(1) After it is determined that the crane configurations meet the criteria in WAC 296-155-53200, the accredited crane certifier must visually inspect, without disassembly, and if applicable, the following items on overhead and bridge cranes for sound physical condition and that they are functional within the manufacturer's recommendations (not including removal of inspection covers):</p> <p>(a) Controllers. Control mechanisms for interfering with proper operation. Control and drive mechanisms for apparent excessive wear of components and contamination by lubricants, water or other foreign matter;</p> <p>(b) Load hooks. Inspect for damage wear to hook nuts, mousing device and hook swivel. Check for deformation, cracks, excessive wear, or damage such as from chemicals or heat. Inspect blocks for wear to sheaves, check plates, and pins. Check for loose pins, bolts and guards;</p> <p>(c) Sheaves and bearings. Check all sheaves and bearings for lubrication and excessive wear. Ensure sheaves turn freely. Check sheave pin locking device;</p> <p>(d) Structural supports. Inspect for damage or bent girders, girder seat top plate, diaphragms and structural column connections. Check for loose bolts or rivets, and cracks;</p> <p>(e) Bridge inspection.</p> <p>(i) Check complete structure for broken, cracked, damaged, missing, or</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>corroded parts and members.</p> <p>(ii) Handrails, Walkways, and Ladders. Inspect for loose, missing, bent, deteriorated or misaligned members, loose bolts, rivets, broken welds and hangers.</p> <p>(f) Brackets. Check for cracked or corroded welds, missing or loose bolts, bent or cracked brackets;</p> <p>(g) End stops. Inspect for damaged wheels, broken welds, loose or missing bolts, damaged bumpers, missing pins or damaged plates;</p> <p>(h) Runway rail and clamps. Inspect for loose, broken or missing clamps. Check the condition of railhead and side wear, rail splice plates and or welds, rail gaps and associated bolts, wedges, connectors and rail switches;</p> <p>(i) Crane alignment. Inspect for proper bridge end float while crane travels in both directions on runway. Check all corner connections for rust, shear marks, loose or missing bolts, nuts and washers. Inspect square marks and legibility of dimension;</p> <p>(j) Wheels and bearings. Inspect wheels for wear, flat spots, chips, flange wear, cracks, loose axle pins, or securing devices. Check bearing clearance, chatter, loose bearing caps and lubrication;</p> <p>(k) Trolley. Check for loose, missing, broken or bent members. Inspect for loose, faulty or missing coupling guards. Check for broken, loose or missing axle pins. Inspect for axle pins displaying excessive wear;</p>	

WAC	Source
<p>(l) Trolley rail. Inspect for bent or damaged members, loose bolts, rivets, guards, trolley rail clamps, end stops and broken welds. Check condition of rail head and side wear, rail splice plates and/or welds and rail gaps;</p> <p>(m) Trolley conductors. Inspect insulators and clamps, loose connectors, bent, pitted or damaged wires or collectors;</p> <p>(n) Shafts, couplings, and bearings. Inspect shafts for vibration, cuts and nicks, loose or worn keyways and misalignment. Check coupling for wear, loose bolts or keys and misalignment. Inspect bearing for clearance, chatter, loose bearings caps and proper lubrication;</p> <p>(o) Gearing. Inspect gears for worn teeth, cracked teeth, superficial root cracks, pitting, unusual indentation or wear marks, full contact or end loading, loose set screws and keys. Check guards and covers. Inspect gear cases for excessive noise and vibration, proper lubrication and leaking;</p> <p>(p) Wire rope and drum. Inspect wire rope for damage. Check rope clip fittings and associated mounting hardware for wear and damage. Inspect drum grooves for excessive wear. Inspect drum pedestal and bearing condition. Check for cracks in drum;</p> <p>(q) Electrical items. Check all contacts for proper alignment and evidence of excess heating or unusual arcing. Inspect all coils, contact leads, shunts and wires, fuses or overload devices for loose connections and evidence of overheating. Inspect panel board and arc shields for cracks, loose bolts, dirt and moisture. Check panel marking for legibility. Inspect speed control resistors for damaged insulation, cracked or broken</p>	

WAC	Source
<p>grids, loose connections, bolts and brackets;</p> <p>(r) Motor. Inspect for damage, bearing noise, vibration and lubrication, spark and cleanliness of commutator and brush wear, loose hold down bolts and motor brackets. Inspect commutator or slip rings for evidence of overheating and brush sparking. Inspect motor leads and insulators, damaged or deteriorated insulation and loose connections. Inspect brush holder for proper clearance to commutator or slip rings, and freedom of brushes;</p> <p>(s) Brakes. Inspect for wear in linkage, pins and cams, weakness of springs, wear and condition of lining, smoothness of the drum, heat check crack and clearance between drum or disk. Inspect for improper solenoid air gap; evidence of overheating; damaged brass, and loose core laminations; delay or restriction in opening of brakes;</p> <p>(t) Hoist brakes. Inspect for wear in linkage, pins and cams weakness of springs, wear and condition of lining, smoothness of drum, heat check cracks and clearance between drum of disks. Inspect for improper solenoid air gap; evidence of overheating; damaged brass, and loose core laminations; delay or restriction in opening of brakes;</p> <p>(u) Limit switches. Remove covers and inspect all electrical and mechanical components for malfunction including contacts, springs, ratchets, pins, arm and insulators, rollers, cams and dogs. Inspect cover gaskets, counterweight guides. Check all securing bolts and guards. Check for weather or moisture damage. Check for proper operation;</p> <p>(v) Crane cleanliness and housekeeping. Inspect for trash, oil, grease,</p>	

WAC	Source
<p>debris or excessive dirt on crane components and catwalks, if applicable;</p> <p>(w) Operation of crane controls. Operate all crane controls and check for proper operation. Check for smooth and regular motions without abnormal sensations, hesitations, binding, vibrations, shimmy, or irregularity;</p> <p>(x) Warning device/fire protection. Inspect for proper operation of sirens, horns, bells and lights. Check switches and inspect wiring and connections;</p> <p>(y) A legible and applicable operator’s manual and load chart is in the operator’s cab or station;</p> <p>(z) A portable fire extinguisher, with a basic minimum extinguishing rating of 10 BC must be installed in the cab or at the machinery housing;</p>	
<p>WAC 296-155-53210 Additional Inspection Criteria and Proof Load Testing – Overhead and Bridge Cranes.</p> <p>(2) Annual proof load testing of bridge/overhead cranes.</p> <p>(a) Annual proof load testing. After the crane has passed the visual and operational tests, the accredited crane certifier must ensure a proof load test is conducted and must be performed according to the manufacturer’s recommendations or a registered professional structural engineer (RPSE). This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the examination.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>c) Crane owners must ensure that cranes are inspected and load proof tested by a certified crane inspector at least annually and after any significant modification or significant repairs of structural parts. If the use of weights for a unit proof load test is not possible or reasonable, other recording test equipment may be used. In adopting rules implementing this requirement, the department may consider similar standards and practices used by the federal government;</p>

WAC	Source
<p>(b) The proof load test must be at least 100 percent but not to exceed 125 percent of the rated capacity.</p> <p>(c) This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the examination.</p> <p>(d) Hoist the test load a distance to assure that the load is supported by the crane and held by the hoist brake(s).</p> <p>(e) Transport the test load by means of the trolley for the full length of the bridge, as practical.</p> <p>(f) Transport the test load by means of the bridge for the full length of the runway in one direction with the trolley as close to the extreme right-hand end of the crane as practical, and in the other direction with the trolley as close to the left-hand end of the crane as practical.</p> <p>(g) Lower the test load, and stop and hold the test load with the brake(s).</p> <p>(h) Mechanical load brake tests. Hoist test load and hold for 5 minutes. Release the holding brake, either mechanically or electrically to verify mechanical load brake function or hoist the rated load then lower, monitoring the hoist for any speed control issues.</p>	
<p>WAC 296-155-53212 Additional Inspection Criteria and Proof Load Testing – Derricks.</p> <p>(1) After it is determined that the derrick configurations meet the criteria in WAC 296-155-53200, the accredited derrick certifier must visually</p>	<p>DOSH initiated language.</p>

WAC	Source
<p>inspect the following items, if applicable, on derricks for sound physical condition and that they are functional within the manufacturer's recommendations (not including removal of inspections covers):</p> <p>(a) All control and drive mechanisms for adjustments interfering with proper operation and for excessive wear or contamination by lubricants or other foreign matter;</p> <p>(b) All chords and lacing, tension in guys, plumb of the mast, external indication of deterioration or leakage in air or hydraulic systems;</p> <p>(c) Derrick hooks for deformation or cracks, distortion causing an increase in throat opening of 5 percent not to exceed ¼ inch or as recommended by the manufacturer. Any wear exceeding 10 percent (or as recommended by the manufacturer) of the original section dimension of the hook;</p> <p>(d) Rope reeving for noncompliance with derrick manufacturer's specifications;</p> <p>(e) Hoist brakes, clutches, and operating levers;</p> <p>(f) Electrical apparatus for malfunctioning, signs of excessive deterioration, dirt and moisture accumulation;</p> <p>(g) Structural members for deformation, cracks, and corrosion;</p> <p>(h) Crane cleanliness and housekeeping. Inspect for trash, oil, grease, debris or excessive dirt on crane components and catwalks, if applicable;</p>	

WAC	Source
<p>(i) Bolts and rivets for tightness;</p> <p>(j) Parts such as pins, bearings, shafts, gears, sheaves, drums, rollers, locking and clamping devices, for wear, cracks, and distortion;</p> <p>(k) Gudgeon pin for cracks, wear and distortion;</p> <p>(l) Foundation or supports for continued ability to sustain the imposed loads;</p> <p>(m) A legible and applicable operator’s manual and load chart is in the operator’s cab or station;</p> <p>(n) A portable fire extinguisher, with a basic minimum extinguishing rating of 10 BC must be installed in the cab or at the machinery housing.</p>	
<p>WAC 296-155-53212 Additional Inspection Criteria and Proof Load Testing – Derricks.</p> <p>(2) Annual proof load testing of derricks.</p> <p>(a) Annual proof load testing. After the derrick has passed the visual and operational tests, the accredited derrick certifier must ensure a proof load test is conducted and must be performed at the maximum and minimum boom angles or radii or as close to these as practical and at such intermediate radii as the derrick manufacturer or RPSE may deem necessary. This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the examination.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(c) Crane owners must ensure that cranes are inspected and load proof tested by a certified crane inspector at least annually and after any significant modification or significant repairs of structural parts. If the use of weights for a unit proof load test is not possible or reasonable, other recording test equipment may be used. In adopting rules implementing this requirement, the department may consider similar standards and practices used by the federal government;</p>

WAC	Source								
<p>(b) Proof load tests and safe working load ratings must be based on the designed load ratings at the ranges of boom angle or operating radii. Proof loads must be as per the manufacturer’s recommendations. When the manufacturer recommendations are not available follow the requirements in the Table below:</p> <p>Table – Derrick Load Test</p> <table border="1" data-bbox="191 618 1127 812"> <thead> <tr> <th data-bbox="199 625 661 695">Safe Working Load SWL</th> <th data-bbox="661 625 1119 695">Proof Load</th> </tr> </thead> <tbody> <tr> <td data-bbox="199 695 661 735">Up to 20 tons</td> <td data-bbox="661 695 1119 735">25 percent in excess</td> </tr> <tr> <td data-bbox="199 735 661 776">20-50 tons</td> <td data-bbox="661 735 1119 776">5 tons in excess</td> </tr> <tr> <td data-bbox="199 776 661 812">Over 50 tons</td> <td data-bbox="661 776 1119 812">10 percent in excess</td> </tr> </tbody> </table> <p>(c) Hoist the test load a few inches and hold to verify that the load is supported by the derrick and held by the hoist brake(s).</p> <p>(d) Swing the derrick, if applicable, the full range of its swing, at the maximum allowable working radius for the test load.</p> <p>(e) Boom the derrick up and down within the allowable working radius for the test load.</p> <p>(f) Lower the test load, stop and hold the load with the brake(s).</p> <p>(g) After satisfactory completion of a proof load test, the derrick and all component parts thereof shall be carefully examined in all applicable requirements in this section.</p>	Safe Working Load SWL	Proof Load	Up to 20 tons	25 percent in excess	20-50 tons	5 tons in excess	Over 50 tons	10 percent in excess	
Safe Working Load SWL	Proof Load								
Up to 20 tons	25 percent in excess								
20-50 tons	5 tons in excess								
Over 50 tons	10 percent in excess								

WAC	Source
<p>(h) This test must be documented on the form or in the format approved by the department. A copy of this completed form and inspection worksheets must be sent to the department within ten working days upon completion of the examination.</p>	
	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(f) A certified crane inspector must notify the department and the crane owner if, after inspection, the certified crane inspector finds that the crane does not meet safety or health standards. A certified crane inspector shall not attest that a crane meets safety or health standards until any deficiencies are corrected and the correction is verified by the certified crane inspector; and</p>
<p>WAC 296-155-53214 Crane De-Certification and Reinstatement.</p> <p>(1) If any of the following occur, the certification becomes invalid:</p> <p>(b) Any overload, other than proof load testing, or one that has been approved in writing in advance by the crane manufacturer or a RPE;</p> <p>(c) Any significant modifications or significant repairs of a load sustaining/bearing part.</p> <p>Note: Replacement of hoisting rope does not constitute de-certification.</p> <p>(2) The owner or lessee must notify the crane certification section by phone within 24 hours if any of the above occurs.</p>	<p>RCW 49.17.420 Construction Crane Certification Program – Rules – Certificate of Operation.</p> <p>(c) Crane owners must ensure that cranes are inspected and load proof tested by a certified crane inspector at least annually and after any significant modification or significant repairs of structural parts. If the use of weights for a unit proof load test is not possible or reasonable, other recording test equipment may be used. In adopting rules implementing this requirement, the department may consider similar standards and practices used by the federal government;.</p>

WAC	Source
<p>(3) The certification may be re-instated only after affected components have been re-inspected by an accredited crane certifier. If the accredited crane certifier identifies any deficiencies during the re-inspection, the deficiencies must be corrected before the certification can be reinstated. If the accredited crane certifier believes proof load testing should be conducted prior to reinstatement of the certification, proof load testing shall be conducted. In the case of major modifications or repairs to important load sustaining/bearing parts, proof load testing shall be performed prior to reinstatement. The accredited crane certifier must notify the department that the certification has been reinstated.</p>	
<p>WAC 296-155-53214 Crane De-Certification and Reinstatement. (1) If any of the following occur, the certification becomes invalid:</p> <p>(a) Contact with an energized power line;</p>	<p>DOSH initiated language.</p>
<p>WAC 296-155-533 Crane Operator Qualifications and Certification. WAC 296-155-53300 Operator qualifications and certification. (1) Prior to operating any crane covered under chapter 296-155 WAC, Part L, with the exception of the trainee/apprentice requirements outlined in subsection (2) of this section, the employer must ensure that the crane operator:</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity.</p> <p>(1) Except for training purposes as provided in subsection (3) of this section, an employer or contractor shall not permit a crane operator to operate a crane unless the crane operator is a qualified crane operator.</p>
	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity.</p> <p>(2) The department shall establish, by rule, requirements that must be met to be considered a qualified crane operator. In establishing rules, the department shall consult nationally recognized crane standards for crane operator certification.</p>

WAC	Source
<p>WAC 296-155-533 Crane Operator Qualifications and Certification.</p> <p>WAC 296-155-53300 Operator qualifications and certification. Has a valid crane operator certificate, for the type of crane to be operated, issued by a crane operator testing organization accredited by a nationally recognized accrediting agency. The operator certification must include a successful passing of a written and practical examination.</p> <p>Notes: An operator's certificate issued by the accredited testing agency is valid for a five year period, and must be renewed to ensure operators maintain qualified operator status. For self-erecting tower cranes, the department will accept a tower crane certification issued by a nationally accrediting testing agency. For derricks, the department will accept, at a minimum, a lattice boom truck or crawler mobile crane operator's certificate.</p>	<p>The rules must include, at a minimum, the following:</p> <p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity.</p> <p>(a) The crane operator must have a valid crane operator certificate, for the type of crane to be operated, issued by a crane operator testing organization accredited by a nationally recognized accrediting agency which administers written and practical examinations, has procedures for recertification that enable the crane operator to recertify at least every five years, and is recognized by the department;</p>
<p>WAC 296-155-533 Crane Operator Qualifications and Certification. (1)(b) Has crane hours of experience as shown in Table 1; and</p> <p>See Crane Operator Experience, Table 1 at end of document</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (b) The crane operator must have up to two thousand hours of documented crane operator experience, which meets experience levels established by the department for crane types and capacities by rule; and</p>
<p>WAC 296-155-53300 Operator qualifications and certification. Pass a substance abuse test conducted by a recognized laboratory.</p> <p>Exemption: When it is necessary in the performance of their duties, manufacture representatives, factory representatives and maintenance personnel are not required to be certified crane operators.</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (c) The crane operator must pass a substance abuse test conducted by a recognized laboratory service.</p>

WAC	Source
<p><i>Note:</i> Cranes and other lifting machines that are exempt can be found in WAC 296-155-52900(2).</p>	
<p>WAC 296-155-53300 Operator qualifications and certification. (2) Pre-qualification/certification training period. An employee who is not a qualified crane operator as outlined in subsection (1) is permitted to operate the crane as part of his/her training providing the following requirements are met:</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (3) An apprentice operator or trainee may operate a crane when:</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(a) The employee (“trainee/apprentice”) must be provided with sufficient training prior to operating the crane to enable the trainee to operate the crane safely under limitations established by this section (including continuous supervision) and any additional limitations established by the employer.</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (a) The apprentice operator or trainee has been provided with training prior to operating the crane that enables the apprentice operator or trainee to operate the crane safely;</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(b) The tasks performed by the trainee/apprentice while operating the crane must be within the trainee’s ability, as determined by the supervising qualified crane operator.</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (b) The apprentice operator or trainee performs operating tasks that are within his or her ability, as determined by the supervising qualified crane operator; and</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(c) Qualified crane operator. While operating the equipment, the trainee/apprentice must be continuously supervised by a qualified crane operator who meets the following requirements:</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (c) The apprentice operator or trainee is under the direct and continuous supervision of a qualified crane operator who meets the following requirements:</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(c)(i) The qualified crane operator is an employee or agent of the</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees –</p>

WAC	Source
trainee's/apprentice's employer.	<p>Reciprocity. (i) The qualified crane operator is an employee or agent of the employer of the apprentice operator or trainee;</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(c)(ii) The qualified crane operator under this section and is familiar with the proper use of the equipment's controls.</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (ii) The qualified crane operator is familiar with the proper use of the crane's controls;</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(c)(iii) While supervising the trainee/apprentice, the qualified crane operator performs no tasks that detract from the qualified crane operator's ability to supervise the trainee/apprentice.</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (iii) While supervising the apprentice operator or trainee, the qualified crane operator performs no tasks that detract from the qualified crane operator's ability to supervise the apprentice operator or trainee;</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(c)(iv) For cranes other than tower cranes: the qualified crane operator and the trainee/apprentice must be in direct line of sight of each other. In addition, they must communicate verbally or by hand signal.</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (iv) For equipment other than tower cranes, the qualified crane operator and the apprentice operator or trainee must be in direct line of sight of each other and shall communicate verbally or by hand signals; and</p>
<p>WAC 296-155-53300 Operator qualifications and certification. (2)(c)(v) For tower cranes: the qualified crane operator and the trainee/apprentice must be in direct communication with each other.</p>	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity. (v) For tower cranes, the qualified crane operator and the apprentice operator or trainee must be in direct communication with each other.</p>
WAC 296-155-53300 Operator qualifications and certification.	DOSH initiated language.

WAC	Source
<p>(d) The trainee/apprentice must not operate the crane in any of the following circumstances:</p> <p>(i) If any part of the crane, load line or load (including rigging and lifting accessories), if operated up to the crane's maximum working radius in the work zone, could get within 20 feet of a power line that is up to 350 kV, or within 50 feet of a power line that is over 350 kV;</p> <p>(ii) If the crane is used to hoist personnel;</p> <p>(iii) In a multiple-crane lift situation; or</p> <p>(iv) Multiple-lift rigging, as defined in WAC 296-155-52902 of this chapter, can only be accomplished by the trainee/apprentice when the qualified crane operator determines that the trainee's/apprentice's skills are sufficient for this high-skill work.</p> <p>(v) Critical lifts, excluding tower cranes, and as defined in WAC 296-52902 of this chapter, can only be accomplished by the trainee/apprentice when the qualified crane operator determines that the trainee's/apprentice's skills are sufficient for this high-skill work.</p> <p>(3) The employer must obtain documentation showing hours of crane operator experience and crane related experience separated out by crane type and capacity.</p> <p>(4) For experience obtained prior to January 1, 2010, the employer may accept a declaration from the crane operator attesting to actual hours of crane operator experience and crane related experience separated out by</p>	

WAC	Source
<p>crane type and capacity. Hours documented prior to 2010 will count towards the hour requirements of actual crane operating experience and crane related experience.</p> <p>(5) Beginning January 1, 2010, crane operator experience and crane related experience must be documented and separated out by crane type and capacity. If the employer is documenting crane operating and/or related crane experience hours, the employer must provide a copy of the hours to the operator as soon as practical, if requested.</p>	
	<p>RCW 49.17.430 Qualified Construction Crane Operators – Rules – Apprentice Operators or Trainees – Reciprocity.</p> <p>(4) The department may recognize crane operator certification from another state or territory of the United States as equivalent to qualified crane operator requirements if the department determines that the other jurisdiction's credentialing standards are substantially similar to the qualified crane operator requirements.</p>
	<p>RCW 49.17.440 Construction Crane Safety – Rules – Implementation. (Effective January 1, 2010)</p> <p>The department of labor and industries shall adopt rules necessary to implement RCW 49.17.400 through 49.17.430.</p>

Appendix 5: Cost Breakdown by Firm Size

Table A5.A Estimating the Cost per Employee for Large Companies.						
Costs by Category	Item	Unit Costs Low	Unit Costs High	Number of Workers Per Firm	Low Total	High Total
Certifiers Accreditaion						
Experience	Existing effort	\$ -				
Application	Time Cost	\$ 3,648		5.52	\$ 20,137	
Training (Non-Union)	Fee	\$ 325	\$ 1,295		\$ 1,794	\$ 7,148
Exam	Fee	\$ 215	\$ 275	5.52	\$ 1,187	\$ 1,518
3 Year Renewal						
Experience	Time Cost	\$ 3,648		5.52	\$ 20,137	
Application	Time Cost	\$ 1,824		5.52	\$ 10,068	
Continuing education	Training Cost	\$ 826		5.52	\$ 4,560	
6 Year Renewal Exam	Fee, Time Cost	\$ 3,863	\$ 3,923	5.52	\$ 21,324	\$ 21,655
Recertifying Cranes	2 cases only	\$ 1,500	\$ 3,000		\$ 3,000	\$ 6,000
	Crane Time	\$ 150			\$ 2,400	
Sub Total W/O Recertification					\$ 79,206	\$ 85,223
Annual Effect					\$ 8,801	\$ 9,469
Ratio for Large Companies \$/employee					\$ 3	\$ 3
Ratio for Large Companies for recertification: \$/employee					\$ 0.08	\$ 0.13

Table A5.B. Estimating the Cost per Employee for Small Companies						
Costs by Category	Item	Unit Costs Low	Unit Costs High	Number of Workers Per Firm	Low Total	High Total
Certifiers Accreditaion						
-Experience	Existing effort	\$ -				
-Application	Time Cost	\$ 5,853		5.37	\$ 31,430	
-Training (Non-Union)	Fee	\$ 325	\$ 1,295		\$ 1,745	\$ 6,954
-Exam	Fee	\$ 215	\$ 275	5.37	\$ 1,155	\$ 1,477
3 Year Renewal						
-Experience	Time Cost	\$ 5,853		5.37	\$ 31,430	
-Application	Time Cost	\$ 2,926		5.37	\$ 15,715	
-Continuing education	Training Cost	\$ 826		5.37	\$ 4,436	
6 Year Renewal Exam	Fee, Time Cost	\$ 6,068	\$ 6,128	5.37	\$ 32,584	\$ 32,906
Recertifying Cranes	2 cases only	\$ 1,500	\$ 3,000		\$ 3,000	\$ 6,000
	Crane Time	\$ 150			\$ 2,400	
Sub Total W/O Recertification					\$118,493	\$ 124,347
Annual Effect					\$ 13,166	\$ 13,816
Ratio for Small Companies \$/employee					\$ 818	\$ 858
Ratio for Small Companies for recertification: \$/employee					\$ 17	\$ 26

Note: Tables A5a and A5b cover only the largest and smallest firms, there are additional firms in the industry.

Appendix 6: References

Summary of Crane Accidents

Crane Types: M = Mobile T = Tower U = Unknown

Crane Accident			Crane type	Month & Year	Fatalities	Injuries	Equipment Damage (\$)	Property Damage (\$)	Cause Identified		
Cal-OSHA Crane Accidents Report ⁱ (158 accidents)				1997-99	1 operator 12 non-operators 13 TOTAL	23 operators 79 non-operators 102 TOTAL	---	---		All Crane Types	Mobile Cranes
Crane Type	No.	%							1. Instability	67	49
Mobile Cranes	115	73							a. Unsecured Load	34	6
Bridge Cranes	26	16							b. Load Capacity Exceeded	0	29
Gantry Cranes	5	3							c. Ground not level/too soft	0	4
Tower Cranes	4	3							2. Lack of Communication	32	24
Ship Cranes	1	1							3. Electrical Contact	13	10
Not Determined	7	4							4. Misc. in 14 Categories	46	32
CANADIAN ACCIDENTS Province of Ontario ⁱⁱ				1969-2002	121 mobile cranes	---	---	---	TOWER CRANE FATALITIES 34 YEARS (1969 - 2002)		
Mobile & Tower Cranes (138 fatal accidents)					15 tower cranes 138 TOTAL				CAUSE NUMBER%		
									Fall From Crane	4	26.6%
									Load Handling	3	20%
									Dismantling	2	13.3%
									Erecting	1	6.6%

Crane Accident	Crane type	Month & Year	Fatalities	Injuries	Equipment Damage (\$)	Property Damage (\$)	Cause Identified
							Structural Collapse (Overload) 1 6.6%
							Wire Rope 1 6.6%
							Miscellaneous 3 20%
							. Boom Hit Swing Stage (1)
							. Pulled Into Drum (1)
							. Motor Exploded (1)
							TOTAL 15 100%
							MOBILE CRANE FATALITIES
							34 YEARS (1969 - 2002)
							CAUSE NUMBER%
							Powerline Contact 53 43.8%
							Load Handling 18 14.9%
							Rigging 16 13.2%
							Overload 10 8.3%
							Operator Error 9 7.4%
							Rapid Breaking (1)
							. Two-Blocking (3)
							. Dropped Boom (1)
							. Crane Misapplication (1)
							. Crane Out-Of-Level (1)
							. Ground Failure (1)
							. Hoist Line Not Vertical (1)
							Dismantling Boom 5 4.1%
							Wire Rope Failure 5 4.1%
							Miscellaneous 5 4.1%
							. Signal Man (1)
							. Contact Power Source (1)
							. Struck By Crane/Cwt (3)

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
							TOTAL 121 100%
Altamonte Springs, FL ⁱⁱⁱ	M	07/14/2008	---	---	---	"The house has been condemned..."	"...they were watching about 10 workers from Gator Tree Service remove a large branch when the crane collapsed, crashing onto the house."
Buyck, MN ^{iv}	M	06/26/2008	1 worker	---	---	---	Worker electrocuted when truck's boom contacted live overhead power lines.
Campbellsport, WI ^v	M	04/21/2008	1 driver	1 car passenger	"...the two vehicles collided, tipping the truck over onto the car."	---	"Investigators said that a ... man ...pulled into the path of a crane truck.... [T]he driver of the truck attempted to swerve, but the two vehicles collided, tipping the truck over onto the car."
Chatsworth, IL ^{vi}	M	07/04/2008	---	2 drivers	---	---	A construction crane with broken wheel fasteners crashed into a semi truck during transport.
Chincoteague, VA ^{vii}	M	04/03/2008	---	---	---	"...the incident caused a electrical short that burned through one of the main circuit cables that feeds power to the island."	"A crane involved in construction of the new Chincoteague bridge struck high-voltage power lines..." "...a crane was being moved away from the construction area closer to March Island. The operator did not have the crane lowered enough to safely clear the lines." "...construction crews may have violated some work requirements when the crane hit the cable."
Colorado Springs., CO ^{viii}	M	06/02/2006	1 operator	---	---	---	Crane tipped over.
Denver, CO ^{ix}	M	04/30/200	---	---	---	---	

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
		8					
Eureka, CA ^x	M	04/28/2008	---	---	---	---	"The crane was large and overturned on a hairpin turn..."
Ft. Lauderdale, FL ^{xi}	M	06/24/2008	---	1 operator	---	"The overturned boom truck began leaking fuel, which authorities later cleaned up... The lift bent a lamp post and damaged a palm tree when it toppled over a fence onto Northeast 26th Avenue"	Boom truck flipped over during a roofing job.
Gainesville, GA ^{xii}	M	07/10/2008	---	---	"...the crane slid into the water."	"...an oil slick appeared on the lake surface... Oil booms were installed and absorbent material was used to contain the oil slick within an area of about 60 feet by 60 feet. ...[T]he county has stopped using water intake pipes near the spill area 'until the situation is stabilized and operations are back to normal at the construction site.'"	"...contractor crews were trying to move the crane onto a barge when an anchor cable came loose and the crane slid into the water."
Houston, TX ^{xiii}	M	07/04/200	1 operator	---	---	---	"Investigators said the unidentified crane operator

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
		8					had just exited the cab of the crane to inspect the boom when it fell and killed him."
Hurst, TX ^{xiv}	M	04/12/2008	1 worker	1 worker	---	---	"Witnesses said crews were using a small crane to hoist a 4,000-pound utility pole up when the cable snapped and it fell on [the victim]."
Laconia, NH ^{xv}	M	07/02/2008	---	---	---	---	Crane snagged on power lines as it was leaving a construction site.
Las Vegas, NV ^{xvi}	M	06/13/2008	---	---	"The metal supports for the crane span malfunctioned,"	---	Crawler crane buckled.
Memphis, TN ^{xvii}	M	04/17/2008	---	---	"A large crane caught fire and exploded..."	---	"A large crane caught fire and exploded during an accident on I-55..."
Miami, FL ^{xviii}	M	06/09/2008	---	2 workers	---	---	The construction workers were building the 318-foot crane to bring up roofing supplies for the condo when the incident happened about 3 p.m., Miami Fire Rescue spokesman Iggy Carroll said. The father is 52; his son is in his 20s. "They were about 100 feet up, putting together the crane, when the elbow part came slamming down, knocking the workers," Carroll said. "At this time we don't know how it happened or why."
Miami, FL ^{xix}	M	07/25/2005	---	Up to 6 workers	---	---	Operator error.
Naples, FL ^{xx}	M	04/22/2008	---	---	"As the construction workers ran away, Rives' Honda Civic plowed through the	Front-end damage to Honda Civic.	"Officials struggled through the afternoon Wednesday to account for the sudden collapse of a crane used to carry concrete pilings for an overpass..."

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
					fallen crane, ripping a hole through its lattice of metal." "...after it fell, pieces of the crane lay on the pavement, mangled by the Honda."		"Brad Closson, a California-based expert in crane safety, said one possibility in the Estero case is that the crane's brakes gave out, sending the boom to the ground."
Overland Park, KS ^{xxi}	M	06/07/2008	---	---	---	---	Road construction crane collapsed during bridge/overpass construction.
Port Angeles, WA ^{xxii}	M	04/24/2008	---	1 operator	---	---	
San Antonio, TX ^{xxiii}	M	04/23/2008	---	---	"The large construction crane flipped and was left standing at a near 90-degree angle."	"As the crane flipped, witnesses watched a large sign fall right in the middle of Southwest Military Drive." "A few businesses in the area had to evacuate for a short time because of a chemical leak the crane caused as it fell."	"Investigators believe he was moving a sign that was way too heavy for his machine." "Emergency workers believe wind may have also been a factor in the accident."
San Antonio, TX ^{xxiv}	M	06/14/2008	---	---	---	---	Crane tangled in power lines.

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
San Luis Obispo, CA ^{xxv}	M	06/25/2008	---	1 operator	---	"... sending it sliding down a neighborhood street, uprooting trees, uplifting a fire hydrant, and smashing cars parked in its way."	"Chaos is a good way to describe what happens when there is a brake failure on a big rig, sending it sliding down a neighborhood street, uprooting trees, uplifting a fire hydrant, and smashing cars parked in its way. One of the uprooted trees ended up on the driver's legs."
St. Augustine, FL ^{xxvi}	M	04/17/2008	---	1 worker	---	"As it fell, the boom of the crane landed directly in the center of the crane operator's 1996 Chevy truck — causing significant damage."	"...the operator extended the boom of a crane and his co-worker... stepped onto the end of the lift. As the operator was lowering the boom, the crane tipped over and [the man] was thrown off; landing on top of some wooden pallets on the ground nearby. The crane may have lost its footing because it was in soft sand at the time of the accident."
Telford, PA ^{xxvii}	M	08/21/2003	1 operator 2 workers 3 TOTAL	---	---	---	All three were electrocuted through crane boom contacting live overhead lines
Wallkill, NY ^{xxviii}	M	06/02/2008	---	---	---	---	Crane became unbalanced, almost tipped over.
Washington, IN ^{xxix}	M	07/16/2008	---	---	"That top section just buckled..."	"The crane fell on a security fence surrounding the tower and a portable baseball batting cage."	
Queens, NY ^{xxx}	M man-lift	07/16/2008	1 worker	---	---	---	"The truck, which was hauling wooden crates ... crashed into the crane. The crane, a Genie Z-80/60 known as a man lift, was being used at a work site..."

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
Baltimore, MD ^{xxxvi}	T	04/30/2008	1 worker	---	"No one else was hurt and nothing is believed to have been wrong with the crane..."	---	"Apparently, they were in the process of dismantling the crane when something went wrong and one worker was caught between pieces and crushed..."
Bellevue, WA ^{xxxvii}	T	11/16/2006	1 bystander	1 worker	---	Three downtown high-rise/ multi-story buildings were damaged.	
Hoover Dam, NV ^{xxxviii}	T	09/15/2006	---	---	"The September crane collapse forced contractors Obayashi Corp. and PSM Construction USA Inc. to find the resources to remove 300,000 pounds of steel cable and debris at the bottom of the Colorado River."	"...the construction accident ... caused \$50 million in damages and set back the project's completion date two years."	Two tower cranes working on Hoover Dam highway bypass collapsed. High winds
Miami, FL ^{xxxix}	T	03/25/2008	2	5	---	---	
New York City, NY ^{xl}	T	05/30/2008	2 construction workers	1 worker 1 bystander 2 TOTAL	"...the crane's turntable fell into the street, and the mast was affected."	"Pieces from the crane hit an apartment building across from the jobsite..."	"Construction crews erected the tower crane in late April and jumped it on May 22 and May 27 with city engineers onsite, LiMandri says. 'The first examination of the records say this crane was inspected, installed and stepped in compliance with regulations,' Bloomberg said. 'We do not know why the top snapped off.'"

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
New York City, NY ^{xxxvi}	T	09/29/2006	---	5	---	"Shattered glass showered down on Sixth Avenue and 43rd Street in one of the busiest areas of Manhattan, forcing authorities to close several streets."	"A crane slammed its load into the side of a signature skyscraper under construction..." "A worker at the site said the crane dropped a crate from the top of the 51-story Bank of America tower..."
New York City, NY ^{xxxvii}	T	10/17/2007	---	6	"Firefighters left the crane in its partially tipped over position until another crane arrived at about 1 p.m. to help lift it back to the ground."	Crane fell on a car, into a building, and into power lines.	Crane tipped over and into power lines and a building.

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
New York City, NY ^{xxxviii, xxxix}	T	03/15/2008	6 construction workers 1 bystander 7 TOTAL	13 construction workers 11 first responders 26 TOTAL	The crane split into pieces as it fell..."	<p>"The big, white crane stood at least 19 stories high and demolished parts of several buildings as it fell. A four-story brownstone was completely pulverized by the falling wreckage, and three buildings were damaged."</p> <p>"The crane split into pieces as it fell. Part of it came to rest against an apartment tower, buckling its facade and smashing it upper floors."</p> <p>Another piece of the crane hit traveled another half a block, ripping away walls and ceilings and crushing a small building."</p> <p>"Firefighters clambered through piles of rubble, several stories high, looking for victims. Witnesses reported a strong smell of gas in the area. Gas utility Consolidated Edison said it shut off service to area buildings. "</p>	<p>"...the crane was scheduled to be moved Saturday so workers could start work on a fresh story when a piece of steel fell and sheared off one of the ties holding it to the building..."</p> <p>"City Building Department records showed that on March 4, a caller told officials that the upper portions of the crane appeared to lack the proper number of safety ties attaching it to the building. A city inspector visited the site and determined on March 6 that no violation was warranted. Another call questioning the crane's safety was dismissed as unwarranted by another inspector in February."</p>

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
Aventura, FL ^{xi}	U	04/03/2008	---	2 workers	"... the smaller [crane] collapsed."		"The two men were moving the air-conditioning unit from a large crane to a smaller one, both on the roof, when the smaller one collapsed."
Casper, WY ^{xii}	U	06/02/2008	---	3 workers	"... the collapse caused extensive damage to the crane. 'It's completely toppled over; it's a mass of blue, twisted metal,' he said. 'My guess would be that they might be able to salvage the power unit and the tracks, and things like that. But the gantry, that's going to be scrap metal, would be my guess.'"	<p>"A 70-foot section of the tubing blocked the [railroad] tracks, and material and debris were also blocking a connection off the main line that serves the Black Thunder and Jacob Ranch mines, Melonas said.</p> <p>"We did shut down railroad traffic," he said."</p> <p>Arch Coal Inc. spokesman Greg Schaefer said the company will assess the damage after crews clear the wreckage.</p> <p>Bill Denning, spokesman for the Mine Safety and Health Administration in Denver, said the mine will be shut down while agency</p>	"...[the crane] was moving a 260-foot, 500,000-pound section of tubing over the triple-track main railroad line -- jointly owned by BNSF Railway and Union Pacific -- when the [crane collapsed]..."

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
						officials conduct an investigation.	
Dallas, TX ^{xiii}	U	06/13/2008	---	3 workers	---	---	
Honolulu, HI ^{xiii}	U	06/02/2008	1 worker	---	---	---	<p>"...Greg Wong, 50 was getting a concrete pumper truck ready to pour cement. That's when police say a gust of wind blew a canvas strap, which was attached to a nearby crane moving overhead.</p> <p>The strap then snagged onto the boom arm of the pumper.</p> <p>"The worker was standing beneath the concrete pumper and the boom from the concrete pumper came down and struck the operator..."</p>
Ingleside, TX ^{xiv}	U	04/29/2008	1 operator	2 workers	"THE CRANE COLLAPSED, PINNING [the operator] INSIDE THE CAB OF HIS CRANE. WORKERS HAD TO BRING IN ANOTHER CRANE TO REMOVE THE TONS OF METAL..."	---	"THE VICTIM... WAS ONE OF FOUR CRANE OPERATORS WHO WERE TRYING TO MOVE A 1000-TON OIL PLATFORM WHEN THE CRANE COLLAPSED..."
Las Vegas, NV ^{xiv}	U	05/31/2008	1 oiler	---	---	---	"[The victim], who worked as a crane oiler for Dielco Crane Service, was crushed Saturday morning when he got stuck between the counterweight of the crane and the track of the crane."

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
Las Vegas, NV ^{xlvi}	U	06/13/2008	---	1 operator	---	---	"Small crane" tipped over.
Lauderhill, FL ^{xlvii}	U	04/11/2008	---	---		"[The roof piece] landed on an unoccupied black passenger car. Flying debris however damaged the window of an apartment with a hole the size of a baseball."	"The crane, which was moving a mansard from the roof of a 10 story building, dropped a 12 foot by 4 foot section from 10 stories up"
Lubbock, TX ^{xlviii}	U	06/10/2008	---	2 workers		"...parts of a parking garage collapsed after a crane dropped an 18,000-pound precast cement beam onto the top floor of the three-story structure under construction. ...The failure caused the load to be dropped 10 feet to the floor of the top level of the garage... That caused a serial "pancake" collapse of parts of the floors below..."	"...The accident happened when a brake drum failed on the part of a crane hoisting the beam..."
Mobile, AL ^{xlix}	U	06/19/2008	1 worker	---	---	---	"...Hicks was operating an overhead crane and was pinned between a sheet of steel and a wall."
Portland, OR ^l	U	06/26/2008	---	---	---	---	Crane hook contacted power lines, shut down power to 8,000 people.

<i>Crane Accident</i>	<i>Crane type</i>	<i>Month & Year</i>	<i>Fatalities</i>	<i>Injuries</i>	<i>Equipment Damage (\$)</i>	<i>Property Damage (\$)</i>	<i>Cause Identified</i>
Seattle, WA ⁱⁱ	U	06/10/2008	---	---			Construction crane knocked out a power line. "About 172 City Light customers remained without power at noon today after a construction crane knocked out a power line... The outage also knocked out power to traffic signals..."
Seattle, WA ⁱⁱⁱ	U	08/22/1994	2 workers	1 operator	Broken crane arm; damaged cab and basket	---	Crane basket fell at the Kingdome during roof repairs: "... the basket carrying the two workers fell 250 feet, sending the men to their deaths, when the crane arm broke near its top. As it dropped, the basket struck the cab carrying the crane operator.
Seattle, WA ⁱⁱⁱ	U	09/22/1994	---	---	---	---	Crane hit the top of the inside of the Kingdome during roof repairs
Woodstock, VA ^{iv}	U	07/01/2008	1 worker	---	---	---	Construction crane part being removed from the crane fell on the worker below.
Yucca Valley, CA ^v	U	04/19/2008	1 operator	---	---	---	"...a crane he was operating came into contact with a live electric line..."

Sources

ⁱ **Report:** *CRANE ACCIDENTS 1997 - 1999: A REPORT OF THE CRANE UNIT OF THE DIVISION OF OCCUPATIONAL SAFETY AND HEALTH*, Division of Occupational Safety and Health, California Department of Industrial Relations, 23 May 2000.

ⁱⁱ **Report:** *CRANE AND RIGGING FATALITIES, PROVINCE OF ONTARIO (CONSTRUCTION ONLY), 1969 – 2002*, a publication of CONSTRUCTION SAFETY ASSOCIATION OF ONTARIO, 21 Voyager Court South, Etobicoke, Ontario M9W 5M7 Canada, www.CSAO.org

ⁱⁱⁱ **Crane Falls On Home; Workers Flee**, From Local6.com TV news web site, Altamonte Springs, FL, July 14, 2008, <http://www.local6.com/news/16876841/detail.html>

^{iv} **28yr Old Electrocuted**, From Northlands News Center, June 26, 2008, <http://www.northlandsnewscenter.com/news/local/21869819.html>

^v **One Dead After Car Hits Crane Near Campbellsport**, From WISN.com, TV news site, April 21, 2008, <http://www.wisn.com/news/15952392/detail.html>

^{vi} **Police release name of drivers in crane, semi crash on U.S. 24**, From Pantagraph.com, Friday, July 4, 2008 8:57 PM CDT, <http://pantagraph.com/articles/2008/07/04/news/doc486db3d331112677917964.txt>

^{vii} **CHINCOTEAGUE: Crane strikes island power line; repairs Friday**, From delmarvanow.com, the Daily Times newspaper site, coastal Virginia, April 3, 2008, CraneAccidents.com cache copy - <http://cachecopy.com/2008/apr/4-03-08va.htm>

^{viii} **Crane Accident Kills COSMIX Worker**, ENR.com, June 2006, <http://colorado.construction.com/news/infrastructure/archive/0606.asp>

^{ix} **Crane Tips Into Denver Building, Hits Power Lines**, Denver, Colorado, April 30, 2008, From CBS4Denver.com TV station site, <http://cbs4denver.com/local/crane.elati.denver.2.712529.html>

^x **Large crane overturns on Route 169**, From the Eureka Reporter newspaper site, Eureka, CA, April 28, 2008, <http://eurekareporter.com/article/080428-large-crane-overturns-on-route-169>

^{xi} **Truck with attached crane at Florida mall maintenance job flips**, From TNCNet.com, (c) 2008, South Florida *Sun-Sentinel*, June 24, 2008, <http://www.tmcnet.com/submit/2008/06/24/3515369.htm>

^{xii} **Crane accident spills fuel into Lake Lanier**, From GainesvilleTimes.com, newspaper Web site, July 10, 2008, <http://www.gainesvilletimes.com/news/archive/6989/>

^{xiii} **Crane operator crushed**, From KHOU.com, a TV station Web site, July 4, 2008, http://www.khou.com/news/local/stories/khou080703_tj_cranefatal.2015375d.html

^{xiv} **Fallen Power Pole Kills Contract Utility Worker**, From Dallas/Fort Worth CBS Channel 11 news Web site, Apr 12, 2008, <http://cbs11tv.com/local/hurst.pole.accident.2.698449.html>

^{xv} **Busy road closed after crane snags power line**, From Citizen.com, a service of *The Citizen* newspaper of Laconia, NH, July 3, 2008, <http://www.citizen.com/apps/pbcs.dll/article?AID=/20080703/GJNEWS02/433989295/-1/CITNEWS>

^{xvi} **Crane buckles at CityCenter**, June 14, 2008, Copyright © Las Vegas Review-Journal

^{xvii} **Crane explosion disrupts I-55 traffic in southern DeSoto County**, From WMC-TV Action news Web site, Memphis, TN, April 17, 2008, <http://www.wmctv.com/global/story.asp?s=8183755>

^{xviii} **Two workers injured in crane fall**, From the Miami *Herald* newspaper Web site, 9 June 2008, CraneAccidents.com cache copy - <http://cachecopy.com/2008/jun/6-09-08fl.htm>

^{xix} **An Accident in Florida Shows a Break in the Decision Chain**, 7/25/2007, By Richard Korman, ENR.com, http://enr.ecnext.com/coms2/article_febiar070725a-1

^{xx} **Driver recalls horror of crane collapse**, From NaplesNews.com, the Naples Daily News newspaper site, April 23, 2008, http://www.naplesnews.com/news/2008/apr/23/crane-accident-i-75-diverts-traffic-near-estero/#gal_victims-crash-photos

^{xxi} **Crane collapses at road construction site**, the Kansas City *Star* newspaper, Accidents.com cache copy -- <http://cachecopy.com/2008/jun/6-07-08ks.htm>

^{xxii} **Crane topples on Port Angeles pier; operator injured**, From Port Angeles *Peninsula Daily News*, April 24, 2008, <http://www.peninsuladailynews.com/article/20080424/NEWS/804240303>

^{xxiii} **Crane Accident Causes Road Closure**, From WOAI.com San Antonio, TX, TV news site, April 23, 2008, http://www.woai.com/news/local/story.aspx?content_id=11a3eebc-f1d0-4559-89ce-b980942f2abe&rss=68

^{xxiv} **Crane Accident Traps Man In Cab**, From KSAT Channel 12 TV news site, June 14, 2008, <http://www.ksat.com/news/16608222/detail.html>

^{xxv} **Crane accident in San Luis Obispo**, From KSBY.com, Channel 6 Action News, California, June 25, 2008, <http://www.ksby.com/Global/story.asp?S=8556447>

^{xxvi} **Construction accident**, From HistoricCity.com, Historic City News site, St. Augustine, FL, April 17, 2008, <http://historiccitey.com/2008/04/17/construction-accident/>

^{xxvii} **Deadly Crane Accident Kills Three**, 9/1/2003, By ENR Staff, ENR.com, http://enr.ecnext.com/coms2/article_nepoar030901b

^{xxviii} Crane problem delays traffic on I-84 today, Wallkill, NY, From the *Times Herald-Record* newspaper site, June 2, 2008 <http://www.recordonline.com/apps/pbcs.dll/article?AID=/20080602/NEWS/80602021/-1/NEWS>

^{xxix} **Crane collapses in Washington Township**, From NWI.com, the Northwest Indiana Times newspaper site, July 16, 2008, http://www.thetimesonline.com/articles/2008/07/16/updates/breaking_news/doc487e259f83ed9437156851.txt

^{xxx} **Worker Dies After Truck Hits Crane in Queens**, From New York *Times* Web site, July 16, 2008, http://www.nytimes.com/2008/07/16/nyregion/16crash.html?_r=1&adxnnl=1&oref=slogin&adxnnlx=1216317833-tOj8bl6S0MgtAO+yUOyYw

^{xxxi} **Man Dies In Crane Accident**, From WBAL Baltimore, MD, TV news site, April 30, 2008, <http://www.wbalv.com/news/16081311/detail.html?rss=bal&psp=news>

^{xxxii} **Crane collapse in Bellevue kills man**, *Seattle Post-Intelligencer* newspaper, Friday, November 17, 2006, http://seattlepi.nwsourc.com/local/292762_crane17.html

^{xxxiii} **Diving for debris: A.F. company cleans up Hoover Dam bypass damage**, Monday, 29 January 2007, GRACE LEONG - Daily Herald, <http://www.heraldextra.com/content/view/208392/>

^{xxxiv} **Miami Police Identify Crane Accident Victims**, 3/27/2008, [ENR.com](http://enr.ecnext.com/coms2/article_nesaar080327), http://enr.ecnext.com/coms2/article_nesaar080327

^{xxxv} **New Yorkers Baffled by Latest Crane Disaster**, 05/30/2008, , from ENR.com

^{xxxvi} **Crane accident injures 6 at NY skyscraper site**, Wed Oct 17, 2007 2:13pm EDT, <http://www.reuters.com/article/latestCrisis/idUSN17331980>

^{xxxvii} **Crane accident injures 6 at NY skyscraper site**, Wed Oct 17, 2007 2:13pm EDT, <http://www.reuters.com/article/latestCrisis/idUSN17331980>

^{xxxviii} Fatal crane accident in Manhattan Toppled and smashed into buildings, http://www.wstm.com/news/news_story.aspx?id=108621
Posted: Saturday, March 15, 2008 at 6:40 p.m.

and

^{xxxix} Report: *Crane-Related Deaths in Construction and Recommendations for Their Prevention*, a publication of The Center for Construction Training and Research, the research, development, and training arm of the Building and Construction Trades Department, AFL-CIO

^{xl} **Crane mishap leaves 2 injured in Aventura**, From Miami Herald newspaper site, April 3, 2008, CraneAccidents.com cache copy - <http://cachecopy.com/2008/apr/4-03-08fl.htm>

^{xli} **Three injured, two critically, in Black Thunder crane accident**, From the Casper Star-Tribune newspaper, Wyoming, Monday, June 2, 2008 11:13 AM MDT, http://www.trib.com/articles/2008/05/31/special_breaking_news/doc4841b59577eaa875988288.txt

^{xlii} **3 injured in crane accident at new Dallas Cowboys stadium**, From DallasNews.com, June 13, 2008, <http://www.dallasnews.com/sharedcontent/dws/news/localnews/stories/061308dnmetcrane.26374bbf.html>

^{xliii} **Deadly Crane Accident on Kapiolani**, From KGMB channel 9 news Web site, 2 June 2008, <http://kgmb9.com/main/content/view/6995/40/>

^{xliiv} **Gregory Man Killed in Industrial Crane Accident**, From KIII TV South Texas TV new site, April 29, 2008, <http://www.kiiitv.com/news/local/18381869.html>

^{xlv} **Workers walk off CityCenter site in protest**, July 8, 2008, Las Vegas *Sun* newspaper, <http://www.lasvegassun.com/news/2008/jun/03/workers-walk-citycenter-site-protest>

^{xlvi} **Small crane tips over at CityCenter, injures operator and stops traffic on the Strip**, Las Vegas *Sun* newspaper, July 8, 2008, <http://www.lasvegassun.com/blogs/cops/2008/jun/13/dangling-crane-stops-traffic-strip/>

^{xlvii} **Crane Drops Part Of 10th Story Roof In Lauderhill**, From Channel 4 CBS News Web site, Lauderhill, FL, Apr 11, 2008, <http://cbs4.com/local/Lauderhill.Crane.Accident.2.698050.html>

^{xlviii} **2 injured in Lubbock when crane drops cement beam**, The Houston *Chronicle*, June 10, 2008, (cache copy at CraneAccidents.com - <http://cachecopy.com/2008/jun/6-10-08tx.htm>)

^{xlix} **Worker dies in Mobile shipyard accident**, From Gone But Not Forgotten, a Web site about healing grief, <http://gonebutnotforgotten.wordpress.com/2008/06/19/worker-dies-in-mobile-shipyard-accident/>

^l **Crane Hits Power Wires In East Portland**, From Oregon FOX 12 TV station Web site, June 26, 2008, <http://www.kptv.com/news/16720744/detail.html>

^{li} **Crane knocks out power in South Lake Union area**, The Seattle *Times* newspaper, June 10, 2008, http://seattletimes.nwsourc.com/html/localnews/2004468891_weboutage10m.html?syndication=rss

^{lii} **Two Workers Killed In Fall; Kingdome Closed Indefinitely -- Basket Drops 250 Feet Onto Cab, Injuring The Operator**, The Seattle *Times* newspaper, August 22, 1994, <http://community.seattletimes.nwsourc.com/archive/?date=19940818&slug=1925961>

ⁱⁱⁱ **Latest Dome Accident More Serious Than Thought**, The Seattle Times newspaper, 22 Sept 1994,
<http://community.seattletimes.nwsourc.com/archive/?date=19940922&slug=1932074>

^{liv} **Fatal Crane Accident in Woodstock**, From WHSV.com, TV station Web site, July 1, 2008, <http://www.wHSV.com/news/headlines/22786554.html>

^{lv} **Crane operator killed**, From *High-Desert Star* newspaper, Yucca Valley, CA, April 19, 2008, <http://cachecopy.com/2008/apr/4-19-08cal.htm>