

---

**Chapter 296-878 WAC**  
**Window Cleaning**  
**(Form Number 414-114-000)**

This book contains rules for Safety Standards for window cleaning, as adopted under the Washington Industrial Safety and Health Act of 1973 (Chapter 49.17 RCW).

The rules in this book are effective October 2020. A brief promulgation history, set within brackets at the end of this chapter, gives statutory authority, administrative order of promulgation, and date of adoption of filing.

**TO RECEIVE E-MAIL UPDATES:**

- Sign up at [https://public.govdelivery.com/accounts/WADLI/subscriber/new?topic\\_id=WADLI\\_19](https://public.govdelivery.com/accounts/WADLI/subscriber/new?topic_id=WADLI_19)

**TO PRINT YOUR OWN PAPER COPY OR TO VIEW THE RULE ONLINE:**

- Go to <https://www.lni.wa.gov/safety-health/safety-rules/rules-by-chapter/?chapter=878/>

**DOSH CONTACT INFORMATION:**

- **Physical address:**

7273 Linderson Way  
Tumwater, WA 98501-5414  
(Located off I-5 Exit 101 south of Tumwater.)

- **Mailing address:**

DOSH Standards and Information  
PO Box 44810  
Olympia, WA 98504-4810

- Telephone: 1-800-423-7233
- For all L&I Contact information, visit <https://www.lni.wa.gov/agency/contact/>

- **Also available on the L&I Safety & Health website:**

- DOSH Core Rules
- Other General Workplace Safety & Health Rules
- Industry and Task-Specific Rules
- Proposed Rules and Hearings
- Newly Adopted Rules and New Rule Information
- DOSH Directives (DD's)
- See <http://www.lni.wa.gov/Safety-Health/>

<b>WAC</b>	<b>Page</b>
<b>WAC 296-878-099 Definitions.....</b>	<b>1</b>
<b>WAC 296-878-100 Scope.....</b>	<b>3</b>
WAC 296-878-10005 Summary. ....	3
<b>WAC 296-878-110 Training. ....</b>	<b>4</b>
Summary.....	4
WAC 296-878-11005 Train workers to use window-cleaning equipment. ....	4
<b>WAC 296-878-120 Building surfaces and fixtures. ....</b>	<b>6</b>
Summary.....	6
WAC 296-878-12005 Make sure building surfaces and fixtures are safe to use. ....	6
<b>WAC 296-878-130 Inspection procedures. ....</b>	<b>7</b>
Summary.....	7
WAC 296-878-13005 Inspect the area to be cleaned.....	7
WAC 296-878-13010 Inspect window-cleaning equipment before use. ....	7
<b>WAC 296-878-140 Develop site-specific service and emergency plans. ....</b>	<b>9</b>
Summary.....	9
WAC 296-878-14005 Develop a site-specific service and emergency recovery plan for window-cleaning operations. ....	9
<b>WAC 296-878-150 Equipment.....</b>	<b>10</b>
Summary.....	10
WAC 296-878-15005 Select and use appropriate equipment. ....	10
WAC 296-878-15015 Select appropriate rope for suspended equipment. ....	11
WAC 296-878-15020 Select appropriate carabiners.....	11
WAC 296-878-15025 Use fall protection equipment. ....	11
<b>WAC 296-878-160 Warning signs and barricades. ....</b>	<b>11</b>
Summary.....	11
WAC 296-878-16005 Provide warning signs and barricades when suspended equipment is used. ....	11
<b>WAC 296-878-170 Power line clearances. ....</b>	<b>13</b>
Summary.....	13
WAC 296-878-17005 Maintain clearance between window cleaners and power lines. ....	13
<b>WAC 296-878-180 Window-cleaners' belts and anchors.....</b>	<b>14</b>
Summary.....	14

<b>WAC</b>	<b>Page</b>
<i>WAC 296-878-18005 Select appropriate window-cleaners' belts and anchors. ....</i>	14
<i>WAC 296-878-18010 Inspect the anchors you plan to use for window cleaning. ....</i>	14
<i>WAC 296-878-18015 Use window-cleaners' belts safely. ....</i>	15
<i>WAC 296-878-18020 Move safely on the outside of buildings. ....</i>	15
<b>WAC 296-878-190 Boatswains' chairs. ....</b>	<b>16</b>
<i>Summary.....</i>	16
<i>WAC 296-878-19005 Select appropriate boatswains' chairs.....</i>	16
<i>WAC 296-878-19010 Safely use boatswains' chairs rigged with a block and tackle. ...</i>	16
<b>WAC 296-878-200 Rope descent systems.....</b>	<b>18</b>
<i>Summary.....</i>	18
<i>WAC 296-878-20005 Select appropriate rope descent systems. ....</i>	18
<i>WAC 296-878-20010 Safely use rope descent systems. ....</i>	18
<i>WAC 296-878-20015 Safely use rope descent devices. ....</i>	19

## **WAC 296-878-099 Definitions.**

**Anchor, window-cleaner's belt.** Fall-preventing attachment points for direct attachment of the terminal portion of a window-cleaner's belt.

**Belt terminal.** That part of the safety belt that is attached to the anchor during the window-cleaning operation.

**Block and tackle.** A lifting device consisting of one or more pulley blocks reeved with chains, wire ropes, or fiber ropes used solely for raising and lowering a load or moving a load horizontally.

**Boatswain's chair.** A single-point adjustable suspension scaffold consisting of a seat or sling designed to support one worker in a sitting position.

**Capstan device.** An upright, spool-shaped cylinder used for hoisting or lifting weights that is turned by a motor or by hand.

**Carabiner.** An oblong metal ring with an openable spring-hinged side, used to clip a rope to an anchoring device.

**Competent person.** One who is capable of identifying existing and predictable hazards in the surroundings, or working conditions which are unsanitary, hazardous, or dangerous to employees, and who has authorization to take prompt corrective measures to eliminate them.

**Drop (drop zone).** A vertical area or work zone accessed by the worker or piece of equipment during one descent.

**Drop line.** A vertical line from a fixed anchorage, independent of the work surface.

**Fixture.** Attachments, anchors, anchorages, tie backs or support equipment permanently dedicated to a given site.

**Grade.** The ground, floor, sidewalk, roof, or any level surface that is considered a safe place to work.

**Lanyard.** A flexible line to secure a wearer of a safety belt or harness to a drop line, lifeline or fixed anchorage.

**Mullion.** A slender, vertical dividing bar between windows, panels, etc.

**Primary support/suspension.** A working line or approved anchorage used for attachment of a working line.

**Qualified person.** A person is qualified if they have one of the following:

1. Extensive knowledge, training, and experience about the subject matter, work, or project
2. A recognized degree, certificate, or professional standing
3. Successful demonstration of problem solving skills in connection with the subject, work, or project.

**Rated capacity.** The combined weight of workers, tools, equipment, and other materials that the device is designed and installed to lift and support.

**Rope descent system (RDS).** An assembly of components that allows the operator to control the rate of descent at any time. A rope descent system includes the following components:

1. Suspension devices
2. Certified roof anchorages
3. Primary support ropes or lines
4. The descent device
5. Carabiners or shackles
6. A seatboard or boatswain's chair.

**Terminal strap.** The strap or rope attached to the waist band on one end, and to the belt terminals on the other end.

**Window cleaning.** Cleaning, wiping, restoring or other methods of cleaning windows.

**Working line.** A rope suspended from an anchorage and used to access parts of a building.

## **WAC 296-878-100 Scope.**

These rules apply to all window-cleaning activities performed on the inside or outside of a building in which the window cleaner is working from a level that is located more than 48 inches above grade.

### **WAC 296-878-10005 Summary.**

**Your responsibility:** Make sure workers clean windows safely, and properly use and maintain their window-cleaning equipment.

<b>Important:</b>
Window-cleaning equipment includes window-cleaner's belts, boatswains' chairs, rope descent systems, ladders, supported scaffolds and the support equipment used to suspend employees cleaning windows.

## **WAC 296-878-110 Training.**

### **Summary**

<b><i>You must meet the requirements...</i></b>	<b><i>in this section:</i></b>
Train workers to use window-cleaning equipment	<a href="#">WAC 296-878-11005</a>

### **WAC 296-878-11005 Train workers to use window-cleaning equipment.**

- (1) You must provide the following training to workers before they use window-cleaning equipment on the job:
  - (a) Proper care and maintenance of the equipment;
  - (b) Review manufacturer's instructions for proper equipment use;
  - (c) Methods for inspection, assembly, and dismantling of components;
  - (d) Identify anchorages;
  - (e) A complete understanding of safe working conditions;
  - (f) How employees will be rescued.
- (2) You must provide additional training to workers using window-cleaners' belts in all the following areas:
  - (a) How to select the proper-sized belt;
  - (b) How to use anchors and terminals;
  - (c) How to deal with obstructions and slippery/wet surfaces.
- (3) You must provide additional training to workers using boatswains' chairs and rope descent systems in all the following areas:
  - (a) Proper rigging practices;
  - (b) Fall arrest requirements;
  - (c) Proper methods of descending;
  - (d) The effects of wind on window-cleaning operations when a worker is suspended;
  - (e) Proper methods of hoisting for ascents.
- (4) You must document the training by recording all of the following:
  - (a) The name and signature of the trainer/educator;
  - (b) The name and signature of the student;
  - (c) The subjects in which the workers were trained;
  - (d) The date of the training;
  - (e) The location of the training.

**Note:** You do not need a specialized educator to provide training. You may use a qualified person to conduct the training. A qualified person is defined as a person who has:

1. Extensive knowledge, training, and experience about the subject matter, work, or project
2. A recognized degree, certificate, or professional standing
3. Successful demonstration of problem solving skills in connection with the subject, work, or project.

## **WAC 296-878-120 Building surfaces and fixtures.**

### **Summary**

<b><i>You must meet the requirements...</i></b>	<b><i>in this section:</i></b>
Make sure building surfaces and fixtures are safe to use	<a href="#">WAC 296-878-12005</a>

### **WAC 296-878-12005 Make sure building surfaces and fixtures are safe to use.**

You must make sure building surfaces and fixtures are safe to be used before you begin the window-cleaning operation. This includes:

- (1) Guardrails, parapets, cornices and other building surfaces used to support suspended loads;
- (2) Permanently installed fixtures used as anchorages and tiebacks;
- (3) Window-cleaning equipment support systems permanently dedicated to the building.

## **WAC 296-878-130 Inspection procedures.**

### **Summary**

<b><i>You must meet the requirements...</i></b>	<b><i>in this section:</i></b>
Inspect the area to be cleaned	<a href="#">WAC 296-878-13005</a>
Inspect window-cleaning equipment before use	<a href="#">WAC 296-878-13010</a>

### **WAC 296-878-13005 Inspect the area to be cleaned.**

- (1) You must inspect the building before cleaning to make sure there are no areas that can damage worker fall protection equipment and window-cleaning equipment. Inspect:
  - (a) Sharp edges of parapets
  - (b) Window frames
  - (c) Open projected windows
  - (d) Cornices
  - (e) Overhangs
  - (f) Any other areas that may abrade, sever, weaken, or damage the equipment.
- (2) You must make sure all working surfaces are safe and free from hazards such as:
  - (a) Grease;
  - (b) Oil;
  - (c) Other slippery substances.

### **WAC 296-878-13010 Inspect window-cleaning equipment before use.**

- (1) You must store your window-cleaning equipment in a way that:
  - (a) Is easy to get to, inspect, and safely take out for use;
  - (b) Provides protection from moisture, sunlight, or corrosion.
- (2) You must make sure a competent person inspects these items before each use:
  - (a) Window-cleaners' belts;
  - (b) Boatswains' chairs;
  - (c) All components of rope descent systems;
  - (d) Suspension devices;
  - (e) Certified roof anchorages;
  - (d) Primary support ropes or lines;
  - (g) The descent device;
  - (h) Carabiners or shackles;

- (i) A seatboard or boatswain's chair;
  - (j) Wear points on rope descent system components exposed to constant friction.
- (3) You must make sure you do not use any piece of window-cleaning equipment with defects.
- (a) Prohibit makeshift repairs to any piece of window-cleaning equipment;
  - (b) Label any piece of window-cleaning equipment that is defective “dangerous, do not use.”
- (4) You must secure any padding or softeners so they do not come loose from:
- (a) The surface of the building;
  - (b) The rope if not attached to the building.

## ***WAC 296-878-140 Develop site-specific service and emergency plans.***

### **Summary**

<b><i>You must meet the requirements...</i></b>	<b><i>in this section:</i></b>
Develop a site-specific service and emergency recovery plan for window-cleaning operations	<a href="#">WAC 296-878-14005</a>

### **WAC 296-878-14005 Develop a site-specific service and emergency recovery plan for window-cleaning operations.**

- (1) You must make sure that a qualified person develops a written plan for each location to be cleaned that identifies:
  - (a) Hazardous areas;
  - (b) Drop zones;
  - (c) Safety features;
  - (d) Methods for emergency recovery of workers working from suspended equipment, or other types of installations, in the event of equipment failure or any other kind of disability.
- (2) You must keep the plan at the work site during the entire cleaning operation.

**Note:** You may use an outside service for rescue and recovery (such as a fire department if:

1. The rescue personnel will be able to reach the victims without undue delay;
2. They have the necessary equipment to retrieve the victims;
3. They are trained and proficient in high angle rescue techniques.

## WAC 296-878-150 Equipment.

### Summary

<i>You must meet the requirements...</i>	<i>in this section:</i>
Select and use appropriate equipment	<a href="#">WAC 296-878-15005</a>
Select appropriate rope for suspended equipment	<a href="#">WAC 296-878-15015</a>
Select appropriate carabiners	<a href="#">WAC 296-878-15020</a>
Use fall protection equipment	<a href="#">WAC 296-878-15025</a>

### WAC 296-878-15005 Select and use appropriate equipment.

- (1) You must make sure that all equipment provided to workers for window-cleaning operations is engineered, designed, and intended for use in commercial applications.

**Note:** Equipment that is designed or labeled for recreational use or rescue use only is prohibited for use in window-cleaning operations.

- (2) You must make sure that the window-cleaning equipment is not altered unless it is specifically approved in writing by the original manufacturer or a registered professional engineer.
- (3) You must provide manufacturer's instructions to employees for all window-cleaning equipment they will use.

**Reference:** Use Table 1 for other window-cleaning equipment requirements.

<b>Table 1 Other window-cleaning equipment</b>	
<b><i>If you use:</i></b>	<b><i>Then follow all requirements in:</i></b>
Portable ladders	Chapter <a href="#">296-876</a> WAC, Ladders, portable and fixed
Supported scaffolds	Chapter <a href="#">296-24</a> WAC, Part J-2, Scaffolds
Suspension ropes and lifelines Powered and manual hoists Suspended scaffold equipment	Chapter <a href="#">296-24</a> WAC, Part J-2, Scaffolds
Single and multipoint adjustable suspension scaffolds	Chapter <a href="#">296-24</a> WAC, Part J-2, Scaffolds
Powered platforms	Chapter <a href="#">296-24</a> WAC, Part J-3, Powered Platforms

**WAC 296-878-15015 Select appropriate rope for suspended equipment.**

You must make sure all rope used for suspended equipment has a minimum breaking strength of 5000 pounds.

**WAC 296-878-15020 Select appropriate carabiners.**

- (1) You must use carabiners for connecting hardware or attaching boatswains' chairs, descent devices, and lifelines to anchors.
- (2) You must use carabiners with a minimum tensile load of 5000 pounds.
- (3) You must make sure carabiners are either manual or auto-locking.

**Note:** You may secure a rope to an anchor with a knot if normal daily use of the rope will not decrease its initial breaking strength below 5000 pounds.

**WAC 296-878-15025 Use fall protection equipment.**

- (1) You must make sure the fall arrest system meets the requirements of chapter [296-880](#) WAC, Unified safety standards for fall protection.
- (2) You must use and inspect fall arrest equipment in accordance with the requirements of chapter [296-880](#) WAC, Unified safety standards for fall protection.
- (3) You must make sure workers operating powered platforms wear and use a fall arrest system.
- (4) You must make sure the boatswain's chair or rope descent system is connected at all times to the suspension line.

**WAC 296-878-160 Warning signs and barricades.****Summary**

<i>You must meet the requirements...</i>	<i>in this section:</i>
Provide warning signs and barricades when suspended equipment is used	<a href="#">WAC 296-878-16005</a>

**WAC 296-878-16005 Provide warning signs and barricades when suspended equipment is used.**

- (1) You must place warning signs below suspended equipment
- (2) You must block the ground area with barricades directly under or next to the work zone
- (3) You must assign a competent person to decide if additional protection is necessary
- (4) You must make sure all tools used by the worker are attached to the worker, seatboard, or boatswain's chair.

**Reference:** Rules for protecting workers from overhead hazards are listed in WAC [296-800-16055](#) Make sure your employees use appropriate head protection.

## WAC 296-878-170 Power line clearances.

### Summary

<i>You must meet the requirements...</i>	<i>in this section:</i>
Maintain clearance between window cleaners and power lines	<a href="#">WAC 296-878-17005</a>

### WAC 296-878-17005 Maintain clearance between window cleaners and power lines.

- (1) You must maintain clearances between window cleaners and power lines as indicated in Tables 2 and 3.

<b>Table 2 Minimum Clearances from Power Lines – Insulated Lines</b>		
<b>Voltage</b>	<b>Minimum distance</b>	<b>Alternatives</b>
Less than 300 volts	3 feet (0.9 m)	-----
300 volts to 50 kv	10 feet (3.1 m)	-----
More than 50 kv	10 feet (3.1 m) plus 0.4 inches (1.0 cm) for each 1 kv over 50 kv	2 times the length of the line insulator, but never less than 10 feet (3.1 m)

<b>Table 3 Minimum Clearances from Power Lines – Uninsulated Lines</b>		
<b>Voltage</b>	<b>Minimum distance</b>	<b>Alternatives</b>
Less than 50 kv	10 feet (3.1 m)	-----
More than 50 kv	10 feet (3.1 m) plus 0.4 inches (1.0 cm) for each 1 kv over 50 kv	2 times the length of the line insulator, but never less than 10 feet (3.1 m)

- (2) You must follow these procedures when window cleaners need to get closer to power lines than allowed in Tables 2 and 3:
- (a) Notify the utility company or electrical system operator of the need to work closer than the minimum clearances to power lines before starting the work;
  - (b) Begin the work only when the utility company or electrical system operator has de-energized or relocated the lines, or installed protective coverings to prevent accidental contact with the lines.

## **WAC 296-878-180 Window-cleaners' belts and anchors.**

### **Summary**

<b><i>You must meet the requirements...</i></b>	<b><i>in this section:</i></b>
Select appropriate window-cleaners' belts and anchors	<a href="#">WAC 296-878-18005</a>
Inspect the anchors you plan to use for window cleaning	<a href="#">WAC 296-878-18010</a>
Use window-cleaners' belts safely	<a href="#">WAC 296-878-18015</a>
Move safely on the outside of buildings	<a href="#">WAC 296-878-18020</a>

### **WAC 296-878-18005 Select appropriate window-cleaners' belts and anchors.**

You must make sure window-cleaners' belts and anchors conform to the:

- (1) Design, manufacture, and maintenance requirements of ANSI/IWCA 1-14.1-2001; and
- (2) Manufacturer's specifications.

### **WAC 296-878-18010 Inspect the anchors you plan to use for window cleaning.**

- (1) You must make sure you do not use anchors if they:
  - (a) Appear to be damaged;
  - (b) Appear deteriorated;
  - (c) Appear to be worn;
  - (d) Appear to be loose;
  - (e) Appear to be unsecured to the building or window frame;
  - (f) Will not allow the belt terminal to easily slip over the anchor head.
- (2) You must use window-cleaner's belts only if:
  - (a) The area to be cleaned is safe;
  - (b) All anchors intended for use are safe.
- (3) You must make sure window ledges and frames will not impair the safe use of the window-cleaner's belt.

**Note:** If unsafe anchors are found, report them to the building owner or manager and do not use them.

**WAC 296-878-18015 Use window-cleaners' belts safely.**

- (1) You must make sure workers do not extend more than one arm beyond the window sash when cleaning windows from inside a building.
- (2) You must attach one belt terminal to an anchor before you put more than one arm outside the window.
- (3) You must pull on the terminal strap and look for signs of damage to the anchor.
- (4) You must attach both belt terminals to anchors before climbing out the window.
- (5) You must keep all belt terminals attached during the entire cleaning operation.
- (6) You must make sure the worker keeps one terminal attached to an anchor when reentering the window and until the worker is inside.

**WAC 296-878-18020 Move safely on the outside of buildings.**

You must make sure you travel on the outside of the building only when:

- (1) You keep at least one window-cleaner's belt terminal attached at all times;
- (2) The anchors are not more than 48 inches apart.

**Note:** Anchors can be up to 72 inches apart if:

1. The sill or ledge is continuous;
2. The sill or ledge is at least 12 inches wide;
3. The sill or ledge has a slope less than 5 degrees;
4. There is at least 6 inches of window sill in front of the mullions.

## **WAC 296-878-190 Boatswains' chairs.**

### **Summary**

<b><i>You must meet the requirements...</i></b>	<b><i>in this section:</i></b>
Select appropriate boatswains' chairs	<a href="#">WAC 296-878-19005</a>
Safely use boatswains' chairs rigged with a block and tackle	<a href="#">WAC 296-878-19010</a>

### **WAC 296-878-19005 Select appropriate boatswains' chairs.**

- (1) You must make sure that when you use a block and tackle, it is the correct size, including:
  - (a) Correctly-sized ball bearings or bushed blocks;
  - (b) Safety hooks;
  - (c) Eye-spliced rope;
  - (d) A minimum breaking strength of 5000 pounds.
- (2) You must make sure all rope used with a boatswain's chair has a minimum breaking strength of 5000 pounds, including rope used for:
  - (a) Suspension;
  - (b) Block and tackle;
  - (c) Seat slings.
- (3) You must make sure the ropes on boatswain's chair seat slings:
  - (a) Are reeved through the 4 corner holes in the seat;
  - (b) Cross each other on the underside of the seat;
  - (c) Are rigged so the chair cannot slip out of a level position.

### **WAC 296-878-19010 Safely use boatswains' chairs rigged with a block and tackle.**

- (1) You must make sure the rated capacity or the maximum intended load, whichever is less, is not exceeded.
- (2) You must make sure the suspension rope stays vertical between the boatswain's chair and suspension device unless all of these requirements are met:
  - (a) The rigging has been designed by a qualified person;
  - (b) The scaffold can be easily reached by rescuers;
  - (c) The suspension rope is protected from damage when a change in direction occurs;
  - (d) The scaffold will not swing and contact another surface.
- (3) You must make sure a suspension height of 75 feet above grade or building setback is not exceeded.

**EXEMPTION:**

Suspension height may be up to 130 feet above grade or building setback if the boatswain's chair block and tackle has all of the following:

1. An automatic breaking system;
2. A design that minimizes the amount of force required to raise or lower the suspended worker;
3. An automatic breaking system that automatically maintains an elevation when no force is applied to the tackle;
4. A system that does not slip.

- (4) You must prohibit tying any kind of knot in a block and tackle system to maintain elevation.
- (5) You must make sure another worker is stationed below any boatswain's chair rigged with a block and tackle who can assist the suspended employee.
- (6) You must make sure workers do not attempt to increase the work area by swinging, swaying, or other maneuvers.

## **WAC 296-878-200 Rope descent systems.**

### **Summary**

<b><i>You must meet the requirements...</i></b>	<b><i>in this section:</i></b>
Select appropriate rope descent systems	<a href="#">WAC 296-878-20005</a>
Safely use rope descent systems	<a href="#">WAC 296-878-20010</a>
Safely use rope descent devices	<a href="#">WAC 296-878-20015</a>

### **WAC 296-878-20005 Select appropriate rope descent systems.**

- (1) You must make sure the rope descent system is designed, used, and maintained according to:
  - (a) ANSI/IWCA 1-14.1-2001;
  - (b) The manufacturer's instructions.
- (2) You must make sure the rope descent system has been manufactured and is intended to be used for window cleaning.

**Note:** Equipment that is designed or labeled for recreational use or rescue use only is prohibited for use in window-cleaning operations.

- (3) You must make sure the rope descent system components are compatible and have a minimum tensile strength of 5000 pounds. This does not apply to the seatboard.
- (4) You must make sure the rope descent system has specific use instructions for each component.

### **WAC 296-878-20010 Safely use rope descent systems.**

- (1) You must make sure workers use extreme care when using rope descent equipment around electrical service, heat sources, and turbulent areas, such as air vents.
- (2) You must connect the seatboard or boatswain's chair to the descent device with a manual- or auto-locking carabiner.
- (3) You must make sure workers are positioned in the seatboard or boatswain's chair before being suspended.
- (4) You must make sure workers do not reach more than 6 feet in any direction as measured from a centerline straight down from where the suspension rope bears on the building.
- (5) You must make sure workers do not descend rapidly, swing excessively, or stop suddenly.
- (6) You must make sure that, in addition to the suspended worker, there is one other person at the job site who is skilled in using the rope descent system and rescue procedures.
- (7) You must make sure you do not exceed a 300-foot height of descent as measured from grade or building setback unless the windows cannot be safely and practicably accessed by other means.

- (8) You must make sure your site-specific service plan addresses the following hazards for descents over 130 feet as measured from grade or building setback:
  - (a) Sudden weather changes, such as wind gusts, micro bursts, or tunneling wind currents;
  - (b) Inability of the rope descent system to function without using excessive force;
  - (c) Workers suspended for long periods of time;
  - (d) Re-rigging and movement of main suspension and safety lines.
- (9) You must stabilize workers suspended from a rope descent system whenever the descent is higher than 130 feet, as measured from grade or building setback.
- (10) You must prohibit workers from working when wind speed makes any stabilization equipment ineffective.

**Note:** Provisions for stabilizing workers may include:

1. Continuous stabilization, such as mullion tracks
2. Intermittent stabilization, such as detent pins/buttons
3. Work station stabilization, such as suction cups.

**WAC 296-878-20015 Safely use rope descent devices.**

- (1) You must make sure the rated capacity or the maximum intended load, whichever is less, is not exceeded.
- (2) You must make sure the descent device manufacturer's specifications for rope diameter and construction are followed.
- (3) You must make sure the rope is rigged through the descent device for a controlled rate of descent.
- (4) You must make sure the attachment point on the descent device is one piece with no gates or openings.
- (5) You must make sure the descent device will remain stationary when positive action is taken.

**WAC 296-878-099 Definitions.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-099, filed 04/22/14, effective 07/01/14.]

**WAC 296-878-100 Scope.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-100, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-100, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-10005 Summary.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-10005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, 49.17.060. 07-03-163, § 296-878-10005, filed 1/24/07, effective 4/1/07; 02-22-027, § 296-878-10005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-120 Building surfaces and pictures.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-120, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-120, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-12005 Make sure building surfaces and fixtures are safe to use.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-12005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-12005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-130 Inspection procedures.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-130, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-130, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-13005 Inspect the area to be cleaned.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-13005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-13005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-13010 Inspect window-cleaning equipment before use.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-13010, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-13010, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-140 Develop site-specific service and emergency plans.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-140, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-140, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-14005 Develop a site-specific service and emergency recovery plan for window-cleaning operations.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-14005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-14005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-150 Equipment.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-150, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-150, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-15005 Select and use appropriate equipment.**

[Statutory Authority: RCW 49.17.010, .040, .050, and .060. 16-23-141 (Order 16-26), § 296-878-15005, filed 11/22/16, effective 12/23/16. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-15005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-15005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-15015 Select appropriate rope for suspended equipment.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-15015, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-15015, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-15020 Select appropriate carabiners.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-15020, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-15020, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-15025 Use fall protection equipment.**

[Statutory Authority: RCW 49.17.010, .040, .050, and .060. 20-12-091 (Order 19-05) § 296-878-15025, filed 06/02/2020, effective 10/01/2020. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-15025, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-15025, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-160 Warning signs and barricades.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-160, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-160, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-16005 Provide warning signs and barricades when suspended equipment is used.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-16005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-16005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-700 Powerline clearances.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-170, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-170, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-17005 Maintain clearance between window cleaners and power lines.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-17005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-17005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-180 Window-cleaners' belts and anchors.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-180, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-180, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-18005 Select appropriate window-cleaners' belts and anchors.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-18005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-18005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-18010 Inspect the anchors you plan to use for window cleaning.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-18010 filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-18010, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-18015 Use window-cleaners' belts safely.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-18015, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-18015, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-18020 Move safely on the outside of buildings.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-18020, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-18020, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-190 Boatswains' chairs.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-190, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-190, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-19005 Select appropriate boatswains' chairs.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-19005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-19005, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-19010 Safely use boatswains' chairs rigged with a block and tackle.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-19010, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-19010, filed 10/28/02, effective 1/1/03.]

**WAC 296-878-200 Rope descent systems.**

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-200, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-200, filed 10/28/02, effective 1/1/03.]

***WAC 296-878-20005 Select appropriate rope descent systems.***

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-20005, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-20005, filed 10/28/02, effective 1/1/03.]

***WAC 296-878-20010 Safely use rope descent systems.***

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-20010, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, 49.17.060. 10-08-069, § 296-878-20010, filed 4/6/10, effective 6/1/10; 02-22-027, § 296-878-20010, filed 10/28/02, effective 1/1/03.]

***WAC 296-878-20015 Safely use rope descent devices.***

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050 and 49.17.060. 14-09-095 (Order 13-10) § 296-878-20015, filed 04/22/14, effective 07/01/14. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, and 49.17.060. 02-22-027, § 296-878-20015, filed 10/28/02, effective 1/1/03.]